

Tripp Lite Estimated Battery Runtime at Various Loads
 Model: SMART5000XFMRLX

	SMART5000XFMRLX Alone	+ 1 BP48V60RT3U	+ 2 BP48V60RT3U	+ 3 BP48V60RT3U	+ 4 BP48V60RT3U	+ 5 BP48V60RT3U	+ 6 BP48V60RT3U	+ 7 BP48V60RT3U	+ 8 BP48V60RT3U	+ 9 BP48V60RT3U	+ 10 BP48V60RT3U
MaxWatts	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes
35	690	881	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
70	620	856	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
105	567	831	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
140	513	806	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
175	371	781	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
210	324	756	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
245	261	724	979	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
280	227	684	899	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
315	202	576	819	1000+	1000+	1000+	1000+	1000+	1000+	1000+	1000+
350	173	494	741	921	1000+	1000+	1000+	1000+	1000+	1000+	1000+
420	140	432	741	851	1000+	1000+	1000+	1000+	1000+	1000+	1000+
490	122	348	624	770	927	1000+	1000+	1000+	1000+	1000+	1000+
560	104	302	536	702	857	1000+	1000+	1000+	1000+	1000+	1000+
640	94	269	468	648	787	962	1000+	1000+	1000+	1000+	1000+
700	83	230	416	556	718	882	1000+	1000+	1000+	1000+	1000+
800	77	221	377	486	662	798	982	1000+	1000+	1000+	1000+
840	69	187	328	464	607	728	891	1000+	1000+	1000+	1000+
910	59	178	291	432	569	672	806	972	1000+	1000+	1000+
1000	56	163	265	392	497	616	735	898	962	1000+	1000+
1050	52	154	250	340	475	577	679	812	903	1000+	1000+
1120	47	139	239	331	442	549	622	741	860	964	1000+
1200	44	130	224	324	400	504	592	684	817	907	1000+
1260	43	125	203	302	373	482	570	627	745	864	968
1330	40	115	192	275	348	448	554	684	688	821	910
1400	38	110	182	259	339	420	509	587	631	749	823
1470	36	107	174	252	323	413	491	543	610	724	792
1540	34	103	166	248	309	406	453	513	590	691	751
1600	32	97	159	226	294	379	426	505	568	666	723
1680	31	91	151	211	282	353	410	490	562	634	693
1750	29	86	146	205	272	329	379	471	537	616	659
1820	28	80	140	200	265	314	356	456	516	593	636
1890	27	78	135	191	259	301	351	431	489	559	614
1960	26	74	127	184	254	286	347	413	459	518	595
2030	23	72	124	178	232	278	343	397	447	511	559
2100	22	69	120	173	215	269	339	359	430	495	520
2170	22	67	117	167	210	263	328	354	422	482	508
2250	21	63	114	157	204	258	317	350	416	461	497
2310	20	60	111	151	201	250	302	346	399	438	478
2400	20	59	107	146	193	241	289	342	361	418	462
2450	19	58	104	143	191	229	280	329	359	405	444
2520	19	57	99	140	188	218	271	319	353	389	432
2590	18	54	95	137	182	212	265	304	349	378	424
2660	17	53	90	130	177	206	259	291	346	363	418
2730	17	52	88	126	174	203	248	283	334	357	405
2800	17	50	85	122	171	195	243	276	323	353	388
2870	16	49	83	121	160	193	231	272	307	349	373
2940	16	47	81	118	155	190	220	266	294	346	363
3010	16	46	79	117	151	184	216	264	290	334	357
3080	16	45	77	116	144	179	209	262	284	323	257
3150	15	44	76	110	139	177	205	251	282	309	349
3220	15	42	73	105	135	173	197	245	276	303	346
3290	14	42	71	104	134	169	195	234	273	300	334
3360	13	41	69	103	132	162	192	222	265	294	323
3430	13	40	68	99	130	159	189	217	261	286	311

Tripp Lite Estimated Battery Runtime at Various Loads
 Model: SMART5000XFMRL

	SMART5000XFMRL Alone + 1 BP48V60RT3U + 2 BP48V60RT3U + 3 BP48V60RT3U + 4 BP48V60RT3U + 5 BP48V60RT3U + 6 BP48V60RT3U + 7 BP48V60RT3U + 8 BP48V60RT3U + 9 BP48V60RT3U + 10 BP48V60RT3U											
MaxWatts	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes	Minutes
3500	12	39	67	96	127	156	175	211	255	276	303	
3570	11	38	65	95	126	153	173	209	248	274	300	
3640	11	38	64	93	124	149	169	200	242	272	296	
3710	10	37	62	91	122	145	167	205	236	269	286	

The policy of Tripp Lite is one of continuous improvement.
 Specifications are subject to change without notice.



1111 West 35th Street, Chicago, IL 60609 U.S.A. (773) 869-1234 www.tripplite.com