

## SLK-102-TP-FL

CLEANABLE SEALED MEDICAL KEYBOARD WITH TOUCHPAD



Designed for the infection control challenges of today's healthcare environment, the SlimKey-MD™ SLK-102-TP-FL medical keyboard is ideal for use in an array of clinical settings. It is manufactured with an integrated GlidePoint™ touchpad pointing device and red LED backlit keys. Featuring a sealed industrial silicone keypad and low-profile keys, the SlimKey-MD™ SLK-102-TP-FL is easily disinfected using any hospital cleaning agent. Other standard features include 12 function keys and an oversized numeric pad. SlimKey-MD™ medical keyboards are compatible with germicidal sprays and wipes, making them ideal for use in ORs, patient rooms, on carts and at nursing stations. Features: Cleanable, Liquidproof Design Integrated 10-Key Numeric Pad Integrated Backlighting Low-profile keys for easy cleaning USB configurations available

### Product Code SLK-102-TP-FL

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10' straight (3 m)
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.040 in. (1mm) ACTUATION FORCE: 4.76 oz. +/- 1.06 oz. (135g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	USB: 210mA@5V (from CPU port)
FLAMMABILITY	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
COMPATIBILITY	USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (+32F to +140F)
WEIGHT	1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	14.85" x 5.87" x 0.86" (w-h-d) 377.2mm x 149.1mm x 21.9mm