



Rack PDU, Basic, Zero U, 30A, 120V, (24) 5-20

AP7532

Overview

Lead time Usually in Stock

Main

Colour	Black	
product or component type	PDU	
PDU type	Basic	
Cord length	10 ft (3.05 m)	
Number of cables	1	
provided equipment	Installation guide Rack mounting brackets Toolless mounting kit	

Complementary

Input Voltage	100 V 120 V
Height	63.7 in (161.9 cm)
Width	2.2 in (5.6 cm)
Output Voltage	120 V
Depth	1.7 in (4.4 cm)
net weight	12.28 lb(US) (5.57 kg)
mounting location	Side
Mounting preference	No preference
Input Plug Type	NEMA L5-30P
mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
[In] rated current	24 A
Input current limits	30 A
Load capacity	2880 VA
Network frequency	50/60 Hz
Outlet type and quantity	24 NEMA 5-20R

Environment

Product certifications	cUL listed UL listed	
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1	
Ambient air temperature for operation	32.0000000000113.0000000000 °F (045 °C)	
Relative humidity	095 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-13.0000000000149.0000000000 °F (-2565 °C)	
Storage Relative Humidity	095 %	
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	5.0000000000 in (12.7 cm)
Package 1 Length	6.0 in (15.2 cm)
Package 1 Weight	14.29 lb(US) (6.48 kg)

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

 \bigcirc

Energy Efficient Product



Take-Back Program Available

Well-being performance



Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information