<section-header>

DATASHEET / BROCHURE



The EB-PU2216B is a high lumens 3LCD projector that's ultralightweight and compact.

The EB-PU2216B offers users significant advantages including much reduced size and weight, easier installation and set-up, simplified maintenance and great image quality. This ultra-lightweight, compact laser projector has been designed for use in large auditoriums, live events, concerts, conference rooms where it delivers high-impact immersive experiences.

Compact and lightweight

The reduced weight and size means the projector is easier to store, transport and install, saving on warehouse space as well as labour and delivery costs.

Outstanding image quality

This high lumens, 3LCD projector offers WUXGA resolution with 4K enhancement and HDR for rich textures and sharper images.

Flexibility

The EB-PU2216B's functionality enables simple installation, stacking, lens flexibility and control. It includes in-built processing for PC-free stacking which means two supported projectors can be stacked to double the brightness without the need for external computerware.

Reliability

Includes improved dustproofing as the hermetically sealed optical engine, and laser light source unit, prevent dust contamination to ensure enhanced durability.

KEY FEATURES

- Ultra-lightweight and compact Easy to store, transport and install
- Stunning image displays 16,000lm, 4K Enhancement technology, WUXGA resolution
- Easy to use Simple installation, stacking, lens flexibility and control
- Fit-and-forget reliability Enhanced dustproof construction. IP5x certified
- Environmental benefits Lower power consumption, reduced packaging, reduced weight





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology	
LCD Panel	1.03 inch with C2 Fine	
IMAGE		
Color Light Output	16,000 Lumen- 11,200 Lumen (economy) In accordance with IDMS15.4	
White Light Output	16,000 Lumen - 11,200 Lumen (economy) In accordance with ISO 21118:2020	
Resolution	WUXGA, 1920 x 1200, 16:10	
High Definition	4K enhancement	
Aspect Ratio	16:10	
Contrast Ratio	Over 2,500,000 : 1	
Native Contrast	2,000 : 1	
Light source	Laser	
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco	
Colour Video Processing	10 Bits	
Colour Reproduction	Upto 1.07 billion colours	
OPTICAL		
Throw Ratio	0.35 - 7.41:1	
Zoom	Motorized, Factor: 1 - 1.6	
Lens	varies by lens	
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %, varies by lens	
Lens position memory	10 positions	
Screen Size	60 inches - 1,000 inches, varies by lens	
Projection Distance Wide)varies by lens	
Projection Distance Tele		
Projection Lens F Number)varies by lens	
Projection Lens Focal Length	varies by lens	
Projection Lens Focus	Varies by lens Motorized	
Interchangeable Lens	Yes	
Standard Lens	Not included	
	Not included	
CONNECTIVITY		
Interfaces	USB 2.0 Type A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet Interface (1000 Base-	
	T/ 100-Base TX/ 10-Base-T), VGA in, DVI in, HDMI in, HDBaseT, Stereo mini jack audio out, 3G-	
	SDI Input, 3G-SDI Output, Wireless LAN IEEE 802.11a/b/g/n (optional)	
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink	
ADVANCED FEATURES		
Security	Kensington lock, Security bar, Password lock, Wireless LAN unit lock, Wireless LAN security,	
	Password protection	
Other features	4K enhancement, Auto Power On, Auto source search, Direct Power on/off, Edge Blending,	
	Lens position memory, Long light source life, OSD copy function, Power on button, Quick	
	Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web	
	Remote, iProjection App	
Video Color Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709	
Projector control	via: AMX, Crestron, Extron	
•		

EB-PU2216B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

wananty	Optional warranty extension available	
OTHER Warranty	36 months Carry in	
Colour	Black	
Positioning	Ceiling Mounted, Desktop, Flying Frame	
Options	Ceiling mount, Wireless LAN unit	
	Management, Epson Projector Professional Tool	
Included Software Content DIY App, iProjection, Epson Projector Content Manager, Epson Projector		
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	
Supported Temperature	Storage -10° C - 60° C	
Noise Level	Normal: 38 dB (A) - Economy: 34 dB (A)	
Product weight	24.2 kg	
Product dimensions	586 x 492 x 218 mm (Width x Depth x Height)	
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz	
Heat Dissipation	3,682 BTU/hour (max)	
	in JBMS-84 902 Watt	
Power consumption	1,083 Watt, 773 Watt (economy), 0.4 Watt (standby), On mode power consumption as defined	
GENERAL		

EB-PU2216B

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User manual
- Lens connector cap
- Warranty document



OPTIONAL ACCESSORIES

- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Camera Unit ELPEC01 V12HA46010
- Ceiling Mount ELPMB68
- V12H006AE0
- Extension Pole ELPMB70 For ELPMB68 V12H006AG0
- Portrait Adaptor ELPMB69 For ELPMB68 V12H006AF0
- Truss Adaptor ELPMB71 For ELPMB68 V12H006AH0

OPTIONAL LENSES

- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLU03S L & G Series ST off axis 1 V12H004UA3
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLW08 Wide throw
- V12H004W08 • Lens - ELPLX02S - UST lens
- V12H004X0B • Lens - ELPLX02WS - UST Lens

V12H004Y0B

LOGISTICS INFORMATION

ѕки	V11HA67840
EAN code	8715946703237
Country of Origin	China



For more information please contact: Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

Web: www.epson.co.uk www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2022-03-23

EB-PU2216B

