

		Reolink Innovation Limited		TM4G4MS2M64-UK	
Picture					
Camera	Video & Audio	Image Sensor		1/3"CMOS Sensor	
		Video Resolution		Up To: 2560 x 1440 (4.0 Megapixels) at 15 frames/sec	
		Lens		f=2.8mm@ F=1.6 , f=8mm@ F=1.6	
		Video Format		H.264, H.265	
		Field of View		Horizontal : 96°-38°	
				Vertical : 55°-21°	
		Zoom Mode		6X hybrid zoom	
		Day & Night		IR-cut filter with auto-switching	
		Infrared Night Vision		Up to 15 Meters (50ft)(LED: 2pcs/850nm)	
		Color Night Vision		Spotlig ht: 1pcs/6500K/450Lumens	
	Audio		Two-way Audio		
	Power	Battery		10400mAh rechargeable battery (Battery life varies based on settings, usage& temperature)	
		Solar		Reolink Solar Panel 2	
		DC Power		5V/2A	
	Interface	Power		USB Type-C port	
		System		Reset Button	
		Storage		MicroSD card slot (Max . 128GB) (Included 64GB microSD Card)	
		Network		Nano SIM card slot	
		Audio		Built-in Microphone and Speaker	
	Pan&Tilt	Pan &Tilt		Pan: 355°, Tilt: 0°~90°; (Speed can be set)	
		Preset		32	
		Auto Tracking		Support	
	3G/4G	Frequency Bands	Europe	LTE FDD: B1/B3/B7/B8/B20/B28A	
				WCDMA: B1/B8	
			America	LTE FDD: B2/B4/B12	
				WCDMA: B2/B4/B5	
			Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28	
				LTE TDD: B40	
		Transmission Data		WCDMA: B1/B2/B5/B8	
				LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)	
			LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)		
			HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)		
			UMTS: Max 384Kbps(DL), Max 384Kbps(UL)		
	Software Features	Frame Rate		Main Stream: 10fps - 15fps	
				Sub St ream: 10fps - 15fps	
		Code Rate		Main Stream: 1024Kbps -4096Kbps	
				Sub Stream: 64Kbps -512Kbps	
		OS Supported		PC: Windows, Mac OS; Smartphone: iOS, Android	
		Smart Alarm		PIR Detection/ HumanDetection/VehicleDetection/ Pet Detection	
		Record Mode		Motion Triggered Recording	
		Protocols & Standards		SSL, TCP/ IP, UDP, UPNP, SMTP, NTP, P2P	
	Working Environment	Maximal User Access		Support up to 12 simultaneous video streams (10 substreams& 2 mainstreams)	
		Work with		Google Assistant, Reolink C loud	
		Temperature		Operating Temperature: - 10°C~-+55°C (14°F~131°F)	
		Humidity		Operating Humidity: 20% ~ 85%	
Waterproof		Support			
Size & Weight	Dimension		228.2*147*129mm		
	Weight		1.4KG		
Warranty	Limited Warranty		2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us		
Solar Panel 2	Electrical Parameters	Max. Voltage		6.0V	
		Max. Current		960mA	
		Max. Power		5.8W	
	Size & Weight	Dimensions		210.6 x 174.6 x 15.4 (mm)	
		Cable Length		4 meters	
		Weight		360g	
		Interface		USB Type-C Port	
	Other	Working Temperature		-10°C~-+55°C (14°F~131°F)	
		Working Humidity		10%~90%	
Waterproof		IP65			