

## Yield Reporting Form

# HP LaserJet Pro M118-M119 and HP LaserJet Pro MFP M148-M149 cartridge model Introductory HP CF294A

## Declared ISO yield

<b>Toner cartridge yield</b> <b>Average cartridge yield 1,000 standard pages<sup>1</sup></b> Declared yield value in accordance with ISO/IEC 19752 based on continuous printing	
---	--

Average <sup>1</sup>	1,093
Standard Dev.	30
90% lower confidence limit <sup>1</sup>	1,083

Test date: beginning	2/18/2019
Test dates: ending	2/20/2019
Number of cartridges used in testing	24
Number of cartridges used in calculations	24
Type of cartridge	Introductory HP CF294A
Shake procedure used?	No
Print mode	Continuous
Job size	100 pages per job
Number of engines used in testing	8
Media	Double A 80g
Paper size	A4
Paper feed orientation	Short edge
Computer model	HP LP2065
Operating system	Microsoft Windows 10
Application software	Adobe Reader 9
Print driver version	44.3.2667
Connection type	network
Test page version*	Version 4.0 pdf
Power on/off every day	No

Engine serial numbers:	Engine Firmware Version:
VNF3K03916	20180726
VNF3K03298	20180726
VNF3K03914	20180726
VNF3K05393	20180726
VNC4701630	20180726
VNC4701680	20180726
VNC4701641	20180726
VNC4701640	20180726

\*filename: Download\_Free\_\_\_19752\_Test\_Chart\_\_\_pdf from ISO SC28 website

## Cartridge testing data

Test environmental limits:	Temperature	Humidity
	°C	%RH
Max running average	23.2	52
Min running average	23.0	49
Average	23.0	51

CF294A-Starter		HP LJ Pro M118dw and M148fdw	
Cartridge	Lot Code	Engine SerNo	Cartridge Yield
CF294A_Intro_1	9A08T1Ba	VNF3K03916	1118
CF294A_Intro_2	9A08T1Ba	VNF3K03298	1075
CF294A_Intro_3	9A08T1Ba	VNF3K03914	1125
CF294A_Intro_4	9A08T1Ba	VNF3K05393	1133
CF294A_Intro_5	9A08T1Ba	VNC4701630	1065
CF294A_Intro_6	9A08T1Ba	VNC4701680	1038
CF294A_Intro_7	9A08T1Ba	VNC4701641	1075
CF294A_Intro_8	9A08T1Ba	VNC4701640	1098
CF294A_Intro_9	9A11T1Ba	VNF3K03916	1125
CF294A_Intro_10	9A11T1Ba	VNF3K03298	1125
CF294A_Intro_11	9A11T1Ba	VNF3K03914	1125
CF294A_Intro_12	9A11T1Ba	VNF3K05393	1125
CF294A_Intro_13	9A11T1Ba	VNC4701630	1046
CF294A_Intro_14	9A11T1Ba	VNC4701680	1107
CF294A_Intro_15	9A11T1Ba	VNC4701641	1100
CF294A_Intro_16	9A11T1Ba	VNC4701640	1125
CF294A_Intro_17	9A15T1Ba	VNF3K03916	1043
CF294A_Intro_18	9A15T1Ba	VNF3K03298	1084
CF294A_Intro_19	9A15T1Ba	VNF3K03914	1125
CF294A_Intro_20	9A15T1Ba	VNF3K05393	1089
CF294A_Intro_21	9A15T1Ba	VNC4701630	1054
CF294A_Intro_22	9A15T1Ba	VNC4701680	1090
CF294A_Intro_23	9A15T1Ba	VNC4701641	1066
CF294A_Intro_24	9A15T1Ba	VNC4701640	1082

<sup>1</sup> In an ISO report two values are commonly listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information visit [www.hp.com/go/learnaboutsupplies](http://www.hp.com/go/learnaboutsupplies).