

## USB-C Multiport Video Adapter - 4-in-1 - 85W Power Delivery - Space Gray

Product ID: CDPVDHMDPDP



This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI, HDMI or Mini DisplayPort (mDP) display. It features USB Power Delivery, so you can power your laptop while outputting video using the same USB-C port.

#### **Power and Video in One Port**

This USB-C adapter supports USB Power Delivery up to 85 watts and features an additional USB-C port. You can charge your laptop using its USB-C power adapter, even while you output video. Many laptops support charging through a USB-C port with Power Delivery, check your specifications to confirm compatibility.



## **Data Sheet**

### All-in-One Video Connectivity with Travel in Mind

Carry one adapter instead of four. This versatile 4-in-1 monitor adapter lets you connect your USB-C laptop to any display. With its durable aluminum enclosure and a magnetic retainer that secures the breakout cable in place while you're not using it, the adapter is rugged enough to carry in your travel bag.

#### **Astonishing Picture Quality**

The HDMI and mDP outputs support UHD 4K resolutions, providing four times the picture quality of highdefinition 1080p. All of the outputs (HDMI, mDP, VGA, DVI) support high-definition resolutions up to 1920 x 1200. The adapter is compatible with USB-C DP Alt Mode devices.

#### **Stylish Connectivity**

The USB-C adapter has a Space Gray trim and built-in USB-C cable designed to match your Space Gray MacBook, or MacBook Pro.

CDPVDHMDPDP is backed by a StarTech.com 3-year warranty and free lifetime technical support.



## **Data Sheet**

#### Certifications, Reports and Compatibility









#### Applications

- Connect to virtually any display while traveling
- Connect a MacBook or USB-C laptop to a VGA, DVI, HDMI or mDP display
- Connect a secondary monitor to your Space Gray MacBook or USB-C laptop

#### Features

- Charge your laptop while connecting a display using just one USB-C port, with USB Power Delivery
- Maximize your video compatibility with a 4-in-1 adapter: USB-C to VGA, DVI, HDMI or Mini DisplayPort
- Space Gray trim matches your Space Gray MacBook or MacBook Pro
- Supports resource-demanding applications with UHD resolutions up to 4K 60Hz
- Maximum portability with a built-in magnetic cable manager



Hard-to-find made easy\*

	Warranty	3 Years
Hardware	Active or Passive Adapter	Active
	Adapter Style	Adapters
	AV Input	USB Type-C
	AV Output	HDMI
		DVI-D
		VGA
		Mini-DisplayPort
	Chipset ID	Parade - PS176 VIA/VLI - VL102 ITE -IT6516
Performance	Audio Specifications	HDMI or mDP output: 7.1 surround sound
	Maximum Analog Resolutions	1920 x 1200 @ 60Hz
	Maximum Digital Resolutions	4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz (HDMI)
		4096 X 2160 @ 60Hz (mDP)
	Supported Resolutions	Maximum HDMI output: 4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz
		Maximum mDP output: 4096 X 2160 @ 60Hz
		Maximum mDP output: 4096 X 2160 @ 60Hz Maximum DVI and VGA output: 1920 x 1200 @ 60Hz
	Video Revision	Maximum DVI and VGA output: 1920 x 1200 @ 60Hz
	Video Revision	<b>Maximum DVI and VGA output:</b> 1920 x 1200 @ 60Hz Lower resolutions and refresh rates may also be supported
	Video Revision Wide Screen Supported	<b>Maximum DVI and VGA output:</b> 1920 x 1200 @ 60Hz Lower resolutions and refresh rates may also be supported HDMI 2.0
Connector(s)		Maximum DVI and VGA output: 1920 x 1200 @ 60Hz Lower resolutions and refresh rates may also be supported HDMI 2.0 DisplayPort 1.2
Connector(s)	Wide Screen Supported	Maximum DVI and VGA output: 1920 x 1200 @ 60Hz Lower resolutions and refresh rates may also be supported HDMI 2.0 DisplayPort 1.2 Yes
Connector(s)	Wide Screen Supported Connector A	Maximum DVI and VGA output: 1920 x 1200 @ 60HzLower resolutions and refresh rates may also be supportedHDMI 2.0DisplayPort 1.2Yes1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
Connector(s)	Wide Screen Supported Connector A	Maximum DVI and VGA output: 1920 x 1200 @ 60HzLower resolutions and refresh rates may also be supportedHDMI 2.0DisplayPort 1.2Yes1 - USB-C (24 pin) DisplayPort Alt Mode Male Input1 - Mini-DisplayPort (20 pin) Female Output
Connector(s)	Wide Screen Supported Connector A	Maximum DVI and VGA output: 1920 x 1200 @ 60HzLower resolutions and refresh rates may also be supportedHDMI 2.0DisplayPort 1.2Yes1 - USB-C (24 pin) DisplayPort Alt Mode Male Input1 - Mini-DisplayPort (20 pin) Female Output1 - VGA (15 pin, High Density D-Sub) Female Output
Connector(s)	Wide Screen Supported Connector A	Maximum DVI and VGA output: 1920 x 1200 @ 60HzLower resolutions and refresh rates may also be supportedHDMI 2.0DisplayPort 1.2Yes1 - USB-C (24 pin) DisplayPort Alt Mode Male Input1 - Mini-DisplayPort (20 pin) Female Output1 - VGA (15 pin, High Density D-Sub) Female Output1 - DVI-I (29 pin) Female Output
Connector(s) Special Notes / Requirements	Wide Screen Supported Connector A	Maximum DVI and VGA output: 1920 x 1200 @ 60HzLower resolutions and refresh rates may also be supportedHDMI 2.0DisplayPort 1.2Yes1 - USB-C (24 pin) DisplayPort Alt Mode Male Input1 - Mini-DisplayPort (20 pin) Female Output1 - VGA (15 pin, High Density D-Sub) Female Output1 - DVI-I (29 pin) Female Output1 - HDMI (19 pin) Female Output



Hard-to-find made easy\*

## **Data Sheet**

	Power Source	Bus Powered
Environmental	Humidity	0~95% RH
	Operating Temperature	0°C to 45°C (32°F to 113°F)
	Storage Temperature	0°C to 60°C (32°F to 140°F)
Physical Characteristics	Accent Color	Black & Space Gray
	Cable Length	4 in [101 mm]
	Color	Black
	Enclosure Type	Aluminum
	Product Height	0.7 in [18 mm]
	Product Length	4.3 in [109 mm]
	Product Weight	2.8 oz [80 g]
	Product Width	2.2 in [57 mm]
Packaging Information	Shipping (Package) Weight	0.3 lb [0.1 kg]
What's in the Box	Included in Package	1 - Travel A/V Adapter

Product appearance and specifications are subject to change without notice.