HP LaserJet M9040/M9050 MFP series





Boost user productivity and enhance performance with fast A3 printing and copying. Save time and make office tasks more efficient with scan-to-email, digital sending and optional faxing, and a choice of paper-handling and finishing options.

An excellent choice for busy departments in large and medium-sized businesses, these MFPs are ideal for workgroups of 30 to 50 users who require fast (and extra fast), high volume, cost-effective printing and copying with digital sending, scanning, optional faxing, and professional finishing.

Simplify everyday office tasks and save valuable time.


The new touch-screen control panel provides an intuitive, consistent user experience across the HP lineup. Enjoy fast printing and copying at up to 40ppm (M9040 MFP¹) and up to 50 ppm (M9050 MFP¹). Save time and integrate documents into workflows with scan-to-email and additional digital sending for easy conversion of documents from paper to electronic format. Add the HP LaserJet MFP Analog Fax Accessory 300² to send and receive documents with ease.

Increase user productivity and improve performance.

Produce complex documents with a range of finishing choices: 8-bin mailbox for easy sorting/collating, stacker for up to 3,000 sheets, stapler/stacker and multi-function finisher for creating booklets. Quickly capture high quality colour images at 600x600 dpi with the dual-head colour scanner. Boost productivity and save paper with two-sided printing, copying and scanning. Extend the MFP's capabilities by adding advanced document capture, job accounting, and security solutions.

Count on these HP LaserJet MFPs to deliver a consistently reliable experience.

Get peace of mind with industry-renowned HP LaserJet reliability. Achieve consistent, trouble-free printing using the Original HP LaserJet print cartridge with Smart printing technology. Produce great-looking documents with 1200 dpi print quality. Easily order and manage supplies with HP SureSupply³. Speed up management processes with HP Web Jetadmin for remote configuration and proactive fleet management. Experience reliable sharing in large workgroups with HP Jetdirect networking.



² Fax capability is optional Please purchase separately



HP LaserJet M9040 MFP



HP Laserlet M9050 MFP

³ Programme features and availability may vary by country For more information, visit www.hp.com/learn/suresupply.

Series at a glance



HP LaserJet M9040 MFP

- Print and copy speed of up to 40 ppm
- 1200 dpi effective output quality
- 600x600dpi scan resolution
- 40 GB hard drive
- 256 MB RAM expandable up to 512 RAM
- 533 MHz processor
- third party connectivity via USB Host
- Gigabit Lan
- standard input capacity of 3100-sheets with a 100-sheet multipurpose tray; two 500-sheet input trays; 2000-sheet input tray and 100-sheet automatic document feeder
- product pictures show printer with one of the four available paper output accessories



HP LaserJet M9050 MFP

- Print and copy speed of up to 50 ppm
- 1200 dpi effective output quality
- 600x600 dpi scan resolution
- 40 GB hard drive
- 256 MB RAM expandable up to 512 RAM
- 533 MHz processor
- third party connectivity via USB Host
- Gigabit Lan
- standard input capacity of 3100-sheets with a 100-sheet multipurpose tray; two 500-sheet input trays; 2000-sheet input tray and 100-sheet automatic document feeder
- product pictures show printer with one of the four available paper output accessories

Recommended accessories



J7951G HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server



J7934G HP Jetdirect 620n Fast Ethernet Print Server



J7961G HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)



J7997G HP Jetdirect 630n Internal Print Server



C8091A HP Staple Cartridge



C8092A HP LaserJet 5000 Staple Cartridge



C9153A HP 220V Maintenance Kit (350,000 pages)



Q5693A HP LaserJet MFP 8-bin Mailbox



C8084A HP LaserJet MFP 3000-sheet Stacker



C8085A HP LaserJet MFP 3000-sheet Stapler/Stacker



C8088B HP Multifunction Finisher



Q3701A HP LaserJet MFP Analog Fax Accessory 300

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 32.5° C. Recommended operating temperature: 17.5 to 25° C. Operating humidity: 20 to 80% RH. Operating humidity recommended: 30 to 70% RH. Storage temperature: 0 to 35° C. Storage humidity: 15 to 90% RH. Noise level per ISO 9296: sound power: LwAd 7.5 B(A) (active), 5.6 B(A) (ready). Sound			
	pressure: LpAm 58 dB(A) (active), 39 dB(A) (ready)			
Certifications	CISPR 22: 1997/EN 55022: 1998 Class B, EN 61000-3-2: 2000, EN 61000-3-3: 1995, EN 55024: 1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly. Regulatory standards: Argentina (TÜV S Mark-Rs.92/98/Ds.1009/98), Australia (AS/NZ 3260), Canada (cUL-CAN/CSA C22.2 No.60950-00), China (GB4943), Czech Republic (CSN-IEC 60950-IEC 60825-1), Estonia (EEI-EN60950-IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TÜV- EN60950-IEC 60825-1), Hungary (MEEI- IEC 60950-IEC 60825-1), Japan Radio Law, Lithuania (LS- IEC 60950-IEC 60825-1), Mexico (NOM NYCE-NOM 019 SCFI), Poland (B Mark- IEC 60950-IEC60825-1), Slovakia (IEC 60950-IEC60825-1), Slov			
Warranty	One-year, next business day onsite warranty			

Ordering information



Accessories

HP LaserJet M9040 MFP (CC394A)

HP LaserJet M9040 MFP, power cord, print cartridge, printer documentation, printer software CD-ROM, control panel overlay, two standard 500-sheet input trays, 100-sheet multi-purpose tray, 2000-sheet input tray, choice of output paper handling device, automatic duplexer accessory (pre-installed), HP Jetdirect Embedded Print Server, automatic document feeder (ADF). Printer must be ordered with one out of four paper output accessories.



HP LaserJet M9050 MFP (CC395A)

HP Jetdirect 510x Print Server

HP LaserJet M9050 MFP, power cord, print cartridge, printer documentation, printer software CD-ROM, control panel overlay, two standard 500-sheet input trays, 100-sheet multi-purpose tray, 2000-sheet input tray, choice of output paper handling device, automatic duplexer accessory (pre-installed), HP Jetdirect Embedded Print Server, automatic document feeder (ADF). Printer must be ordered with one out of four paper output accessories.

Accessories, Supplies and Support

C8091A	HP Staple Cartridge				
C8092A	HP LaserJet 5000 Staple Cartridge				
C9153A	HP 220V Maintenance Kit (350,000 pages)				
Q5693A	HP LaserJet MFP 8-bin Mailbox				
C8084A	HP LaserJet MFP 3000-sheet Stacker				
C8085A	HP LaserJet MFP 3000-sheet Stapler/Stacker				
C8088B	HP Multifunction Finisher				
Q3701A	HP LaserJet MFP Analog Fax Accessory 300				
Q7719A	HP 256 MB 100-pin DDR DIMM				
J7989G	HP High Performance Serial ATA EIO Hard Disk				
J7972G	HP 1284B Parallel EIO Card				
Supplies					
C8543X	HP LaserJet C8543X Black Print Cartridge with Smart Printing Technology 38,000 standard pages in accordance with ISO/IEC				
	19752				
Connectivi					
Connectivi J7951G					
	HP Jetdirect ew2400 802.11g Wireless and Fast				
J7951G	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server				
J7951G J7934G	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server HP Jetdirect 620n Fast Ethernet Print Server HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO,				

H7700	A/E HP Care Pack, Next Business Day On site Response, 3
years	
U2019	E HP Care Pack, Same Business Day On site Response,
4-Hour	, 13x5, 3 years
UJ5281 years	E HP Care Pack, Next Business Day On site Response, 4
	E HP Care Pack, Next Business Day On site Response, 5
Ú2020	PE HP Care Pack, Post Warranty, Next Business Day On site ise, 1 year
U2052	PE HP Care Pack, Post Warranty Same Business Day On sit- ise, 4-Hour, 13x5, 1 year
	o offers Managed Print Services: a scalable solution
	ng everything from imaging and printing devices and toner
cartrid	ges, to installation, management, maintenance, and suppor re information visit: www.hp.com/go/printservices.
	complete list of supplies, accessories and services, please http://www.hp.com
	rkflow, device management and other solutions, please visit obal Solutions catalog: www.hp.com/go/gsc

J7983G

10/100TX)



Technical specifications

Print technology	Monochrome Laser						
Print speed	First page out black: < 9.5 sec (from ready)						
	All printed pages originate from	9050mfp with a High-Capacity Input (HCI) Tray	4.				
Processor	533 MHz. MIPS 20KC Processo	or (Unity ASIC)					
Memory	384 MB. Expandable to 512 N	AB replacing 128 MB (DIMM Slot 2) with	256 MB. No open slot available. Hard Disk C	Capacity: Standard, 40 GB			
Print	Quality Resolution Enhancement technology (REt)						
	Resolution	HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi					
	Printer languages	HP PCL 6, HP PCL 5e, HP Postscript level 3 emulation, direct PDF printing (v 1.3) with at least 128 MB memory enabled, XHTML-Print v 0.95, HP PJL (Printe					
		Job Language), PML (Printer Management Language)					
	Economical printing Typefaces/fonts	Standard automatic two-sided printing and N-up printing (saves paper), Economode (saves toner) 80 internal TrueType fonts scalable in HP PCL and HP Postscript level 3 emulation; additional font solutions available					
	volume	71 3					
	Print margins (mm)	Top: 2.1 mm. Left: 3.2 mm. Right: 3.7	mm. Bottom: 2.9 mm				
Fax	Modem speed						
	Fax memory	Dependent upon available disk space					
	Fax resolution	Standard: 300 x 300 dpi (with optional analog fax accessory). Superfine: 300 x 300 dpi (with optional analog fax accessory). Photo: 200 x 100 dpi					
		(with optional analog fax accessory)					
_	Quick dialing	Ùp to 100					
Digital sending	File formats	PDF, JPEG, TIFF, MTIFF					
	Features	Standard: Scan to e-mail, Desktop folder, Network folder. LDAP addressing. User Authentication: PIN, LDAP/Active Directory with Kerberos. Optional: Sen					
			cation, FTP, workflow, OCR. Advanced user aut	hentication solutions.			
Scan	Туре	Flatbed, ADF. Colour scanning: Yes					
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up	to 600 dpi				
	Bit depth	30-bit					
	Grey scale levels Scannable area	256 Maximum media size: 279 x 432 mm					
			2 (A4) Rottom: 4 2 (A4)				
		Margins for scanned items Left: 4.2 (A4). Top: 4.2 (A4). Right: 4.2 (A4). Bottom: 4.2 (A4)					
Сору	Copy resolution Multiple copies	Up to 600 x 600 dpi Up to 999					
	Reduce/enlarge	25 to 400%					
Media handling	Input:	Capacity	Weight	Size			
media hahaling	Tray 1	sheets: 100, envelopes: 10	64 to 227 g/m²	A3 (ISO), A4 (ISO), A5 (ISO), B4 (JIS), B5 (JIS),			
	,	, ,	<u>5</u> ,	letter, legal, executive, tabloid, JPostD, 98 x 191 to			
				312 x 470 mm			
	Tray 2	sheets: 500	64 to 199 g/m²	A3 (ISO), A4 (ISO), A4-R (ISO), A5 (ISO) (except			
				tray 4), B4 (JIS), B5 (JIS), letter, letter-R, legal,			
				executive, tabloid, 148 x 210 to 297 x 432 mm			
	Tray 3	sheets: 500	64 to 199 g/m²	A3 (ISO), A4 (ISO), A4-R (ISO), A5 (ISO) (except			
				tray 4), B4 (JIS), B5 (JIS), letter, letter-R, legal,			
	ADF			executive, tabloid, 148 x 210 to 297 x 432 mm			
	Output: B5 (IIS), Executive, legal, letter, tabloid Output: Sheets: Up to 3000 (with stacker or stapler/stacker). Envelopes: Up to 10						
	Output. Duplex printing: Automatic (standard)						
Media types			rough) labels cardstock transparencies				
Interface and connectivity	Paper (bond, colour, letterhead, plain, preprinted, prepunched, recycled, rough), labels, cardstock, transparencies Hi-Speed USB (compatible with USB 2.0 specifications), HP Jetdirect Gigabit Ethernet Embedded Print Server, 1 open EIO slot, Jetlink connection for paper handling device, host USB port						
,	(compatible with USB 2.0 specifications) for additional functionality, I foreign Interface Harms (FIH). Optional: HP Jetdirect Element purposes to so, Jennik continection to puper instances and so so point (compatible with USB 2.0 specifications) for additional functionality, I foreign Interface Harms (FIH). Optional: HP Jetdirect Element print servers, HP Jetdirect external print servers, and the print servers of the print s						
	Fast Infrared connect (FIR): Connectivity: HP Jetdirect en 1700 USB 2.0 Print Server J7988G, HP Jetdirect en 3700 USB 2.0 Print Server J7942G, HP Jetdirect ew 2400 Wireless USB 2.0 Print Server J7942G, HP Jetdirect ew						
	Server J7951G, HP Jetdirect 510x Parallel Print Server J7983G, HP Jetdirect 300x Parallel Print Server J3263G, HP EIO 1284 adapter J7972G, HP Jetdirect 620n EIO print server J7934G,						
	HP Jetdirect 635n EIO Print Ser	ver J7961G, HP Jetdirect 630n EIO Print	Server J7997G, HP Jetdirect 690n Wireless pri	nt server J8007G			
Operating systems compatibility	Microsoft® Windows® 2000;	XP Home, XP Professional; Windows Visto	a® Ready; OS/2 v3.0 or higher; Mac OS X v1	0.2.8, v10.3, v10.4 or higher; Linux; AutoCAD. Current printer			
	drivers and software for all supported operating systems are available at http://www.hp.com/support. Depending on the configuration of Windows-driven computers, the installation						
	program for the printer software automatically checks the computer for Internet access to obtain the latest software						
Network operating systems compatibility	Microsoft® Windows® 2000, Server 2003, XP, 2003 64-bit, XP 64-bit; Windows Vista®, Windows Vista® 64-bit (for Microsoft® IPv6 compatible with Microsoft® Windows® 2003, XP,						
	and Windows Vista®); Novell® 5.1 and higher Mac OS X v10.2, v10.3, v10.4 and higher, RED HAT Linux 7.x and higher, SUSE Linux 8.x and higher, HPUX 10.20, 11.x, 11.i; Solaris®						
	2.5 and higher (SPARC® systems only); IBM® AIX 3.2.5 and higher; MPE-iX; Citrix® MetaFrame Server; Windows® Terminal Services						
Minimum system requirements				l: 233 MHz processor, 64 MB RAM; 180 MB of free hard disk space			
	for Windows®, CD-ROM drive or Internet connection. Mac OS X v10.2.8, v10.3, v10.4 or higher with 128 MB RAM, CD-ROM, 160 MB of free hard disk space. For Mac OS v10.4 and						
		re Processor Macs are supported					
Standard software	Print drivers and installation software on CD-ROM: remote hardcopy management, HP disk management utility, HP common installer, HP Internet installer, HP disk image utility, HP common						
	, ,			disk image utility for Macintosh, HP common drivers Macintosh			
	client, PPDS/PDES for Macintosh, HP LaserJet utility for Macintosh, fonts for Macintosh, help files for Macintosh (English only)						
Control panel	3 light-emitting device (LED) indicator lights, 10-key numeric pad, graphical touchscreen display (193 x 72 mm)						
n	Requirements: Input voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consumption: 1070 watts maximum (active/printing),						
Power	1120 watts maximum (scan), 340 watts maximum (ready), 179 watts maximum (sleep), 3 watts maximum (off); Typical Electricity Consumption (TEC): 18.9 kWh/Week*						
rower	Out of package: With 8-bin mailbox: 1092 x 838 x 1219 mm, with stacker: 1168 x 787 by 1194 mm, with stapler/stacker: 1168 x 787 x 1194 mm, with multifunction finisher: 1295 x						
Dimensions (w x d x h)		iilbox: 1092 x 838 x 1219 mm, with sta	cker: 1168 x 787 by 1194 mm, with stapler/st	acker: 1108 x /8/ x 1194 mm, with multifunction finisher: 1295 x			
	Out of package: With 8-bin mo	silbox: 1092 x 838 x 1219 mm, with stad '8 x 914 x 1448 mm (without finishing of		acker: 1108 x 787 x 1194 mm, with multifunction finisher: 1295 x			
	Out of package: With 8-bin mo 787 x 1194 mm. Packaged: 97		utput solution)	acker: 1108 x 787 x 1174 mm, with multifunction tinisher: 1295 x			

http://www.hp.com/uk













