

# Product data sheet

Specifications



## APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V

P11VNT3

⚠ Discontinued on: Feb 14, 2024

⚠ To be end-of-service on: Sep 30, 2024

⚠ To be discontinued

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	8 ft (2.4 m)
Number of cables	1
Provided equipment	6ft Network cable Coaxial cable Cord management straps Telephone Cable User Manual

### Physical

Color	Black
Height	1.6 in (4 cm)
Width	4.7 in (11.9 cm)
Depth	11.9 in (30.2 cm)
Net Weight	2.34 lb(US) (1.06 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

### Input

Input Frequency	50/60 Hz
Switching current capacity	15 A

### Output

Number of power socket outlets	11
Outlet standard	NEMA 5-15R

### Conformance

UL 1449 TVSS Rating	L-N: 400 L-G: 500 N-G: 500
---------------------	----------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Product Certifications</b>	CSA NOM
<b>Standards</b>	UL 1363 UL 1449
<b>Equipment protection policy</b>	Lifetime : \$100000

## Environmental

<b>Ambient Air Temperature for Operation</b>	32...113 °F (0...45 °C)
<b>Relative Humidity</b>	0...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage Relative Humidity</b>	0...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Surge Protection and Filtering

<b>NM Surge Response Time (ns)</b>	0 ns common mode
<b>Common mode rejection</b>	70 dB
<b>Surge energy rating</b>	3020 J

## Ordering and shipping details

<b>GTIN</b>	731304249023
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	2.4 in (6 cm)
<b>Package 1 Width</b>	13.6 in (34.5 cm)
<b>Package 1 Length</b>	7.6 in (19.2 cm)
<b>Package 1 Weight</b>	2.98 lb(US) (1.35 kg)
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	15 in (381.0000000000 mm)
<b>Package 2 Width</b>	8 in (203.2 mm)
<b>Package 2 Length</b>	15 in (381.0000000000 mm)
<b>Package 2 Weight</b>	19.58 lb(US) (8.88 kg)
<b>SCC14</b>	10731304249020

## Contractual warranty

<b>Warranty</b>	Limited Lifetime
-----------------	------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

## Well-being performance

Reach Free Of Svhc

---

Mercury Free

---

Rohs Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive [Compliant with Exemptions](#)

---

Circularity Profile [End of Life Information](#)

---