# **Product data sheet**

Specification



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A, 208V, (21) C13 & (3) C19

AP8659NA3

#### **Overview**

Presentation	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Lead time	Usually in Stock

#### Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched metered outlet
Cord length	9.84 ft (3.00 m)
Provided Equipment	CAN Port Terminator Installation guide Locking input power cord Rack Mounting brackets Safety guide Serial configuration cable

### Complementary

Input Voltage	200 V 208 V 230 V
Height	72.008 in (182.9 cm)
Width	2.2 in (5.6 cm)
Output Voltage	208 V
Depth	2.008 in (5.1 cm)
Net Weight	14.93 lb(US) (6.77 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-20P
Mounting Mode	Not rack-mountable

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Rack units	0U
Mounting position	Vertical
Line Rated Current	16 A
Acceptable Input Voltage	100240 V
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19

### **Environment**

Product Certifications	UL Listed VCCI Class A VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC Part 15 class A ICES-003
Ambient Air Temperature for Operation	23140 °F (-560 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

# Ordering and shipping details

GTIN 731304299523

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.2 in (203.8 cm)
Package 1 Width	4.6 in (11.7 cm)
Package 1 Length	6.4 in (16.2 cm)
Package 1 Weight	19.95 lb(US) (9.05 kg)

# **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

#### Resource performance

Energy Efficient Product

Take-Back Program Available

### Well-being performance

Lead Free

Mercury Free

Rohs Exemption Information Yes

### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information