22" (21.5" viewable) Full HD 10-Point Touch Display



Frameless SuperClear® IPS-Type Panel & Versatile Connectivity

TD2230



Laid flat or angled for customized comfort, this display delivers touchscreen versatility to the max. Offering fantastic flexibility for retail, education, or business settings, the ViewSonic® TD2230 is a 22" (21.5" viewable) Full HD display with 10-point multi-touch functionality. Delivering adjustable positioning, wide-angle viewing, and a durable design, the TD2230 has everything to accommodate your unique needs. Adding even more convenience, cross-compatibility with a wide range of operating systems includes Windows® 10, and certain Android™ and Linux® versions. With a sleek edge-to-edge screen and frameless bezel, this intuitive touchscreen performs like your favorite tablet or smartphone to deliver a highly accurate, ultra-responsive touch experience ideal for interactivity in public environments, kiosk and wayfinding applications, classroom settings, and more.

Key Features:

10-point projected capacitive touch
SuperClear IPS-type panel technology
Frameless design
Versatile connectivity

Durable, scratch-resistant screen

Designed for:

Retail

Education

Business

22" (21.5" viewable) Full HD 10-Point Touch Display



TD2230

VESA® Compatible Wall Mount (100 x 100mm)



Specifications

| • | | |
|---------------|--|---|
| LCD PANEL | Type Display Area Optimum Resolution Brightness Contrast Ratio Dynamic Contrast Ratio Viewing Angles Colors Response Time Backlight Backlight Life Panel Surface | ADS Type, a-si TFT Active Matrix LCD 18.8" horizontal x 10.6" vertical; 21.5" diagonal 1920x1080 250 cd/m² (typ.) 1000:1 (typ.) 50M:1 178° horizontal, 178° vertical 16.7M (6bit + A-FRC) 7ms (GtG) White-light LED 30,000 hours (min.) Anti-glare, hard-coating (7H) |
| VIDEO INPUT | Digital Analog Frequency Sync | DisplayPort, HDMI VGA Fh: 24~82kHz, Fv: 50~76Hz Separate Sync, Composite Sync, Sync on Green, TMDS, PCI-E |
| AUDIO OUTPUT | Speakers | 3-watt (x2) |
| COMPATIBILITY | PC Mac® | Up to 1920x1080 non-interlaced Up to 1920x1080 |
| CONNECTOR | Video In Audio In Headphones USB 3.0 Power | DisplayPort, HDMI, VGA 3.5mm mini jack 3.5mm mini jack Type A x2 / Type B x1 DC 19V/2.37A |
| CONTROLS | Front Panel Buttons OSD | 1, 2, Down, Up, Power Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |

| ERGONOMICS | Tilt | 20°~70°, lay flat |
|---------------------------|--|---|
| POWER | Voltage Consumption Optimize Conserve | AC 100–240V (universal), 50 / 60Hz 25W (typ.) / 28W (max.) 22W (typ.) 19W (typ.) |
| OPERATING CONDITIONS | Temperature Humidity | 32–104° F (0–40° C) 20–90% (non-condensing) |
| DIMENSIONS (W x H x D) | Physical with Stand Physical without Stand Packaging | 19.3 x 11.8 x 5.1 in. / 490.3 x 298.8 x 129.7 mm 19.3 x 11.8 x 1.9 in. / 490.3 x 298.8 x 47.3 mm 21.7 x 14.6 x 4.5 in. / 550 x 371 x 114 mm |
| WEIGHT | Net with Stand Net without Stand Gross | 7.9 lb. / 3.6 kg 7.9 lb. / 3.6 kg 10.4 lb. / 4.7 kg |
| WALL MOUNT | VESA compatible | 100 x 100 mm |
| REGULATIONS | | cULus, FCC-B w/ICES003, EPEAT Silver, UL-MX-CoC, Mexico Energy |
| RECYCLE/DISPOSAL | | Please dispose of in accordance with local, state, or federal laws |
| WARRANTY | | Three-year limited warranty on parts, labor and backlight |
| | | |

Optional Accessories

| HDMI to DVI cable 6FT | CB-00008948 |
|---|---------------|
| Mini DisplayPort to DisplayPort cable 6FT | CB-00010958 |
| DisplayPort to DisplayPort cable 30FT | CB-00010684 |
| Display Port Male to VGA Female Adapter (Single Link) | CB-00011486 |
| DisplayPort to DisplayPort cable 6FT | CB-00010555 |
| DisplayPort to DVI Adapter | LCD-CABLE-001 |
| Desktop Display Wall Mount Kit | LCD-WMK-001 |
| | |

What's in the box?

TD2230 monitor, Power cable, Power adapter, HDMI cable, USB 3.0 cable, Audio cable, Quick Start Guide, ViewSonic Wizard CD













