



2

One touch, two roles

Serves as a meeting room controller for managing in-room video calls or a scheduling display showing room availability outside the door.



Hear everyone clearly

Extend audio pickup in the room for clearer conversations.



Your rooms, your rules

Native support for Google Meet, Microsoft Teams, and Zoom, with flexibility through Neat Open and Neat Open Apps.



Stay in command from anywhere

Configure, update, and monitor your rooms through Neat Pulse.

P2

Ready for more

Powered by our next-generation P2 platform for improved performance and reliability.

Neat Pad Generation 2

As a meeting room controller and scheduling display, Neat Pad Generation 2 gives teams instant, familiar control and IT a simple, scalable way to standardize rooms across every space. Compact, reliable, and easy to deploy, it delivers a consistent experience across every room—so everything just works.

General

- 8-inch diagonal touch screen
- 1280 × 800 screen resolution
- 16:10 aspect ratio
- Anti-glare, anti-fingerprint coating
- Ambient light sensor
- Sensors for temperature, humidity, and VOC index (*)
- RGB side LED Indicators
- 3D Accelerometer
- Mounting options: wall, glass, and side
- Native support for Zoom Rooms
- Native support for Microsoft Teams Rooms on Android**
- Native support for Google Meet (room controller)
- Ultrasound-capable speakers (*)
- One integrated microphone

Size and weight

- Width: 7.90 in (200 mm)
- Height: 2 inches (51 mm)
- Depth: 4.9 in (125 mm)
- Weight: 1.20 lb (0.54 kg)

Boxed size and weight

- Width: 9.33 inches (237 mm)
- Height: 3.03 inches (77 mm)
- Depth: 6.61 inches (168 mm)
- Weight : 2.50 lb (1.14 kg)

Networking and ports

- Wi-Fi 6E
- USB-C port (for debug only)
- Ethernet 1.0 Gbps (supports PoE)
- Power adapter for AC (optional)

Electrical and environmental requirements

- Ambient operating temperature: 32° to 95° F (0° - 35° C)
- Storage temperature: -4° to 140° F (-20° to 60° C)
- Relative humidity: 10% to 90% (non-condensing)
- Power over Ethernet (PoE): IEEE 802.3af PoE, Class 3 (mode A&B)
- Input: 56V = 0.275A

Power consumption

- Idle: 3.4 W
- Idle (screen off): 2 W
- In-call: 3.4 W

In the box

- Neat Pad Generation 2
- Hex key: 2mm
- Ethernet cable: 9.8 ft (3m)
- Warranty book

*Feature not supported by Microsoft Teams

**Microsoft Teams will be available first as a Console for meeting control with Neat OS



2

One touch, two roles

Serves as a meeting room controller for managing in-room video calls or a scheduling display showing room availability outside the door.



Hear everyone clearly

Extend audio pickup in the room for clearer conversations.



Your rooms, your rules

Native support for Google Meet, Microsoft Teams, and Zoom, with flexibility through Neat Open and Neat Open Apps.



Stay in command from anywhere

Configure, update, and monitor your rooms through Neat Pulse.

P2

Ready for more

Powered by our next-generation P2 platform for improved performance and reliability.

Neat Pad Generation 2

As a meeting room controller and scheduling display, Neat Pad Generation 2 gives teams instant, familiar control and IT a simple, scalable way to standardize rooms across every space. Compact, reliable, and easy to deploy, it delivers a consistent experience across every room—so everything just works.

General

- 8-inch diagonal touch screen
- 1280 × 800 screen resolution
- 16:10 aspect ratio
- Anti-glare, anti-fingerprint coating
- Ambient light sensor
- Sensors for temperature, humidity, and VOC index (*)
- RGB side LED Indicators
- 3D Accelerometer
- Mounting options: wall, glass, and side
- Native support for Zoom Rooms
- Native support for Microsoft Teams Rooms on Android**
- Native support for Google Meet (room controller)
- Ultrasound-capable speakers (*)
- One integrated microphone

Size and weight

- Width: 7.90 in (200 mm)
- Height: 2 inches (51 mm)
- Depth: 4.9 in (125 mm)
- Weight: 1.20 lb (0.54 kg)

Boxed size and weight

- Width: 9.33 inches (237 mm)
- Height: 3.03 inches (77 mm)
- Depth: 6.61 inches (168 mm)
- Weight : 2.50 lb (1.14 kg)

Networking and ports

- Wi-Fi 6E
- USB-C (for debug)
- Ethernet 2.5 Gbps (supports PoE)
- Power adapter for AC (optional)

Electrical and environmental requirements

- Ambient operating temperature: 32 ° to 95 ° F (0 ° - 35 ° C)
- Storage temperature: - 4 ° to 140° F (-20 ° to 60° C)
- Relative humidity: 10 % to 90 %
- Power over Ethernet (PoE): 802.3af PoE (Class 0/ mode A/ B)
- Input: 56 V = 0.2 75A

Power consumption

- Idle: 3.4 W
- Idle (screen off): 2 W
- In-call: 3.4 W

In the box

- Neat Pad Generation 2
- Hex key: 2mm
- Ethernet cable: 9.8 ft (3m)
- Warranty book

*Feature not supported by Microsoft Teams

**Microsoft Teams will be available first as a Console for meeting control with Neat OS