



































— WebCam <sup>M</sup>	licrophone	Low Power SILVER
Cabinet Color		Piano-black Glossy Finish with Translucent Deco
Panel		TFT Active Matrix LCD
		22" Class Widescreen, Diagonal
		21.6" Viewable Image Size
Pixel Pitch		0.277 x 0.277mm
Display Area		465mm x 291mm
Brightness		280 cd/m2 (typ)
Contrast Ratio		100,000:1 (dynamic)
Response Time		2ms (GTG)
Viewing Angle		Horizontal: 160 Degrees (CR>10)
		Vertical: 160 Degrees (CR>10)
<b>Scanning Frequency</b>		Horizontal: 30K~80KHz
		Vertical: 56~75 Hz
Pixel Frequency		165MHz
<b>Maximum Resolution</b>		1680x1050x60Hz
Recommended Reso	lution	1680x1050@60Hz
Supported Resolution	ns	720x400@70Hz, 640x480@60/75Hz, 800x600@60/75hz,
		1024x768@60/70/75Hz, 1280x1024@60/75Hz, 1366x768@60Hz,
		1440x900@60Hz, 1680x1050@60Hz
Color		16.7M
Analog Input		Analog: 0.7Vp-p(standard), 75 OHM, Positive
Digital Input		HDMI with HDCP*
Connectors		Analog RGB Signal: 15-pin D-sub Male
		Digital Signal: 18-pin HDMI
Power Source		Universal 100~240VAC, 50/60Hz (External Power Adapter)
Power Consumption		28Watts (typ)
Plug & Play		DDC/2B, DDC/CI
EPA ENERGY STAR	3)	Yes
User Control		Power/Menu, Eco/DCR/Up, Source/Auto/Down, Vol./Left, Image Ratio/Right
OSD Languages		Multi-language including English, French and Spanish
Regulations		cTUVus, FCC, CE, Certified for Windows Vista Logo, ROHS, EPEAT
		Silver
Built-in Speakers		1.5Wx2
Other Features		Built-in Webcam and Microphone, Ultra Thin (18.5mm) Profile, Hard
		Glass Base, User Friendly Graphical OSD Menu, includes AOC
		proprietory i-Menu software OSD, 4:3 Mode, Mercury Free WLED
		backlight
Dimensions (WxHxD	•	Monitor: 526.0x438.8x190.0, Carton: 590x510x116
Dimensions (WxHxD	inches)	<u> </u>
Weight		8.36 lbs (3.8 kgs) Net
		17.38 lbs (7.9 kgs) Gross
Loading Qty w/pallet		20' = 720 pcs.; 40' Std = 1548 pcs.
UPC Code		685417024087