

# Product data sheet

Specifications



## Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m, North America

AP8706S-NA

### Overview

**Presentation** Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

**Lead time** Usually in Stock

### Main

<b>Product or Component Type</b>	Power cord
<b>Input Connection Type</b>	IEC 60320 C14
<b>Cable length</b>	6 ft (1.8 m)
<b>Number of cables</b>	6

### Physical

<b>Color</b>	Black
<b>Height</b>	9.4 in (24 cm)
<b>Width</b>	3.0 in (7.5 cm)
<b>Depth</b>	2.2 in (5.5 cm)
<b>Net Weight</b>	2.98 lb(US) (1.35 kg)
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable

### Input

<b>Max line current</b>	10 A
<b>Input current limits</b>	10 A

### Output

<b>Maximum Total Current Draw per Phase</b>	10 A
<b>Number of power socket outlets</b>	1 IEC 60320 C13
<b>Cord Length</b>	6 ft (1.8 m)

### Conformance

<b>Product Certifications</b>	CSA UL Listed
-------------------------------	------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environmental

Ambient Air Temperature for Operation	32.0000000000...221.0000000000 °F (0...105 °C)
Relative Humidity	20...80 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...221.0000000000 °F (-25...105 °C)
Storage Relative Humidity	20...80 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

GTIN	731304294405
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.4 in (24 cm)
Package 1 Width	2.2 in (5.5 cm)
Package 1 Length	3.0 in (7.5 cm)
Package 1 Weight	2.98 lb(US) (1.35 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back   Transparency   RoHS/REACH

## Resource performance

 Take-Back Program Available

## Well-being performance

 Lead Free

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)