

MPN: FIB412002-2

Optical Fibre Cable, LC-ST, Multimode, Duplex, OM2 (Orange), 2m

The 50/125µm OM2 multimode fiber optic cable is optically tested for insertion loss to ensure high quality. It is very cost-effective for network cabling in data centers, enterprise networks, telecom rooms, server farms, cloud storage networks, and any place where fiber patch cables are needed. OM2 patch cords are manufactured using LSZH cables and conform to IEC, EIA TIA or Telcordia standards.

- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- RoHS compliant



Spezifikationen

Battery	Battery Type	NONE - Only use for non-battery items
Features	Einfügedämpfung	0,3 dB
	Fasermodusstruktur	Multi-mode
	Glasfasertyp	OM2
	Halogen frei	Yes
	Jackenmaterial	Low smoke zero halogen (LSZH)
	Kabellänge	2 m
	Kerndurchmesser	50 µm
	Manteldurchmesser	125 µm
	Produktfarbe	Orange
	RoHS-Konformität	Yes
	Stecker 1	LC/UPC
	Stecker 1 Geschlecht	Male
	Stecker 2	ST/UPC
	Stecker 2 Geschlecht	Male
Operational conditions	Betriebstemperatur (TT)	-40 - 85 °C
	Lagertemperatur (TT)	-40 - 85 °C
Other features	Dämpfung (max.)	0,4 dB/km
Package dimensions	Depth (package,cm)	1,5 cm
	Gross Weight	0,05 kg
	Height (package,cm)	15 cm
	Width (package,cm)	16 cm
Product dimensions	Net Weight	0,04 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Jahre)

Weight & dimensions

Biegungsradius	6 cm
Kabeldurchmesser	2 mm

Weitere Produkte dieser Serie

Kabellänge	OM1	OM2	OM3	OM4
0,5	FIB4120005-1	FIB4120005-2	FIB4120005	FIB4120005-4
1,0		FIB412001-2	FIB412001	FIB412001-4
2,0	FIB4130002	FIB412002-2	FIB412002	FIB412002-4
3,0	FIB4130003	FIB412003-2	FIB412003	FIB412003-4
5,0	FIB4130005	FIB412005-2	FIB412005	FIB412005-4
7,0		FIB412007-2	FIB412007	FIB412007-4
10,0		FIB412010-2	FIB412010	FIB412010-4
15,0		FIB412015-2	FIB412015	FIB412015-4
20,0		FIB412020-2	FIB412020	FIB412020-4
25,0		FIB412025-2	FIB412025	FIB412025-4