
# QuickSpecs

#### Overview

## **HP PUSB Thermal Receipt Printer**



### Models

HP PUSB Thermal Receipt Printer

FK224AA/AT

## Introduction

The HP PUSB Thermal Receipt Printer is designed for retail environments with its durable design and print performance. Its compact size also makes it perfect for space-constrained locations.

It is the ideal printing companion for the HP Point of Sale Systems and the HP Cash Drawers (Models FK182AA and QT457AA).

### **Key Features and Benefits**

- Counter space is maximized by the printer's compact size
- Two color and monochrome thermal printing
- Spill resistant built-in liquid dam with drainage helps prevent damage to printing mechanism
- 8 MB Flash Memory for custom tasks (add store logos, offer promotions, highlight sales items, print coupons)
- Able to withstand the wear and tear of retail environments with the steel modular frame
- Connects to a powered USB connection on POS system, no separate power cable needed which helps to reduce cable clutter and power consumption.

## Compatibility

The HP PUSB Receipt Printer is compatible with HP rp3100, rp5800, rp7100 and rp7800 Point of Sale Systems.

**NOTE:** Not all Point of Sale system models are available in all regions. Not all HP Cash Drawer models are available in all regions. This printer does not comply with fiscalization requirements that may be required in certain countries.

### **Service and Support**

Your HP Peripheral Limited Warranty is a three (3) year (HP Option Limited Warranty Period) parts replacement warranty.



# QuickSpecs

# **Technical Specifications**

General	Supported Character Sets	- Pasidant Cada Pagas
General	Supported character Sets	437 (US)
		737 (Greek)
		850 (Multilingual Latin I)
		852 (Latin II)
		857 (Turkish)
		858 (Multilingual Latin I + Euro)
		860 (Portuguese)
		862 (Hebrew) 863 (Canadian French)
		865 (Nordic)
		866 (Russian)
		874 (Thai) – Thai effective February 2011
		1251 (Cyrillic)
		1252 (Latin 1)
		1255 (Hebrew)
		Downloaded from Installation CD:
		932 (Japanese)
		936 (Simplified Chinese)
		949 (Korean)
		950 (Traditional Chinese)
	Two-Color Capability	Yes (2-color thermal receipt paper required)
	Receipt-Columns	44/56
	Paper Roll Size	80 mm x 90 mm
	Other Paper Widths	58, 60, 82.5 mm
	Paper Thickness Range	2.0–3.4 mil
	Resolution	203 DPI
	Knife	Standard (Ceramic, Rotary)
	Flash Memory	8 MB
	RAM	512 KB
	Cash Drawers	1 connector can drive 2 cash drawers with separately purchased splitter cable (default configuration is connection to 1 cash drawer)
	Bar Codes	UPC-A, UPC-E, Code 39, Code 128, EAN128, Jan8 and Jan13 (EAN), Interleaved 2 of 5, Codabar, PDF417, Code 128 extended, GS1 Databar
	Print method	Direct thermal
	Paper type	Direct thermal POS Grade(s)
Mechanical	Dimensions (HxWxD)	134 x 144 x 184 mm (5.34 x 5.66 x 7.24 in)
	Weight	1.34 kg (2.9 lbs)
	Color	HP Carbonite
Interface/Connection	Interface	24 V Powered USB 24 V Cash Drawer support with RJ12 interface
Power	Operating Voltage	24 V
	Current consumption	1.4A (printing a typical receipt) 88mA (idle)
	Cable Length	6.01 ft (1.85 m)
Operating Range	Operating	5°C to 35°C (41°F to 95°F) at 5 – 90 % Humidity 35°C to 50°C (95°F to 122°F) at 5 – 40 % Humidity
	Storage	-10°C to 50°C (14°F to 122°F) at 5 – 90 % Humidity

## **Technical Specifications**

	Transit	40°C to 60°C (-40°F to 140°F) at -5 – 95 % Humidity	
Drivers	Windows native, OPOS, JPOS		
Operating Systems (Compatible with)	Genuine Windows® 7 Professional 32 Genuine Windows® 7 Professional 64 Genuine Windows Vista® Business 32 Genuine Windows XP Professional 32 Genuine Windows Embedded for Point of Service (WEPOS) Genuine Windows Embedded POSReady 2009		
Reliability	MCBF Printlines (64mill); MCBF Knife Cuts (2mill)		
Agency Certifications	EMI: FCC, ICES-003, VCCI: Class B; CE, Austel: Class B Safety, UL 1950, CSA 22.2 No. 950, CE (EN60950), MITI (power supply), FCC Class B, MIC, C-Tick, CCC, WHQL, RoHS, WEEE, SABS, GS		
Option kit contents	HP branded PUSB Printer, Starter paper roll, PUSB cable ( 1.8M length), HP Documentation		

Date of change:	Version History:		Description of change:
	From v1 to v2		
November 24, 2015	From v11 to v12	Changed	Kit Contents
May 3, 2018	From v12 to v13	Add	Model

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft, Windows, Windows XP and Windows Vista are trademarks of the Microsoft group of companies.

