

## Cisco-Compatible QSFP-100G-SR4-S QSFP28 Transceiver - 100GBase-SR4, Multimode MTP/MPO, 850 nm, 100 m

MODEL NUMBER: N286-100G-SR4-S



Links a multimode Gigabit Ethernet network cable to a Cisco router, server or switch's QSFP28 port.

### Features

#### QSFP28 Transceiver Designed for Connection to Your Cisco Network Switch or Server

This QSFP28 transceiver allows you to connect a multimode fiber optic cable to a 100 Gbps network router, server or switch. It transmits data up to 100 meters (328 feet) using an 850 nm wavelength. The zinc housing protects against electromagnetic interference (EMI) and excessive power dissipation.

#### Functionally Equivalent to Cisco GLC-TE Transceiver Module

The MSA-compliant N286-100G-SR4-S functions just like the equivalent Cisco QSFP-100G-SR4-S transceiver module and is manufactured to meet or exceed Cisco specifications. You can use this transceiver with any compatible Cisco router, server or switch and receive the same performance as the QSFP-100G-SR4-S.

#### Hot-Swappable for Installation Without Network Interruption

This input/output device is fully hot-swappable, so you can install it without a potentially costly 100 Gbps network shutdown or device reboot. Just plug the QSFP28 end of the transceiver into your Cisco network device. The other end has an MTP/MPO connector to link with multimode fiber cable (sold separately). A push/pull tab connector is easily accessible in high-density data center applications and makes the plug-and-play transceiver easy to install and remove with one hand.

### Highlights

- QSFP28 transceiver module  
100% compatible with Cisco's equivalent module
- Provides 100 Gbps throughput up to 100 m (328 ft.) via multimode fiber cabling
- 12-strand MTP/MPO connector supports 100GBase-LR4 signal at 850 nm wavelength
- Hot-swappable interface lets you install and uninstall without shutting down
- Meets or exceeds MSA standards and works in all MSA-compliant platforms

### Applications

- Install an additional MTP/MPO port on a Cisco router, server or switch for the purpose of connecting a multimode Gigabit Ethernet network cable

### System Requirements

- Cisco or other compatible network router, server or switch

### Package Includes

- N286-100G-SR4-S Cisco-Compatible QSFP-100G-SR4-S QSFP28 Transceiver

## Specifications

OVERVIEW	
UPC Code	037332248497
Optical Mode	OM4



<b>PHYSICAL</b>	
Color	Silver
Unit Dimensions (hwd / cm)	0.84 x 1.83 x 11.63
Unit Dimensions (hwd / in.)	0.33 x 0.72 x 4.58
Unit Dimensions (hwd / mm)	8.4 x 18.3 x 116.3
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 to 158F (0 to 70C)
Storage Temperature Range	-4 to 185F (-20 to 85C)
Relative Humidity	5% to 85%
<b>CONNECTIONS</b>	
Side A - Connector 1	12-STRAND MTP (MALE)
Side B - Connector 1	QSFP28 (MALE)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Driver Required	No
Technology	MTP/MPO; Multimode; SFP+/QSFP+/QSFP28
Wavelength	850nm
Optical Port	MPO/MTP
Multi-Source Agreement (MSA) Compliant	Yes
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>