

Product data sheet

Specifications



Rack ATS, 230 V, 32 A, IEC 309 in, (16) C13 (2) C19 out



AP4424

⚠ To be discontinued on: Nov 1, 2024

⚠ To be discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P+E
Number of rack unit	2U
Cable length	8 ft (2.4 m)
Number of cables	2
Provided Equipment	Rack Mounting brackets RS-232 configuration cable Serial configuration cable

Physical

Color	Black
Height	3.5 in (8.8 cm)
Width	17.008 in (43.2 cm)
Depth	9.3 in (23.6 cm)
Net Weight	15.30 lb(US) (6.94 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Max line current	32 A
Input current limits	32 A
Load Capacity	7400 VA

Output

Maximum Total Current Draw per Phase 32 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power socket outlets	16 IEC 60320 C13 2 IEC 60320 C19
---------------------------------------	-------------------------------------

Protection Type	Circuit breaker
------------------------	-----------------

Conformance

Standards	EN 55022 Class A FCC Part 15 class A
------------------	---

Environmental

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
--	--------------------------

Relative Humidity	5...95 %
--------------------------	----------

Operating altitude	0...10000 ft
---------------------------	--------------

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
--	----------------------------

Storage Relative Humidity	5...95 %
----------------------------------	----------

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
-------------------------	--

Ordering and shipping details

GTIN	731304333432
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	8.3 in (21 cm)
-------------------------	----------------

Package 1 Width	14.02 in (35.6 cm)
------------------------	--------------------

Package 1 Length	23.0 in (58.4 cm)
-------------------------	-------------------

Package 1 Weight	20.79 lb(US) (9.43 kg)
-------------------------	------------------------

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH


Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
