Product data sheet

Specifications

Green Premium"	Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A, 208V, (21) C13 & (3) C19	
Overview		
Presentation	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.	
Lead time	Usually in Stock	
Main		
Colour	Black	
product or component type	PDU	
PDU type	Switched metered outlet	
Cord length	9.84 ft (3.00 m)	
provided equipment	CAN port terminator Installation guide	

Locking input power cord Rack mounting brackets Safety guide Serial configuration cable

Complementary

Input Voltage	200 V 208 V 230 V	
Height	72.008 in (182.9 cm)	
Width	2.2 in (5.6 cm)	
Output Voltage	208 V	
Depth	2.008 in (5.1 cm)	
net weight	14.93 lb(US) (6.77 kg)	
mounting location	Side	
Mounting preference	No preference	
Input Plug Type	NEMA L6-20P	
mounting mode	Not rack-mountable	

Rack units	0U	
Mounting position	Vertical	
[In] rated current	16 A	
Permissible voltage	100240 V	
Input current limits	20 A	
Load capacity	3300 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19	

Environment

Product certifications	UL listed VCCI class A VDE	
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003	
Ambient air temperature for operation	23.000000000140.000000000 °F (-560 °C)	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	ature for -13.000000000149.000000000 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (0.00000000015240.000000000 m)	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	80.2 in (203.8 cm)	
Package 1 Width	4.6 in (11.7 cm)	
Package 1 Length	6.4 in (16.2 cm)	
Package 1 Weight	19.95 lb(US) (9.05 kg)	

Contractual warranty

Warranty

2 years repair or replace

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Resource performance

Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

Lead Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information