



HT812TC HOME THEATER SURGE PROTECTOR

Safeguard your equipment from damaging power transients

The Home Theater Surge Protector HT812TC provides 4350 joules of protection and 8 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. Gold-plated RG6 coaxial connectors protect cable/satellite TV receivers & modems.

Features of the HT812TC include automatic shutdown, 8 surge-protected outlets (4 widely spaced to accommodate a transformer plug), a power cord (12 ft.), a right-angle plug with 45° off-set, LED status indicators, keyhole mounting slots, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Office computers
- Home theater

FEATURES

- 4350 Joule Surge Protection
- 125 Volts
- 8 x NEMA 5-15R Outlets
- 4 x Transformer Outlets
- Data Line, Coax Protection
- 12 ft Power Cord
- Limited Lifetime Warranty
- \$350,000 CEG

SPECIFICATIONS

GENERAL	
Type	Home Theater
INPUT	
Cord Length (ft)	12
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Circuit Breaker	15 A
Switch	Non Lighted On/Off - Reset
OUTPUT	
Outlets - Widely Spaced	4
Outlet Type	NEMA 5-15R
Outlets - Total	8

SURGE PROTECTION & FILTERING	
Maximum Surge Current H-G	30,000 amps
Clamping Voltage	500 V (L-N, L-G, N-G)
Attenuation	Up to 58 dB
EMI/RFI Filtration	150 kHz - 100 MHz
Maximum Surge Current H-N	90,000 amps
Maximum Surge Current N-G	30,000 amps
Response Time	< 1 nanosecond
Coaxial Protection RG6 (Gold Plated)	1 Pair
Surge Suppression	4350
Phone Protection RJ11	1-In, 2-Out

HT812TC HOME THEATER SURGE PROTECTOR

SPECIFICATIONS CONT.

INDICATORS

Indicators	Protected (green) Grounded (green)
------------	---------------------------------------

PHYSICAL

Keyhole Mounting Slots	Yes
------------------------	-----

Safety Covers	Yes
---------------	-----

DIMENSIONS

Shipping - Dimensions (WxHxD, in)	6.75 x 2.125 x 13.75 (in)
-----------------------------------	---------------------------

Shipping - Dimensions (WxHxD, mm)	171.45 x 53.98 x 349.25 (mm)
-----------------------------------	------------------------------

Shipping - Weight (lb)	2.4
------------------------	-----

Shipping - Weight (kg)	1.09
------------------------	------

Shipping Dimensions - (WxHxD) (cm)	17.15 x 5.4 x 34.93 (cm)
------------------------------------	--------------------------

CERTIFICATIONS

Environmental	RoHS Compliant
---------------	----------------

Safety	UL1363, UL1449 4th Edition
--------	----------------------------

WARRANTY

CEG Amount	\$350,000
------------	-----------

Product Warranty	Limited Lifetime
------------------	------------------

Connected Equipment Guarantee	Lifetime
-------------------------------	----------

