

Product datasheet

Specifications



Power Cord, C20 to IEC309 (16A), 2.5m

AP9899

Overview

Presentation	This cable connects an IEC C19 outlet to an IEC 309-16A connector. It can be used as a means to plug in a 16A IEC 309 plug into a Rack PDU with IEC C19 outlets.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C20
Cable length	2.5 m

Physical

Colour	Black
Height	9.5 cm
Width	29.2 cm
Depth	9.5 cm
Net weight	0.5 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Number of power socket outlets	1 IEC 60309 16 A 2P + E
---------------------------------------	-------------------------

Conformance

Product certifications	VDE
-------------------------------	-----

Environmental

Ambient air temperature for operation	-10...40 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	10...30 °C

Storage Relative Humidity	20...80 %
---------------------------	-----------

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	10.2 cm
------------------	---------

Package 1 Width	30.5 cm
-----------------	---------

Package 1 Length	10.2 cm
------------------	---------

Package 1 Weight	0.609 kg
------------------	----------

Unit Type of Package 2	CAR
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	25.4 cm
------------------	---------

Package 2 Width	32.2 cm
-----------------	---------

Package 2 Length	53.2 cm
------------------	---------

Package 2 Weight	6.12 kg
------------------	---------

Unit Type of Package 3	PAL
------------------------	-----

Number of Units in Package 3	10
------------------------------	----

Package 3 Height	143.99 cm
------------------	-----------

Package 3 Width	100 cm
-----------------	--------

Package 3 Length	120 cm
------------------	--------

Package 3 Weight	6.12 kg
------------------	---------

Logistical informations

Country of origin	US
-------------------	----

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)