

# Product datasheet

Specifications



## "Lifting eyebolts, PanelSeT SFN, PanelSet SF, steel , M12 , set of 4"

Local distributor code:  
21034628

NSYSFEB



EAN Code: 3606485131542

## Overview

Lead time Usually Ships within 4 Weeks

## Main

|                           |   |
|---------------------------|---|
| Area                      | PanelSeT  |
| category                  | Lifting accessory   |
| Product or component type | Lifting eye   |
| Application               | Multi-purpose   |
| Mounting location         | Enclosure top   |
| Mounting support          | Directly in the axis of the uprights                                |
| Range compatibility       | Prisma Prisma PH<br>PanelSeT PanelSeT SFHD<br>PanelSeT PanelSeT SFM |
| Device composition        | 4 eyebolt   |
| Quantity per set          | Set of 1  |

## Complementary

|                            |   |
|----------------------------|---|
| Material                   | Cast steel                              |
| Surface finish             | Galvanized                              |
| Fixing mode                | Screwed                                 |
| Permanent permissible load | 340 kg for 1 eyebolt vertical direction |
| Height                     | 62.5 mm                                 |
| Width                      | 55 mm                                   |
| Depth                      | 24 mm                                   |
| Diameter                   | 29 mm                                   |
| ISO thread                 | M12                                     |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 6.000 cm  |
| Package 1 Width              | 10.000 cm |
| Package 1 Length             | 10.500 cm |
| Package 1 Weight             | 771.000 g |

|                                     |            |
|-------------------------------------|------------|
| <b>Unit Type of Package 2</b>       | S03        |
| <b>Number of Units in Package 2</b> | 24         |
| <b>Package 2 Height</b>             | 30.000 cm  |
| <b>Package 2 Width</b>              | 30.000 cm  |
| <b>Package 2 Length</b>             | 40.000 cm  |
| <b>Package 2 Weight</b>             | 18.924 kg  |
| <b>Unit Type of Package 3</b>       | P12        |
| <b>Number of Units in Package 3</b> | 192        |
| <b>Package 3 Height</b>             | 45.000 cm  |
| <b>Package 3 Width</b>              | 80.000 cm  |
| <b>Package 3 Length</b>             | 120.000 cm |
| <b>Package 3 Weight</b>             | 163.392 kg |

## Logistical informations

|                          |    |
|--------------------------|----|
| <b>Country of origin</b> | ES |
|--------------------------|----|

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations