

# USB-C Multiport Video Adapter - Rose Gold - 4-in-1 USB-C to VGA, DVI, HDMI or mDP - 4K

Product ID: CDPVDHDMDPRG



This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C or Thunderbolt 3 computer to a VGA, DVI, HDMI® or Mini DisplayPort display.

### All-in-one video connectivity, with travel in mind

Avoid the hassle of carrying different adapters for different displays with this 4-in-1 USB-C video adapter'. With VGA, DVI, HDMI and mDP output, you can connect your laptop to virtually any display. It's a convenient plug-and-play solution for travel or Bring Your Own Device (BYOD) applications, wherever you go.

The adapter features a built-in magnetic fastener that helps guide the breakout cable into place for quick and secure portability. With its durable aluminum enclosure, the adapter can withstand being carried around in any travel bag.





### **Astonishing picture quality**

The HDMI and mDP outputs on this adapter support UHD 4K resolutions providing four times the picture quality of high-definition 1080p. All of the outputs (HDMI, mDP, VGA, DVI) can support high-definition resolutions of up to  $1920 \times 1200$ .

### Stylish connectivity for your rose gold MacBook or any laptop

This USB-C adapter has an aluminum housing and built-in white USB-C cable designed to match your rose gold MacBook. The adapter is compatible with any device that supports USB-C DP Alt Mode.

The CDPVDHDMDPRG is backed by a StarTech.com 2-year warranty and free lifetime technical support.





# Certifications, Reports and Compatibility













### **Applications**

- Keep the adapter with you while traveling, to connect to virtually any display
- Connect your BYOD MacBook to a provided VGA, DVI, HDMI or mDP display at work or school
- Connect a VGA, DVI, HDMI or Mini DisplayPort monitor to your rose gold MacBook, to use as a secondary monitor

#### **Features**

- 4-in-1 adapter USB-C to VGA, USB-C to DVI, USB-C to HDMI or USB-C to Mini DisplayPort
- Maximum portability with built-in magnetic cable manager
- Astonishing picture quality with support for 4K UHD



## **Data Sheet**

|                                 | Warranty                    | 2 Years  |
|---------------------------------|-----------------------------|--|
| Hardware                        | Active or Passive Adapter   | Active   |
|                                 | Adapter Style               | Adapters   |
|                                 | AV Input                    | USB Type-C   |
|                                 | AV Output                   | HDMI   |
|                                 |                             | DVI-D  |
|                                 |                             | VGA  |
|                                 |                             | Mini-DisplayPort   |
|                                 | Chipset ID                  | Cypress - CYPD1120<br>Cypress - CY7C65210<br>Parade - PS8348B<br>Parade - PS171  |
| Performance                     | Audio Specifications        | HDMI and mDP output - 7.1 surround sound   |
|                                 | Maximum Analog Resolutions  | 1920 x 1200 @ 60Hz   |
|                                 | Maximum Digital Resolutions | 3840 x 2160 @ 30Hz   |
|                                 | Supported Resolutions       | <b>Max HDMI output:</b> 3840 x 2160 @ 30Hz   |
|                                 |                             | <b>Max mDP output:</b> 3840 x 2160 @ 60Hz  |
|                                 |                             | <b>HDMI and mDP output:</b> 3840 x 2160, 2560 x 1600, 1920 x 1200, 1920 x 1080, 1280 x 720   |
|                                 |                             | DVI and VGA output: $1920 \times 1200$ , $1920 \times 1080$ , $1280 \times 720$  |
|                                 | Wide Screen Supported       | Yes  |
| Connector(s)                    | Connector A                 | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input   |
|                                 | Connector B                 | 1 - Mini-DisplayPort (20 pin) Female Output  |
|                                 |                             | 1 - VGA (15 pin, High Density D-Sub) Female Output   |
|                                 |                             | 1 - DVI-D (25 pin) Female Output   |
|                                 |                             | 1 - HDMI (19 pin) Female Output  |
| Special Notes /<br>Requirements | Note                        | Only one video output is supported on the video adapter at a time, if multiple connections are made, only one of the outputs will function |
| Environmental                   | Humidity                    | Storage: 5% ~ 90 % RH (no condensation) Operating: 10% ~ 85 % RH (no condensation)   |
|                                 | Operating Temperature       | 0°C to 45°C (32°F to 113°F)  |
|                                 | Storage Temperature         | -10°C to 70°C (14°F to 158°F)  |
|                                 |                             |  |



## **Data Sheet**

| Physical<br>Characteristics | Cable Length              | 4.5 in [115 mm]        |
|-----------------------------|---------------------------|------------------------|
|                             | Color                     | Rose Gold              |
|                             | Enclosure Type            | Aluminum               |
|                             | Product Height            | 0.6 in [15 mm]         |
|                             | Product Length            | 4.1 in [104 mm]        |
|                             | Product Weight            | 3.2 oz [90 g]          |
|                             | Product Width             | 2.1 in [54 mm]         |
| Packaging<br>Information    | Shipping (Package) Weight | 0.3 lb [0.1 kg]        |
| What's in the Box           | Included in Package       | 1 - travel A/V adapter |

Product appearance and specifications are subject to change without notice.