

# Product datasheet

Specifications



## Power Cord, Locking C19 to CEE/7 Schuko, 3.0m

AP8755

### Overview

**Presentation** Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

**Lead time** Usually in Stock

### Main

<b>Product or component type</b>	Power cord
<b>Main Output Voltage</b>	240 V
<b>Input Connection Type</b>	Schuko CEE 7/7P
<b>Cable length</b>	3.00 m
<b>Number of cables</b>	1

### Physical

<b>Colour</b>	Black
<b>Height</b>	23 cm
<b>Width</b>	23 cm
<b>Depth</b>	4.5 cm
<b>Net weight</b>	0.42 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable

### Input

<b>Max line current</b>	16 A
<b>Input current limits</b>	16 A

### Output

<b>Max current draw</b>	16 A
<b>Number of power socket outlets</b>	1 IEC 60320 C19
<b>Power cable length</b>	3.05 m

### Conformance

<b>Product certifications</b>	VDE
-------------------------------	-----

## Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...70 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	23 cm
Package 1 Length	4.5 cm
Package 1 Weight	0.42 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	25 cm
Package 2 Width	33.5 cm
Package 2 Length	56.5 cm
Package 2 Weight	3.376 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	8
Package 3 Height	143.99 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	3.376 kg
SCC14	10731304279799

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

## Resource performance

 Take-Back Program Available

## Well-being performance

 Lead Free

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)