



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

Model #: B120-000

## DVI Dual Link Signal Extender (DVI F/F)



### Highlights

- Extend a DVI-D Dual Link signal up to 150 ft. from the source
- Use P560-Series DVI Dual-Link cables in most applications.
- When extending a 2560 x 1600 video signal more than 75 ft., use cable made with 24Awg wiring
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Description

Tripp Lite's B120-000 DVI Dual Link Signal Extender increases the distance a DVI-D signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports video resolutions up to 2560 x 1600 @ 60Hz, and a maximum distance of 150 ft. from the source. Use P560-Series DVI Dual-Link cables in most applications. When extending a 2560 x 1600 video signal more than 75 ft., use cable made with 24Awg wiring. (Available from Tripp Lite as a custom order) Simply connect the longer cable between the source and the B120-000, and the shorter cable (16 ft. or less) between the adapter and the monitor. Software or drivers are not required. Built-in Equalization control to adjust the video image. HDCP and DDC compatible. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

#### Package Includes

- B120-000 DVI Dual Link Signal Extender
- External Power Supply ( Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Screwdriver for Equalization adjustment
- Owner's Manual

### Features

- Extend a DVI-D Dual Link signal up to 150 ft. from the source
- Supports a maximum video resolution of 2560 x 1600 @ 60Hz
- Use P560-Series DVI Dual-Link cables in most applications
- When extending a 2560 x 1600 video signal more than 75 ft., use a cable made with 24Awg wiring (Available from Tripp Lite as a custom order)
- Built-in Equalization control to adjust the video image
- HDCP and DDC compatible
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Specifications

OVERVIEW	
Display Style	Signal Booster
PHYSICAL	
Color	Black
CONNECTIONS	

Connector A	 DVI-I (FEMALE)
Connector B	 DVI-I (FEMALE)
Number of Connectors	2
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">P560-006</a>	6-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">P560-010</a>	10-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">P560-015</a>	15-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">P560-025</a>	25-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">P560-050</a>	50-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">P560-100</a>	100-ft. DVI Dual Link TDMS Cable (DVI-D M/M)	1
<a href="#">B120-000-SL</a>	DVI Single Link Signal Extender (DVI F/F)	1
<a href="#">B140-101X</a>	DVI over Cat5 Active Extender Kit	1
<a href="#">B140-101-WP</a>	DVI over Cat5 Passive Extender Wallplate Kit	1
<a href="#">B140-101</a>	DVI over Cat5 Passive Extender Kit	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=3502](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=3502).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.