





# 75" 4K COMMERCIAL DISPLAY WITH 350 CD/M<sup>2</sup> BRIGHTNESS, 16/7 OPERATION, HDMI, USB-C, CONTENT SHARING, REMOTE MANAGEMENT | CDE7514

## Key Features


- SEAMLESS AV INTEGRATION: Certified for Q-SYS, compatible with Crestron, Extron, and AMX.
- STUNNING VISUALS: Enjoy vivid 4K detail with bright reflection-free viewing.
- FAST STARTUP: Boots in seconds so meetings start on time, every time.
- FREE FLEET CONTROL: Easily manage your displays remotely with free ViewSonic Manage
- SIMPLE CONNECTIVITY: One USB-C cable plus HDMI for quick, easy laptop connections.



75"  
DISPLAY



ADS  
PANEL



RESOLUTION



## Product Description

The ViewSonic CDE14 series is a high-performance 4K display purpose-built for Corporate Offices, Higher Education, and the Public Sector. Featuring a 25% high-haze anti-glare coating and a 350-nit "sweet spot" for eye comfort, it ensures reflection-free clarity in Retail Boutiques and Professional Services. This series eliminates technical friction with Single-Cable USB-C connectivity, AirSync™ wireless casting, and a secure Android 14 platform. Unlike standard 16/7 displays that require expensive licenses or proprietary hardware, the CDE14 offers a Certified Pro-AV Ecosystem (Crestron, Extron, Q-SYS) and includes ViewSonic Manager™ Basic for free, centralized fleet control. With Intelligent Signal Failover and a fast "Warm Boot" startup, your communications remain active and efficient. Eco-certified, the CDE7514 delivers a premium, secure experience with a significantly lower total cost of ownership than leading competitors.

## Specifications

| More Information |                                         |
|------------------|-----------------------------------------|
| UPC              | 766907036350                            |
| OS               | Android 14 AOSP                         |
| GPU              | ARM Mali-G57 MC1                        |
| CPU              | MT9681 (ARM Cortex-A73 x4)              |
| Memory           | 4GB DDR4                                |
| Storage          | 32GB                                    |
| Photo            | BMP, GIF, JPEG, PNG                     |
| Video            | AVI, FLV, F4V, MKV, MOV, MP4, MPG, WEBM |

|                                  |                                                                                                                                                                             |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Music</b>                     | AAC, APE, FLAC, PCM, MP3, OGG, WAV                                                                                                                                          |
| <b>HDMI 2.1</b>                  | 480i, 480p,720p,1080i,1080p, 4K@60Hz                                                                                                                                        |
| <b>HDMI Out</b>                  | 4K@60Hz                                                                                                                                                                     |
| <b>USB-C</b>                     | 480p, 576p, 720p, 1080p, 4K@60Hz                                                                                                                                            |
| <b>Internal Speakers</b>         | 10W (x2)                                                                                                                                                                    |
| <b>Speaker Position</b>          | Bottom                                                                                                                                                                      |
| <b>HDMI 2.1 In</b>               | 3                                                                                                                                                                           |
| <b>3.5mm Audio Out</b>           | 1                                                                                                                                                                           |
| <b>SPDIF</b>                     | 1                                                                                                                                                                           |
| <b>USB Type A</b>                | 2                                                                                                                                                                           |
| <b>USB Type C</b>                | 15W x 1                                                                                                                                                                     |
| <b>RS232</b>                     | 1                                                                                                                                                                           |
| <b>Ethernet LAN (RJ45)</b>       | 1                                                                                                                                                                           |
| <b>Voltage</b>                   | 100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz                                                                                                                             |
| <b>Consumption (max)</b>         | 182.5W                                                                                                                                                                      |
| <b>Consumption (typical)</b>     | 105.7W                                                                                                                                                                      |
| <b>Stand-by</b>                  | <0.5W                                                                                                                                                                       |
| <b>Temperature</b>               | 32-104° F (0 - 40° C)                                                                                                                                                       |
| <b>Humidity (non-condensing)</b> | 20-80%                                                                                                                                                                      |
| <b>Net (lbs)</b>                 | 75.29                                                                                                                                                                       |
| <b>Gross (lbs)</b>               | 106.79                                                                                                                                                                      |
| <b>Net (kg)</b>                  | 34.2                                                                                                                                                                        |
| <b>Gross (kg)</b>                | 48.4                                                                                                                                                                        |
| <b>Packaging (in.)</b>           | 73.35 x 42.91 x 6.14                                                                                                                                                        |
| <b>Physical (in.)</b>            | 66.36 x 37.94 x 2.94                                                                                                                                                        |
| <b>Packaging (mm)</b>            | 1863 x 1090 x 225                                                                                                                                                           |
| <b>Physical (mm)</b>             | 1685.6 x 963.7 x 74.6                                                                                                                                                       |
| <b>VESA Compatible</b>           | 600 x 400 mm                                                                                                                                                                |
| <b>Screw Size</b>                | M8                                                                                                                                                                          |
| <b>Screw Length (mm)</b>         | 25                                                                                                                                                                          |
| <b>AV Control</b>                | AMX Certified, Extron Certified, Crestron Connected                                                                                                                         |
| <b>Warranty</b>                  | Three-year limited warranty on parts, labor and backlight                                                                                                                   |
| <b>Recycle/Disposal</b>          | Please dispose of in accordance with local, state or federal laws.                                                                                                          |
| <b>Package Contents</b>          | CDE7514 Commercial Display, Remote control with batteries, Quick Start Guide, Power cable (3m), HDMI Cable (3m), Wall Mount Screws (x4), AAA battery (x2) and RS232 adapter |
| <b>Regulations</b>               | cTUs, FCC, Energy Star 8.0, RoHS                                                                                                                                            |

|                                    |                                               |
|------------------------------------|-----------------------------------------------|
| <b>Wifi</b>                        | VB-WIFI-005 adapter, 802.11AX + Bluetooth 5.2 |
| <b>Screen Size</b>                 | 75"                                           |
| <b>Viewable Area (in.)</b>         | 75                                            |
| <b>Orientation</b>                 | Landscape                                     |
| <b>Colors</b>                      | 1.07B                                         |
| <b>Color Space Support</b>         | 8 bit + FRC                                   |
| <b>Light Source</b>                | DLED                                          |
| <b>Display Resolution</b>          | 3840 x 2160                                   |
| <b>Refresh Rate</b>                | 60Hz                                          |
| <b>Panel Type</b>                  | ADS                                           |
| <b>Aspect Ratio</b>                | 16:9                                          |
| <b>Static Contrast Ratio</b>       | 1,200:1                                       |
| <b>Dynamic Contrast Ratio</b>      | 2,000:1                                       |
| <b>Backlight Life (Hours)</b>      | 30,000                                        |
| <b>Brightness</b>                  | 350 cd/m2                                     |
| <b>Response Time (Typical GTG)</b> | 11ms                                          |
| <b>Bezel Width (in.)</b>           | 0.63                                          |
| <b>Bezel Width (mm)</b>            | 15.9                                          |
| <b>Viewing Angles</b>              | 178º horizontal, 178º vertical                |
| <b>Panel Surface</b>               | Anti-Glare type, Hard-coating (3H), Haze 25%  |
| <b>Operation Rating</b>            | 16/7                                          |
| UPC: 766907036350                  |                                               |



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 