



Power Cord Kit (6 ea), Locking, C19 to C20, 1.8m, Blue

AP8716SX593

Overview

Lead time Usually in Stock

Main

| Product or Component Type | Power cord |
|---------------------------|---------------|
| Input Connection Type | IEC 60320 C20 |
| Cable length | 6 ft (1.8 m) |
| Number of cables | 6 |

Physical

| Color | Blue |
|---------------------|-----------------------|
| Height | 11.8 in (30 cm) |
| Width | 3.1 in (8 cm) |
| Depth | 2.8 in (7 cm) |
| Net Weight | 4.76 lb(US) (2.16 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |

Input

| Max line current | 16 A |
|----------------------|------|
| Input current limits | 16 A |

Output

| Maximum Total Current Draw per Phase | 16 A |
|---|-----------------|
| Number of power socket outlets | 1 IEC 60320 C19 |
| Cord Length | 6 ft (1.8 m) |

Conformance

| Product Certifications | CCC |
|------------------------|-----------|
| | CSA |
| | PSE |
| | UL Listed |
| | VDE |

Environmental

Ambient Air Temperature for 32...167 °F (0...75 °C)
Operation

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Relative Humidity | 2080 % | |
|-------------------------------------|--|--|
| Operating altitude | 010000 ft | |
| Ambient Air Temperature for Storage | -13167 °F (-2575 °C) | |
| Storage Relative Humidity | 2080 % | |
| Storage altitude | 050000 ft (0.000000000015240.0000000000 m) | |

Ordering and shipping details

GTIN 731304285014

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.8 in (30 cm) |
| Package 1 Width | 2.8 in (7 cm) |
| Package 1 Length | 3.1 in (8 cm) |
| Package 1 Weight | 4.76 lb(US) (2.16 kg) |
| SCC14 | 10731304285011 |

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Take-back Transparency RoHS/REACh

Resource performance



Take-Back Program Available

Well-being performance



Lead Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |