

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

USB 2.0 Hi-Speed Active Extension Repeater Cable (USB-A M/F), 15 m (49 ft.)

MODEL NUMBER: U026-15M





Description

Tripp Lite's U026-15M USB 2.0 Hi-Speed Active Extension Repeater Cable (M/F) increases the length of a device cable up to 49 feet with no danger of signal loss or performance decrease. Connect the male plug to a USB port on your computer or hub and the female end to a USB device cable. A built-in bus-powered signal booster ensures peak USB 2.0 signal quality. Backward compatible with previous USB generations, this cable supports data transfer rates up to 480 Mbps.

Highlights

- Adds 49 ft. to existing USB device cable
- Supports data transfer rates up to 480 Mbps
- Built-in booster for peak USB 2.0 signal quality
- Provides up to 250mA of power to connected device
- Backward compatible with previous USB generations

System Requirements

- USB 2.0 computer port and USB
 2.0 device required to meet USB
 2.0 speeds
- External power supply or powered USB hub (such as U222-004-R) required for power applications above 250mA.

Package Includes

 U026-15M USB 2.0 Hi-Speed Active Extension Repeater Cable (M/F), 15 m

The U026-15M works with all computers, devices and cables with USB-A connectors, and provides up to 250mA of power to a connected device (an external power supply or powered USB 2.0 hub is required for power applications stronger than 250mA). Premium foil and braid shielding delivers top-of-the-line signal quality and protection from EMI/RFI interference. Nickel-plated USB connectors with gold-plated copper contacts ensure excellent conductivity. Integral strain relief ensures the cable and connectors last a long time.

Features

Extends Transmission Distance Between USB Device and Computer by 49 ft.

- Supports data transfer rates up to 480 Mbps
- Built-in bus-powered signal booster for peak performance
- Provides up to 250mA of power to connected device
- Backward compatible with previous USB generations

Premium Construction for Superior Signal Transfer

- Premium foil and braid shielding protects against EMI/RFI
- Nickel-plated connectors with gold-plated copper contacts ensure excellent conductivity
- Works with all computers, devices and cables with USB-A connectors
- External power supply or powered USB hub required for power applications stronger than 250mA

Specifications





INPUT	
Cable Length (ft.)	49.2
Cable Length (m)	15
PHYSICAL	
Color	Black
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	USB A (FEMALE)
CERTIFICATIONS	
Certifications	RoHS Compliant
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies