

Part Number: V1206-P

V1206-P Zero Client for VMware Next-Generation Tera2 PCoIP Portal Processor

The V1206-P supports the efficiency and security of centralized computing and offers an uncompromised end-user experience. The V1206-P delivers a powerful, secure and easy to manage desktop. With six USB ports, rich multimedia playback, HD audio and multiple monitor support, the V1206-P is the perfect fit for any VMware VDI environment.



▶ TERA2 PCoIP Portal Processor	▶ 6 USB Ports
▶ 1x (2560x1600) 2x (1920x1200)	▶ VESA Mounting capability
▶ Dual Monitor Support	▶ Free Centralized Management

vmware ^{teradici} PCoIP

Americas P: 866-865-5250

EMEA P: +44 (0) 116 214 8650

APAC P: 1300 768 799

E: info@10ZiG.com

E: info@10ZiG.eu

E: info@10ZiG.com.au

W: www.10ZiG.com

W: www.10ZiG.eu

W: www.10ZiG.com.au

TERA2 PCoIP Zero Client Series

V1206-P

System	V1206-P
Management	Teradici Management
Form Factor	Slim Line
Processor	Teradici PCoIP™ Portal Processor -TERA2
Chipset	TERA2321 PCoIP™

Dimensions	
Device	6.3" (Height) x 5.28" (Length) x 1.7" (Thickness)
Weight	1.5lbs - 0.68kgs

Connections	
Ports	USB x 6, DVI-I x 1, DVI-D x 1, Mic-In x 1, Line-Out x 1
Video	1 x (2560 x 1600) - 2 x (1920 x 1200)
Imaging	50 Mpps (VDI) - 150 Mpps (with Work Station Card)

Networking	
Ethernet	10/100/1000 Base-T

Environmental	
Operating Temp.	50~104F (10~40C), 10-95% non-condensing humidity
Power	8 Watt Consumption, 36 Watt, DC-12V/3A Input

Certifications	
	CE, FCC, CAN ICES-3/NMB-3, VCCI, UL, TUV-GS, C-Tick, GOST, BSMI, RoHS