

Key Features

Smart Platform



Quad Core SoC*

The High Performance SoC can execute several tasks at the same time and provides smooth content playback.



*System-on-Chip

webOS 2.0

The webOS 2.0 platform provides easy and convenient tools to create content. LG's SDK* and technical supports make content development and management easier.



*Software Development Kit

Simple Installation

Installation has been simplified by removing the external media player and Ethernet/RS232C cables.



Built-in Wi-Fi: (removing Ethernet or RS232C cables) 802.11n (2.4GHz/5GHz)

Connectivity Supports



Simple Network Management Protocol

SNMP support ensures convenient network management.



Mirroring

Content sharing is more convenient on a Wi-Fi network.



SoftAP

The 22SM3B with SoftAP software can operate as a wireless access point for mobile devices.



Easy Maintenance



Real-Time Remote Monitoring

When an alarm occurs, an e-mail notification is sent using SuperSign C or SI SW through the SNMP Protocol. In case of malfunctions or errors, real-time remote care is available.



Supportive Convenience

BEACON

With BEACON and Bluetooth Low Energy (BLE) supported by 22SM3B, retail stores can provide coupons and information in real-time.





Intuitive Information Delivery



Screen Size

22SM3B

• Brightness: 250 cd/m²

• Bezel: Top/Left/Right/Bottom 16.3mm (Even Bezel)

• Depth : 53.8mm

• Special : BEACON support, Wi-Fi Built in (Mirroring, Soft AP)

• Interface : HDMI / USB / RGB / RJ45 / IR

• Built-in Speaker : 1W x 1W






| Specification | ons | 22SM3B |
|-----------------------------|--|--|
| PANEL | Screen Size | 21.5 |
| | Panel Technology | IPS |
| | Aspect Ratio | 16:9 |
| | Native Resolution | 1,920 × 1,080 (FHD) |
| | Brightness | 250cd/m ² |
| | Contrast Ratio | 1,000:1 |
| | Dynamic CR | 4,000,000:1 |
| | Viewing Angle (H x V) | 178 x 178 |
| | Surface Treatment | Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1%(Typ.)) |
| | Guaranteed Operating Hour | 16 Hours |
| | Orientation | Portrait & Landscape |
| CONNECTIVITY | Input | HDMI, RGB, Audio, USB 3.0 |
| | Output | - |
| | External Control | RS232C In, IR Receiver, Pixel Sensor, RJ45 |
| PHYSICAL SPECIFICATION | Bezel Color | Black |
| | Bezel Width | 16.3mm (T/R/L/B) |
| | Monitor Dimension (W x H x D) | 510.3 x 302.1 x 53.8 mm |
| | Weight (Head) | 3.6kg |
| | Carton Dimensions (W x H x D) | 565 x 357 x 103 mm |
| | Packed Weight | 4.7kg |
| | VESA [™] Standard Mount Interface | 100 x 100mm |
| SPECIAL FEATURES | | ISM Method, Internal Memory 8GB (System 4GB + Free 4GB), Wi-Fi (802.11n combo built-in), USB Cloning, Local Contents Scheduling, Sync Mode, PM Mode, Local Time Auto Setting, Wake on LAN, Pivot Mode, Content Rotation 0,90,270, Fail Over, BEACON On/Off, Embedded Templat |
| ENVIRONMENTAL CONDITIONS | Operating Temperature Range | 0 °C to 40 °C |
| | Operating Humidity Range | 10 % to 80 % |
| POWER | Power Supply | 100-240V~, 50/60Hz |
| | Power Type | Built-In Power |
| | Power Typ. | 35W |
| | Consumption Smart Energy Saving | On 25.13W / Off 29.76W |
| AUDIO POWER | | 2W(1W x 2) for Internal Speaker |
| STANDARD (CERTIFICATION) | Safety | UL / cUL / CB / TUV |
| | EMC | FCC Class "B" / CE |
| SOFTWARE COMPATIBILITY | SuperSign-W / Lite | Yes |
| | SuperSign-C | Yes |
| ACCESSORY | Basic | Remote Controller (include 2ea batteries), Power Cord, QSG, RGB Cable, Phone to RS232C Gender |
| | Optional | Pixel Sensor (KT-SP0) |


Dimension (unit:mm)

22"

510.3 x 302.1 x 53.8 / 3.6kg







Connectivity

1 RS-232C IN

G RGB IN

2 AUDIO IN

(1) HDMIIN

3 PIXEL SENSOR

4 LAN

1 USB 3.0





Download LG Commercial Display Mobile App





More info www.lgecommercial.com





