

PCT2485 - Multi-Touch Monitor



rtical)
buch
44.5
44.5

Display Weight (w/o stand)	Not applicable. Integrated stand folds into the monitor.
Shipping weight	17.0 lbs. (7.7 kgs.)
Video Inputs	Analog, HDMI, DisplayPort
Audio Output	2 speakers, 1W/ch
Compatibility	Windows® 7, 8 - HID Compliant - no drivers needed for basic touchscreen operation
External Connections	VGA 15-pin, HDMI 19-pin, DisplayPort 20-pin, 3.5 mm audio in, 3.5mm headphone out, USB (A to B), USB 2.0 A type x 2, AC power-in
Power Supply	Internal Power Supply (AC power)
Power Requirements	100-240 VAC, 50/60 Hz
Power Consumption	35W typical (<1.0W standby, off)
Operating Temperature	0 to 40°C
VESA Compatible/Location	Built-in 100 mm VESA, back
Service and Support	3-Year Customer First™ Warranty featuring FREE 2- Day Advance Replacement (US only)
Options / Features	Integrated HD (720p) webcam with microphone; built- in USB Hub -USB 2.0 - x 2, Kensington® Security Slot
Product Approvals	UL/c-UL, FCC-Class B, CE, TUV/Bauart, RoHS
CI-Black-PN	997-7052-00
CI-White-PN	N/A
In the Box	PCT2485 24" Wide Multi-Touch Monitor, Power Cord, VGA Cable, HDMI Cable, USB Cable (A to B), Audio- in Cable, User's Guide, Cleaning Cloth, Stylus, Cable Wrap
UPC	8 10689 07052 8

For more information, please visit www.planar.com

Specifications are subject to change without notice. Specification Report Date: 7/10/2013 (c)Copyright 2013 Planar Systems, Inc. All rights reserved