

Overview

HP ZBook 8 G1a 14 Mobile Workstation



- 1 ACS & ALS Sensor
- 2 Microphone (2)
- 3 IR Camera (optional)
- 4 Webcam
- 5 Camera Shutter
- 6 IR LEDS (optional)
- 7 Webcam LED
- 8 Nano SIM card slot (Optional)

Left

- 9 LED Indicator
- 10 USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 11 USB Type-A 5Gbps signaling rate (Powered)
- 12 RJ45 Ethernet port (standard)
- 13 Security lock slot (Integrated)
- 14 Fingerprint reader / Power button
- 15 Touchpad

Overview



		Right	
1	HDMI 2.1	4	Power Indicator LED
2	Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)	5	Headphone/mic combo jack
3	Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)	6	Smart Card Reader (Optional)

Features

PRODUCT NAME

HP ZBook 8 G1ah 14 Mobile Workstation/ HP ZBook 8 G1ak 14 Mobile Workstation/ HP ZBook 8 G1as 14 Mobile Workstation

OPERATING SYSTEM

Preinstalled OS

- FreeDOS
- Windows 11 Home - HP recommends Windows 11 Pro for business ¹
- Windows 11 Home Single Language - HP recommends Windows 11 Pro for business ¹
- Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement) ¹
- Windows 11 Pro ¹

¹ Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>



Features

PROCESSOR

Name ^{1,2,4,5,7}	Cores	Threads	Smart Cache	Max Boost Frequency	Base Frequency	Pro	NPU	NPU TOPs
AMD Ryzen 5 PRO 230	6 cores	12	16 MB	4.90 GHz	3.5	Yes	Y	15
AMD Ryzen AI 5 PRO 340	6 cores	12	16 MB	4.80 GHz	2.0	Yes	Y	50
AMD Ryzen AI 7 PRO 350	8 cores	16	16 MB	5.00 GHz	2.0	Yes	Y	50
AMD Ryzen AI 9 HX PRO 375	12 cores	24	24 MB	5.10 GHz	2.0	Yes	Y	55
<div><div></div><div><p>¹ Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.</p><p>² Intel Turbo Boost performance varies depending on hardware, software and overall system configuration. See http://www.intel.com/technology/turboboost for more information.</p><p>⁴ In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com.</p><p>⁵ Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.</p><p>⁷ Features and software that require a NPU may require software purchase, subscription or enablement by a software or platform provider, and third party software may have specific configuration or compatibility requirements. Performance varies by use, configuration, and other factors.</p></div></div>								

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

- AMD Radeon™ Graphics with Pro Graphics driver
- AMD Radeon™ 840M Graphics with Pro Graphics driver (1)
- AMD Radeon™ 860M Graphics with Pro Graphics driver (2)
- AMD Radeon™ 890M Graphics with Pro Graphics driver (3)

Support

Support HDMI 2.1

¹Only available with the Ryzen™ AI 5 PRO

²Only available with the Ryzen™ AI 7 PRO

³Only available with the Ryzen™ AI 9 HX PRO

Features

DISPLAY

Non-Touch

- 35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Anti-Glare, Low Blue Light, 800 nits, sRGB 100%, HP Sure View 5 [6]
- 35.6 cm (14") diagonal, WQXGA (2560 x 1600), Bent, LCD, 120Hz, UWVA, anti-glare, WLED, 500 nits, DCI-P3 100%, HP DreamColor
- 35.6 cm (14") diagonal, 2.5K (2560 x 1600), LCD, 120Hz (VRR), UWVA, Anti-Glare, WLED + Low Blue Light, 400 nits, Adobe 100% + DCI-P3 100%
- 35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Anti-Glare, WLED + Low Blue Light, 400 nits, Low Power, sRGB 100%
- 35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, UWVA, Anti-Glare, WLED, 300 nits, Low Power, sRGB 62.5%

Touch

- 35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, Touch, UWVA, Anti-Glare, Low Blue Light, 800 nits, sRGB 100%, HP Sure View 5 [6]
- 35.6 cm (14") diagonal, WUXGA (1920 x 1200), LCD, Touch, UWVA, Anti-Glare, 300 nits, Low Power, sRGB 62.5%

DisplayPort™ 1.4

HDMI 2.0 Support resolution up to 4K @60 Hz

Displays support

Supports dual display through the dock

Display Size

- 14.0"
- 35.6 cm

Docking (Sold Separately)

Docking station model #1	HP USB-C™ Dock G5
Total number of supported displays (incl.the notebook) display)	3
Max.resolutions supported	Multi-Function Mode: (2) 5k @ 30Hz and (1) 4k UHD @ 30Hz on any port High-Resolution Mode: (2) 5k @ 60Hz on DisplayPort ports and (1) 4k UHD @ 60Hz on HDMI port
Dock Connectors	1x HDMI 2.0, 2x DisplayPort 1.4
Technicallimitations	Maximum resolution and display support is dependent on the maximum capability of the notebook. Highest resolution with dual displays is two 8K@ 60Hz host in High Resolution mode. Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode

Features

Docking station model #2
Total number of supported displays (incl.the notebook) display)
Max.resolutions supported

The highest resolution for a non-Thunderbolt host in Multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.
HP Thunderbolt™ 120W G4 Dock

4

Quad 4K @60Hz
Dual 8K single cable@30 for Thunderbolt hosts or USB-C hosts DisplayPort 1.4 with Display Stream Compression in High-Resolution Mode
2x HDMI 2.0, 2x DisplayPort 1.4, 1x Thunderbolt 4, 1x USB-C 3.2 Gen 2 DisplayPort
Maximum resolution and display support is dependent on the maximum capability of the notebook.

Dock Connectors
Technicallimitations

Thunderbolt Hosts:
Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt host.
Maximum resolution possible is dual 8K displays @ 60Hz running Thunderbolt host or running a non-Thunderbolt host in high resolution mode @30Hz
Non-Thunderbolt hosts:
The highest resolution for dual displays running a non-Thunderbolt host in multi-function mode is
(1) 5K dual cable (using both DP ports) +(1) 4K on USB-C DP port
Non-Thunderbolt hosts support (3) displays with a maximum resolution of (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.



Features

STORAGE AND DRIVES

- Primary M.2 Storage**
- 2 TB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell [6]
 - 1 TB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell [6]
 - 1 TB PCIe® NVMe™ SSD Value [6]
 - 512 GB PCIe® Gen4x4 NVMe™ SSD Three Layer Cell [6]
 - 512 GB PCIe® Gen4x4 NVMe™ Self Encrypted OPAL2 SSD Three Layer Cell [6]
 - 512 GB PCIe® NVMe™ SSD Value [6]
 - 256 GB PCIe® NVMe™ Self Encrypted OPAL2 SSD Value [6]
 - 256 GB PCIe® NVMe™ SSD Value [6]

MEMORY

- Maximum Memory**
- 64GB DDR5-5600 MT/s (2 x 32 GB) Memory
 - 64GB DDR5-5600 MT/s (2 x 32 GB) Memory
 - 32GB DDR5-5600 MT/s (1 x 32 GB) Memory
 - 32GB DDR5-5600 MT/s (2 x 16 GB) Memory
 - 16GB DDR5-5600 MT/s (1 x 16 GB) Memory
 - 16GB DDR5-5600 MT/s (2 x 8 GB) Memory
 - 24GB DDR5-5600 MT/s (2x12GB) Memory

- Memory Slots**
- 2 SODIMM
 - System runs at up to 5600 MT/s
 - Supports Dual Channel Memory(optional).
 - The memory is accessible/upgradeable by IT or self-maintainers only

Features

NETWORKING /COMMUNICATIONS

WLAN

- Mediatek RZ616 Wi-Fi 6E Bluetooth® 5.3 AIM-T WLAN
- Mediatek MT7925 Wi-Fi 7 Bluetooth® 5.4 AIM-T WW WLAN
- Qualcomm® Fast Connect 7800 Wi-Fi 7 Bluetooth® 5.4 AIM-T WW WLAN

WWAN

- HP 5G Sub-6 CAT19
- HP 4G CAT19

LPWAN

- Qualcomm 9205 LTE-M (CAT-M1 fSVC) [12]

NFC

- NFC Mirage WNC XRAV-1

Miracast

- Native Miracast Support

Ethernet

- Realtek RTL8111EPP 1GbE Ethernet Controller
-

AUDIO/MULTIMEDIA

- Audio by Poly Studio
- 2 Integrated stereo speakers
- Discrete Amplifiers
- 2 Integrated dual array microphone

Speaker Power

- 1W / 8 ohm per speaker

Camera

- 5MP + Infrared camera
- 5MP camera

Sensors

- Ambient Light Sensor
- Color Sensor with Ambient Light Sensing



Features

Fingerprint Sensor (optional)
Hall Effect Sensor
HP Sure Platform
HP Tamper Lock [14]
Thermal Sensor

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

HP Premium NB Keyboard, spill-resistant, backlit, Durakey keyboard.
HP Premium NB Keyboard, spill-resistant, Privacy, backlit, Durakey, keyboard.

Pointing Device

Clickpad
Microsoft Precision Touchpad Default Gestures Support
Multi-touch gesture support

Function Keys

ESC - System information
F1 - Display Switching
F2 - Blank or Privacy
F3 - Brightness Down
F4 - Brightness Up
F5 - Blank or Keyboard Backlight
F6 - Audio Mute
F7 - Volume Down
F8 - Volume Up
F9 - Mic Mute
F10 - Play and Pause
F11 - Programmable Key
F12 - HOME
Power Button (with LED)
Insert
Delete
End
Page up
Page down
Microsoft Copilot [15]

Hidden Keys

Fn+R - Break, Fn+S - Sys Rq, Fn+C - Scroll Lock



Features

SOFTWARE AND SECURITY

Application Software

Buy Microsoft Office (Sold Separately)
HP Connection Optimizer
Edge Customization
HP Hotkey Support
HP Mac Address Manager
HP Notifications
HP PC Hardware Diagnostics UEFI
HP PC Hardware Diagnostics Windows
HP Privacy Settings
HP Services Scan [15]
HP Smart Support [16]
HP Support Assistant [17]
myHP
HSA Fusion for Commercial
HSA Telemetry for Commercial
Poly Lens [18]
Poly Camera Pro
Ubuntu Data Science Stack

Manageability Features

HP Client Catalog ([download](#)) [19]
HP Client Management Script Library ([download](#)) [20]
HP Cloud Recovery [21]
HP Connect for Microsoft Endpoint Manager
HP Driver Packs ([download](#)) [[22]
HP Image Assistant ([download](#)) [23]
HP Manageability Integration Kit ([download](#)) [24]
HP Power Manager with Battery Health Manager ([download](#)) [25]

Security Management

Secured-Core PC Enable [26]
Windows Hello Enhanced Sign-In Security (ESS)
HP Wolf Security for Business which includes: [27]
HP Tamper Lock
HP Sure Admin [28]
HP Sure Click [29]
HP Sure Recover [30]
HP Sure Run [31]
HP Sure Sense [32]



Features

HP Sure Start [33]

BIOS

Absolute Persistence Module [34]

Audio Permanent Disable

HP BIOS Recovery

HP Fingerprint Sensor [35]

BIOS Update via Network

HP BIOSphere Gen6 [36]

HP DriveLock & Automatic DriveLock

HP Secure Erase [37]

HP Wake on WLAN

15. HP Services Scan is preinstalled and/or provided thru Windows Update and checks for service entitlement on each hardware device and downloads the applicable software agent automatically. To disable this feature, please follow the instructions at <http://www.hpdaas.com/requirements>. The HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to the HP Insights agent is required. For full system requirements, please visit <http://www.hpdaas.com/requirements>. Not available in China.

16. HP Smart Support requires the HP Insights agent to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>. HP Services Scan is preinstalled and/or provided thru Windows Update and will check entitlement on each hardware device to determine if an HP Insights agent-enabled service has been purchased, and will download applicable software automatically. HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access is required. For full system requirements or to disable this feature, please visit <https://www.hpdaas.com/requirements>.

17. HP Support Assistant is available on Windows. For more information, please visit <https://support.hp.com/us-en/help/hp-support-assistant>.

18. Poly Lens Desktop requires a Windows OS.

19. HP Client Catalog not preinstalled, however available for download at (<https://www.hp.com/us-en/solutions/client-management-solutions.html>)

20. HP Client Management Script Library (<https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools>).

21. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/computer>.

22. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

23. HP Image Assistant not preinstalled, however available for download at (<https://ftp.ext.hp.com/pub/caps-softpaq/cmit/HPIA.html>),

24. HP Manageability Integration Kit not preinstalled, however available for download from <https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools>.

25. HP Power Manager with Battery Health can be downloaded by entering your system information here: https://support.hp.com/in-en/document/ish_4449597-3519507-16.

26. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.



Features

- 27. HP Wolf Security for Business requires Windows 10 or 11 Pro or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.
- 28. HP Sure Admin requires HP G8 or newer platforms, Windows 10 or higher, HP BIOS, HP Manageability Kit or KMS Service from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.
- 29. HP Sure Click requires Windows 10 and higher. See https://bit.ly/2PrLT6A_SureClick for complete details.
- 30. HP Sure Recover is available on select HP PCs and requires Windows 10 or 11 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen6 with Embedded Reimaging is an optional feature on select HP PCs which requires Windows 10 or 11 must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.
- 31. HP Sure Run is available on select HP PCs and requires Windows 10 and higher.
- 32. HP Sure Sense requires Windows 10 and higher. See product specifications for availability. On units with WWAN shipping to China, HP Sure Sense is only available via Softpaq download.
- 33. HP Sure Start is available on select HP PCs and requires Windows 10 and higher.
- 34. Absolute Persistence firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.
- 35. HP Fingerprint Reader is an optional feature that requires Windows 10 or 11 and must be configured at purchase.
- 36. HP BIOSphere Gen6 features may vary depending on the platform and configuration.
- 37. HP Secure Erase implements the methods outlined in the National Institute of Standards and Technology Special Publication 800-88r "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

POWER

HP 140W Slim USB Type-C® AC power adapter
HP 100W Slim USB Type-C® AC power adapter

Battery

HP Long Life 3 cell, 62Whr Polymer

Power Cord

3-wired plug- 1.0m

Battery life

TBD

WEIGHT & DIMENSIONS



Features

Weight

Product Weight- 62Whr

Starting at 1.44 kg (3.18 lb) with 62.00 Wh battery

Weight will vary by configuration. Does not include power adapter.

315.60 mm (W) x 222.00 mm (D) x 11.75 mm (front)/ 15.50 mm (rear) (12.43 in (W) x 8.74 in (D) x 0.46 in (front)/ 0.61 in (rear))

Maximum height 18.95 mm (0.75)

Front height measurement is near the front edge where the chassis bottom cover taper begins. Back height measurement is near the back edge where the chassis bottom cover taper ends.

PORTS/SLOTS

Left Side

2 x Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1) [40]

1 x HDMI 2.1

1 x headphone/mic combo jack

1 x Smart Card Reader (Optional)

Right Side

1 x USB Type-C® 10Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

1 x USB Type-A 5Gbps signaling rate (Powered)

1 x RJ45 Ethernet port (Optional)

1 x Nano SIM card slot (Optional)

1 x Security lock slot (Integrated)

SERVICE AND SUPPORT

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for HP Long Life batteries which will follow the one or three year warranty of the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.



Features

Certification and Compliance

CSA/UL 62368-1
ENERGY STAR®
FCC/ICES/CISPR/VCCI
CE MARKING
GS Mark
China CCC/SRRC
Taiwan BSMI/NCC
Korea KCC/KC/KES
Ukraine NSoC/TEC
EAEU Compliance
Saudi Arabian Compliance
TCO
EPEAT® Gold ¹
Low Blue Light

¹EPEAT® registered where applicable. EPEAT® registration varies by country. See www.epeat.net for registration status by country.



Technical Specifications – System Unit

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)

Nominal Operating Voltage	20.0V
Temperature	
Operating	0° to 35° C (32° to 95° F) System performance may be reduced above 32°C (89.6°F)
Non-operating	-20° to 60° C (-4° to 140° F) System performance may be reduced above 32°C (89.6°F)
Relative Humidity	
Operating	10% to 90 % (non-condensing)
Non-operating	5% to 95 %, 38.7° C (101.6° F) maximum wet bulb temperature
Shock	
Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine
Random Vibration	
Operating	1.043 grms
Non-operating	3.500 grms
Altitude (unpressurized)	
Operating	3048 m (10000 ft)
Non-operating	12192 m (40000 ft)
Planned Industry Standard Certifications	
Regulatory Model Number	HSN-I62C-4

Technical Specifications – Displays

DISPLAYS

Actual brightness will be lower with touchscreen or HP Sure View.
Availability may vary by country

14.0 in 2.5K (2560 x 1600)
Anti-Glare UWVA WLED+LBL
AD-100 400 eDP 1.4+PSR2
120Hz (VRR) bent LCD Panel

Outline Dimensions (W x H x D)	306.890 x 197.900 (max)
Active Area	301.594 x 188.496 (typ)
Weight	200 (max)
Diagonal Size	14
Thickness	2.0 / 3.8 (max)
Interface	eDP1.4
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	2000:1 (typ)
Refresh Rate	120 (typ)
Brightness	400 (typ)
Pixel Resolution - Format	2560 x 1600 (2.5K)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	Adobe RGB 100% + DCI-P3 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.3 (max)/ 2.7 (max)

14.0 in WUXGA (1920 x 1200)
Anti-Glare UWVA LED sRGB
62.5 8bit 300 eDP 1.2 w/o PSR
Low-Power 60Hz bent LCD
Panel

Outline Dimensions (W x H x D)	307.590 x 199.150 (max)
Active Area	301.59 X 188.50(typ)
Weight	300 (max)
Diagonal Size	14
Thickness	3.0/4.8 (max)
Interface	eDP1.2
Surface Treatment	Anti-Glare
Touch Enabled	No

Technical Specifications – Displays

Contrast Ratio	1000 : 1 (typ)
Refresh Rate	60 (typ)
Brightness	300 (typ)
Pixel Resolution - Format	1920 x 1200 (WUXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 62.5%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.70 (max)/2.10(max)

14.0 in WUXGA (1920 x 1200)
 Anti-Glare UWVA LED sRGB
 62.5 8bit 300 TOP eDP 1.2 w/o
 PSR Low-Power 60Hz bent LCD
 Panel

Outline Dimensions (W x H x D)	307.59 x 199.15 (max)
Active Area	301.590 x 188.500 (typ)
Weight	300 (max)
Diagonal Size	14
Thickness	3.0/4.8 (max)
Interface	eDP 1.2
Surface Treatment	Anti-Glare
Touch Enabled	Yes
Contrast Ratio	1000:1(typ)
Refresh Rate	60 (typ)
Brightness	300 (typ)
Pixel Resolution - Format	1920 x 1200 (WUXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 62.5%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.75 (max) / 2.15 (max)

14.0 in WUXGA (1920 x 1200)
 Anti-Glare UWVA Low Blue
 Light sRGB 100 800 eDP



Technical Specifications – Displays

1.4+PSR+IOL Sure View 5 bent LCD Panel

Outline Dimensions (W x H x D)	306.890 x 197.900 (max)
Active Area	301.590 X 188.500 (typ)
Weight	260 (max)
Diagonal Size	14
Thickness	2.2/ 3.9 (max)
Interface	eDP 1.4
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1500 : 1 (typ)
Refresh Rate	60 (typ)
Brightness	800 (typ)
Pixel Resolution - Format	1920 x 1200 (WUXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.48 (max)/1.8(max)

14.0 in WUXGA (1920 x 1200) Anti-Glare UWVA Low Blue Light sRGB 100 800 TOP eDP 1.4+PSR+IOL Sure View 5 bent LCD Panel

Outline Dimensions (W x H x D)	306.890 x 197.900 (max)
Active Area	301.590 X 188.500 (typ)
Weight	260 (max)
Diagonal Size	14
Thickness	2.4 / 4.2 (max)
Interface	eDP 1.4
Surface Treatment	Anti-Glare
Touch Enabled	Yes
Contrast Ratio	1500 : 1 (typ)
Refresh Rate	60 (typ)
Brightness	800 (typ)
Pixel Resolution - Format	1920 x 1200 (WUXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 100%



Technical Specifications – Displays

Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.60 (max)/ 1.97 (max)

**14.0 in WUXGA (1920 x 1200)
Anti-Glare UWVA WLED+LBL
sRGB NB2X 400 eDP 1.4+PSR2
Low-Power 100 bent LCD Panel**

Outline Dimensions (W x H x D)	307.590 x 199.550 (max)
Active Area	301.590 x 188.500 (typ)
Weight	210 (max)
Diagonal Size	14
Thickness	2.0 / 3.8 (max)
Interface	eDP 1.4
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1000:1(typ)
Refresh Rate	60 (typ)
Brightness	400 (typ)
Pixel Resolution - Format	1920 x 1200 (WUXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	1.29 (max) / 1.66 (max)

**14.0 in WQXGA DRM (2560 x 1600) Anti-Glare UWVA LED
DCI-P3 NB2X 500 eDP 1.4+PSR2
100 120Hz bent LCD Panel**

Outline Dimensions (W x H x D)	307.594 x 199.546 (max)
Active Area	301.594 x 188.496 (typ)
Weight	230 (max)
Diagonal Size	14
Thickness	2.0 / 3.8 (max)
Interface	eDP 1.4
Surface Treatment	Anti-Glare



Technical Specifications – Displays

Touch Enabled	No
Contrast Ratio	1200:1 (typ)
Refresh Rate	120 (typ)
Brightness	500 (typ)
Pixel Resolution - Format	2560 x1600 (WQXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	DCI-P3 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	No
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.88 (max) / 3.44 (max)



Technical Specifications – Storage

STORAGE

SSD 2TB 2280 PCIe-4x4 NVMe
Three Layer Cell

Form Factor	M.2 2280
Capacity	2TB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	6400 MB/s ±20%
Maximum Sequential Write	5000 MB/s ±20%
Logical Blocks	4000797360
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.

SSD 1TB 2280 PCIe-4x4 NVMe
Three Layer Cell

Form Factor	M.2 2280
Capacity	1TB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	6400 MB/s ±20%
Maximum Sequential Write	5000 MB/s ±20%
Logical Blocks	2000409264
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.

SSD 512GB 2280 PCIe-4x4
NVMe Three Layer Cell

Form Factor	M.2 2280
Capacity	512GB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)

Technical Specifications – Storage

Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	6400 MB/s ±20%
Maximum Sequential Write	3500 MB/s ±20%
Logical Blocks	1000215215
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.

512GB PCIe-4x4 2280 NVME
Self Encrypted OPAL2 Three
Layer Cell Solid State Drive

Form Factor	M.2 2280
Capacity	512GB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	6400 MB/s ±20%
Maximum Sequential Write	3500 MB/s ±20%
Logical Blocks	1000215215
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	TCG Opal 2.0; TRIM; L1.2
	Not all features are available in all versions.

SSD 1TB 2280 PCIe NVMe Value

Form Factor	M.2 2280
Capacity	1TB
NAND Type	Value
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	2200 MB/s ±20%
Maximum Sequential Write	1600 MB/s ±20%
Logical Blocks	2000409264
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.

SSD 512GB 2280 PCIe NVMe
Value

Technical Specifications – Storage

Form Factor	M.2 2280
Capacity	512 GB
NAND Type	Value
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	2200 MB/s ±20%
Maximum Sequential Write	1600 MB/s ±20%
Logical Blocks	1000215215
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.

SSD 256GB 2280 PCIe NVMe
Value

Form Factor	M.2 2280
Capacity	256 GB
NAND Type	Value
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (10 g)
Interface	PCIe NVMe Gen4X4
Maximum Sequential Read	3100 MB/s ±20%
Maximum Sequential Write	1200 MB/s ±20%
Logical Blocks	500118192
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	Pyrite 2.0; TRIM; L1.2
	Not all features are available in all versions.



Technical Specifications – Networking

NETWORKING / COMMUNICATION

Mediatek RZ616 Wi-Fi 6E	Wireless LAN Standards	IEEE 802.11a IEEE 802.11ac IEEE 802.11ax IEEE 802.11b IEEE 802.11d IEEE 802.11e IEEE 802.11g IEEE 802.11h IEEE 802.11i IEEE 802.11j IEEE 802.11k IEEE 802.11mc IEEE 802.11n IEEE 802.11r IEEE 802.11v IEEE 802.11w Wi-Fi certified
Bluetooth® 5.3 AIM-T WLAN [1]		802.11b/g/n/ax 2.402 – 2.482 GHz 802.11a/n/ac/ax 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz 5.925 – 7.125 GHz
	Interoperability	
	Frequency Band	
	Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11ac: MCS0~MCS9, (20MHz, 40MHz, 80MHz, 160MHz) 802.11ax: MCS0~MCS11, (20MHz, 40MHz, 80MHz, 160MHz) 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS0~MCS15, (20MHz, 40MHz)
	Modulation	1024QAM, 16-QAM, 256-QAM, 64-QAM, BPSK, CCK, Direct Sequence Spread Spectrum, OFDM, QPSK
	Security	802.1x authentication AES-CCMP: 128 bit in hardware IEEE 802.11i IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only WAPI WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 (personal) certification

Technical Specifications – Networking

Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	2.4GHz (MIMO, typical): <ul style="list-style-type: none"> • 802.11b : +18dBm • 802.11g : +16.5dBm • 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm • 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm 5GHz (MIMO, typical): <ul style="list-style-type: none"> • 802.11a : +13dBm • 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm • 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm • 802.11ac/ax (VHT80/HE80) : +11.5dBm • 802.11ax HE160 : +11.5dBm 6GHz LPI mode (MIMO, typical):: <ul style="list-style-type: none"> • 802.11a : 0dBm • 802.11ax HE20 : +1dBm • 802.11ax HE40 : +4dBm • 802.11ax HE80 : +7dBm • 802.11ax HE160 : +7.5dBm
Power Consumption	Transmit mode : 2.5 W Receive mode : 2.0 W Idle mode (PSP) : 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby : 10 mW Radio disabled : 8 mW
Power Management	ACPI and PCI Express compliant power management
Receiver Sensitivity[2]	802.11 compliant power saving mode 2.4GHz (SISO): <ul style="list-style-type: none"> • 802.11b, 11Mbps : -82dBm maximum • 802.11g, 54Mbps : -71dBm maximum • 802.11n, MCS7 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum • 802.11ax, MCS11(HT40): -49dBm maximum 5GHz (SISO): <ul style="list-style-type: none"> • 802.11a, 54Mbps : -71dBm maximum • 802.11n, MCS07 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum • 802.11ax, MCS11(HE80/HE160): -46dBm maximum 6GHz (SISO): <ul style="list-style-type: none"> • 802.11a, 54Mbps : -71dBm maximum • 802.11n, MCS7 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum



Technical Specifications – Networking

Antenna type	<ul style="list-style-type: none"> •802.11ax, MCS11(HE160): -46dBm maximum High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	30.00 x 22.00 x 2.30 mm (1.18 x 0.87 x 0.09 inch)
Weight	1. Type 2230: 2.8 g
Operating Voltage	3.3 v +/- 9 %
Subtitle	Integrated Bluetooth® specifications
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407; ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth Profiles Supported	2Mbps LE Advanced Audio Distribution Profile (A2DP) Basic Imaging Profile (BIP) Bluetooth 4.1 -ESR 5/6/7 Compliance Bluetooth 4.2 ESR08 Compliance Bluetooth 5.2 Bluetooth 5.3 wireless card Channel Selection Algo Encryption key size control enhancements ESR9/10 Compliance FAX Profile (FAX) Hands Free Profile (HFP)



Technical Specifications – Networking

- Headset Profile (HSP)
- LE Advertisement Extensions
- LE Data Packet Length Extension
- LE Dual Mode
- LE L2CAP Connection Oriented Channels
- LE Link Layer
- LE Link Layer Ping
- LE Long Range
- LE Low Duty Cycle Directed Advertising
- LE Privacy 1.2 –Extended Scanner Filter Policies
- LE Privacy 1.2 –Link Layer Privacy
- LE Secure Connection- Basic/Full
- Limited High Duty Cycle Non-Connectable Advertising
- Periodic Advertisement interval
- Train Nudging & Interlaced Scan
- Windows Bluetooth profiles support

[1] Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately.

[2] Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

1. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately.

2. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Mediatek MT7925 Wi-Fi 7 Bluetooth® 5.4 AIM-T WW WLAN [1]	Wireless LAN Standards	IEEE 802.11a
		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11b
		IEEE 802.11be
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11g
		IEEE 802.11h

Technical Specifications – Networking

Interoperability Frequency Band

IEEE 802.11i
IEEE 802.11k
IEEE 802.11n
IEEE 802.11r
IEEE 802.11v
Wi-Fi certified
802.11b/g/n/ax
2.402 – 2.482 GHz
802.11a/n/ac/ax
4.9 – 4.95 GHz (Japan)
5.15 – 5.25 GHz
5.25 – 5.35 GHz
5.47 – 5.725 GHz
5.825 – 5.850 GHz
5.955 – 6.415 GHz
6.435 – 6.515 GHz
6.535 – 6.875 GHz
6.895 – 7.115 GHz

Data Rates

802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11ac: MCS0~MCS9, (20MHz, 40MHz, 80MHz, 160MHz)
802.11ax: MCS0~MCS11, (20MHz, 40MHz, 80MHz, 160MHz)
802.11b: 1, 2, 5.5, 11 Mbps
802.11be: MCS0~13, (20MHz, 40MHz, 80MHz, 160MHz)
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n: MCS0~MCS15, (20MHz, 40MHz)

Modulation

1024QAM, 16-QAM, 256-QAM, 4096-QAM, 64-QAM, BPSK, CCK,
Direct Sequence Spread Spectrum, OFDM, QPSK

Security

802.1x authentication
AES-CCMP: 128 bit in hardware
IEEE 802.11i
IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only
WAPI
WPA, WPA2: 802.1x, WPA-PSK, WPA2-PSK, TKIP, and AES.
WPA2 certification
WPA3 (personal) certification

Network Architecture Models

Ad-hoc (Peer to Peer)
Infrastructure (Access Point Required)

Roaming

IEEE 802.11 compliant roaming between access points

Output Power

- 802.11b, 1Mbps : +17dBm minimum
- 802.11g, 6Mbps : +16dBm minimum
- 802.11a, 6Mbps : +17dBm minimum
- 802.11n, MCS7(HT20) : +14dBm minimum
- 802.11n, MCS7(HT40) : +13.5dBm minimum



Technical Specifications – Networking

Power Consumption

- 802.11ac MCS9(VHT20) : 13.5dBm minimum
- 802.11ac MCS9(VHT40) : +13.5dBm minimum
- 802.11ac MCS9(VHT80) : +12.5dBm minimum
- 802.11ac MCS9(VHT160) : +10.5dBm minimum
- 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum
- 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum
- 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum
- 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum
- 802.11be MCS13(EHT20)(6GHz) : +11.5dBm
- 802.11be MCS13(EHT40)(6GHz) : +7.5dBm
- 802.11be MCS13(EHT80)(6GHz) : +7.5dBm
- 802.11be MCS13(EHT160)(6GHz) : +6.5dBm

Transmit mode : 2.7 W

Receive mode : 1.8 W

Idle mode (PSP) : 180 mW (WLAN Associated)

Idle mode: 50 mW (WLAN unassociated)

Connected Standby/Modern Standby : 10 mW

Radio disabled : 8 mW

Power Management

ACPI and PCI Express compliant power management; 802.11 compliant power saving mode

Receiver Sensitivity[2]

- 802.11b, 1Mbps : -93.5dBm maximum
- 802.11b, 11Mbps : -85dBm maximum
- 802.11a/g, 6Mbps : -90.5dBm maximum
- 802.11a/g, 54Mbps : -72.5dBm maximum
- 802.11n, MCS0(HT20) : -90dBm maximum
- 802.11n, MCS7(HT20) : -71.5dBm maximum
- 802.11n, MCS0(HT40) : -88.5dBm maximum
- 802.11n, MCS7(HT40) : -68.5dBm maximum
- 802.11ac, MCS9(VHT20) : -88.5dBm maximum
- 802.11ac, MCS9(VHT40) : -65.5dBm maximum
- 802.11ac, MCS9(VHT80) : -60.5dBm maximum
- 802.11ac, MCS9(VHT160) : -58.5dBm maximum
- 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
- 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
- 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
- 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
- 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
- 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum
- 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum
- 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum

Antenna type

High efficiency antenna with spatial diversity, mounted in the display enclosure

Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth



Technical Specifications – Networking

Form Factor	communications PCI-Express M.2 MiniCard
Dimensions	30.00 x 22.00 x 2.30 mm (1.18 x 0.87 x 0.09 inch)
Weight	1. Type 2230: 2.8 g
Operating Voltage	3.3 v +/- 9 %
Subtitle	Integrated Bluetooth® specifications
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407; ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth Profiles Supported	2Mbps LE Advanced Audio Distribution Profile (A2DP) Basic Imaging Profile (BIP) Channel Selection Algo Encryption key size control enhancements ESR9/10 Compliance FAX Profile (FAX) Hands Free Profile (HFP) Headset Profile (HSP) LE Advertisement Extensions LE Data Packet Length Extension LE Dual Mode LE L2CAP Connection Oriented Channels LE Link Layer LE Link Layer Ping LE Long Range



Technical Specifications – Networking

		LE Low Duty Cycle Directed Advertising LE Privacy 1.2 –Extended Scanner Filter Policies LE Privacy 1.2 –Link Layer Privacy LE Secure Connection- Basic/Full Limited High Duty Cycle Non-Connectable Advertising Train Nudging & Interlaced Scan
		[1]Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels. [2] Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
		1.Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels. 2. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
Qualcomm® Fast Connect 7800 Wi-Fi 7 Bluetooth® 5.4 AIM-T WW WLAN [1]	Wireless LAN Standards	IEEE 802.11a IEEE 802.11ac IEEE 802.11ax IEEE 802.11b IEEE 802.11be IEEE 802.11d IEEE 802.11e IEEE 802.11g IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11n IEEE 802.11r IEEE 802.11v Wi-Fi certified 802.11b/g/n/ax 2.402 – 2.482 GHz 802.11a/n/ac/ax
	Interoperability Frequency Band	

Technical Specifications – Networking

	4.9 – 4.95 GHz (Japan)
	5.15 – 5.25 GHz
	5.25 – 5.35 GHz
	5.47 – 5.725 GHz
	5.825 – 5.850 GHz
	5.955 – 6.415 GHz
	6.435 – 6.515 GHz
	6.535 – 6.875 GHz
	6.895 – 7.115 GHz
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, 80MHz, 160MHz) 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, 80MHz, 160MHz) 802.11b: 1, 2, 5.5, 11 Mbps 802.11be : MCS0~13, (20MHz, 40MHz, ,80MHz, 160MHz, 320MHz) 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, 40MHz)
Modulation	1024QAM, 16-QAM, 256-QAM, 4096QAM, 64-QAM, BPSK, CCK, Direct Sequence Spread Spectrum, OFDM, QPSK
Security	802.1x authentication AES-CCMP: 128 bit in hardware IEEE 802.11i IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only WAPI WPA, WPA2: 802.1x, WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 (personal) certification
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	<ul style="list-style-type: none"> • 802.11b, 1Mbps : +17dBm minimum • 802.11g, 6Mbps : +16dBm minimum • 802.11a, 6Mbps : +17dBm minimum • 802.11n, MCS7(HT20) : +14dBm minimum • 802.11n, MCS7(HT40) : +13.5dBm minimum • 802.11ac MCS9(VHT20) : 13.5dBm minimum • 802.11ac MCS9(VHT40) : +13.5dBm minimum • 802.11ac MCS9(VHT80) : +12.5dBm minimum • 802.11ac MCS9(VHT160) : +10.5dBm minimum • 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum • 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum • 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum • 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum • 802.11be MCS13(EHT20)(6GHz) : 11.5dBm



Technical Specifications – Networking

Power Consumption	<ul style="list-style-type: none"> • 802.11be MCS13(EHT40)(6GHz) : 7.5dBm • 802.11be MCS13(EHT80)(6GHz) : 7.5dBm • 802.11be MCS13(EHT160)(6GHz) : 6.5dBm • 802.11be MCS13(EHT320)(6GHz) : 4.5dBm <p>Transmit mode : 3.1 W Receive mode : 1.8 W Idle mode (PSP) : 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby : 10 mW Radio disabled : 8 mW</p>
Power Management	ACPI and PCI Express compliant power management; 802.11 compliant power saving mode
Receiver Sensitivity[2]	<ul style="list-style-type: none"> • 802.11b, 1Mbps : -93.5dBm maximum • 802.11b, 11Mbps : -85dBm maximum • 802.11a/g, 6Mbps : -90.5dBm maximum • 802.11a/g, 54Mbps : -72.5dBm maximum • 802.11n, MCS0(HT20) : -90dBm maximum • 802.11n, MCS7(HT20) : -71.5dBm maximum • 802.11n, MCS0(HT40) : -88.5dBm maximum • 802.11n, MCS7(HT40) : -68.5dBm maximum • 802.11ac, MCS9(VHT20) : -88.5dBm maximum • 802.11ac, MCS9(VHT40) : -65.5dBm maximum • 802.11ac, MCS9(VHT80) : -60.5dBm maximum • 802.11ac, MCS9(VHT160) : -58.5dBm maximum • 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum • 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum • 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum • 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum • 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum • 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum • 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum • 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum • 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum
Antenna type	<p>High efficiency antenna with spatial diversity</p> <p>Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications</p>
Form Factor	PCI-Express M.2 MiniCard
Dimensions	30.00 x 22.00 x 2.35 mm (1.18 x 0.87 x 0.09 inch)
Weight	1. Type 2230: 3.1 g
Operating Voltage	3.3 v +/- 9 %
Subtitle	Integrated Bluetooth® specifications
Bluetooth Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
Frequency Band	2402 to 2480 MHz



Technical Specifications – Networking

Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported Link Topology	Microsoft Windows Bluetooth Software
Power Management Certifications	Microsoft Windows ACPI, and USB Bus Support FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407; ETSI 300 328, ETSI 301 893, ETSI 303 687
Bluetooth Profiles Supported	2Mbps LE Advanced Audio Distribution Profile (A2DP) Basic Imaging Profile (BIP) Bluetooth 4.1 -ESR 5/6/7 Compliance Bluetooth 4.2 ESR08 Compliance Bluetooth 5.2 Bluetooth 5.3 wireless card Channel Selection Algo Encryption key size control enhancements ESR9/10 Compliance FAX Profile (FAX) Hands Free Profile (HFP) Headset Profile (HSP) LE Advertisement Extensions LE Data Packet Length Extension LE Dual Mode LE L2CAP Connection Oriented Channels LE Link Layer LE Link Layer Ping LE Long Range LE Low Duty Cycle Directed Advertising LE Privacy 1.2 –Extended Scanner Filter Policies LE Privacy 1.2 –Link Layer Privacy LE Secure Connection- Basic/Full



Technical Specifications – Networking

- Limited High Duty Cycle Non-Connectable Advertising
Periodic Advertisement interval
Train Nudging & Interlaced Scan
Windows Bluetooth profiles support
- [1]Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

[2] Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

- 1.Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP 5G Sub-6 CAT19

Technology/Operating bands

- WCDMA/HSPA+ operating bands:
Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
- LTE FDD/TDD operating bands:
Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)
Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)
Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)
Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)
Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)
Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)
Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)

Technical Specifications – Networking

	Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
	Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
	Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)
	Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
	Band 29: 717 to 728 MHz (DL)
	Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
	Band 34: 2010 to 2025 MHz (UL/DL)
	Band 38: 2570 to 2620 MHz (UL/DL)
	Band 39: 1880 to 1920 MHz (UL/DL)
	Band 40: 2300 to 2400 MHz (UL/DL)
	Band 41: 2496 to 2690 MHz (UL/DL)
	Band 42: 3400 to 3600 MHz (UL/DL)
	Band 43: 3400 to 3800 MHz (UL/DL)
	Band 46: 5150 to 5925 MHz (DL)
	Band 48: 3550 to 3700 MHz (UL/DL)
	Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
	Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
Wireless protocol standards	5G NR Air Interface
	3GPP Rel15 5G NR sub-6
	LTE Rel15
	3GPP Release 8 UMTS Specification
GPS	Standalone/A-GPS (MS-A, MS-B)
GPS bands	GPS L1 (1575.42MHz), GLONASS L1 (1602MHz), Beidou B1 (1561.098MHz), Galileo E1 (1575.42MHz), QZSS (1575.42MHz)
Maximum data rates	SA 5G/NR sub-6 Peak: 4.67 Gbps(Download), 1.25 Gbps(Upload)
Maximum output power	HSPA+: 23.5 dBm
	LTE (all bands except B41): 23.0 dBm (Not support HPUE)
	NR (all band except n41, n77, n78, n79): 23.0 dBm (Not support HPUE)
	NR n41, n77, n78, n79 HPUE: 26.0 dBm (Support HPUE)
Maximum power consumption	5G Sub 6: 3,500 mA
	LTE: 2,500 mA (peak); mA (average)
Form Factor	M.2; 3052-S3 Key B
Weight	8.6 g (0.303 oz)
Dimensions (Length x Width x Thickness)	30.00 x 52.00 x 2.30 mm (1.18 x 2.05 x 0.09 inch)
embedded eSIM	Yes

1. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module

Technical Specifications – Networking

planned to be available in select platforms and select countries, where carrier supported.

HP 4G CAT19	<div>Technology/Operating bands</div> <div>WCDMA/HSPA+ operating bands: Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL) Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL) LTE FDD/TDD operating bands: Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL) Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL) Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL) Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL) Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL) Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL) Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL) Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL) Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL) Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL) Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL) Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL) Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL) Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL) Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL) Band 29: 717 to 728 MHz (DL) Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL) Band 34: 2010 to 2025 MHz (UL/DL) Band 38: 2570 to 2620 MHz (UL/DL) Band 39: 1880 to 1920 MHz (UL/DL) Band 40: 2300 to 2400 MHz (UL/DL) Band 41: 2496 to 2690 MHz (UL/DL) Band 42: 3400 to 3600 MHz (UL/DL) Band 43: 3400 to 3800 MHz (UL/DL) Band 46: 5150 to 5925 MHz (DL) Band 48: 3550 to 3700 MHz (UL/DL) Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL) Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)</div> <div>Wireless protocol standards</div> <div>LTE Rel15 3GPP Release 8 UMTS Specification Standalone/A-GPS (MS-A, MS-B) GPS</div> <div>GPS bands</div> <div>GPS L1 (1575.42MHz), GLONASS L1 (1602MHz), Beidou B1</div>
-------------	--

Technical Specifications – Networking

Maximum data rates	(1561.098MHz), Galileo E1 (1575.42MHz), QZSS (1575.42MHz) UE Category DL 19 (1.6 Gbps Download) , UE Category UL 18 (211 Mbps Upload)
Maximum output power	LTE (all bands except B41): 23.0 dBm (Not support HPUE)
Maximum power consumption	LTE: 2,500 mA (peak)
Form Factor	M.2; 3052-S3 Key B
Weight	8.4 g (0.296 oz)
Dimensions (Length x Width x Thickness)	30.00 x 52.00 x 2.30 mm (1.18 x 2.05 x 0.09 inch)
embedded eSIM	Yes

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

Value

NFC Mirage WNC XRAV-1	Dimensions (L x W x H)	17.00 x 10.00 x 2.00 mm (0.67 x 0.39 x 0.08 inch)
	Chipset	NPC300
	System interface	I2C
	NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
	NFC Forum Support Reader (PCD-VCD) Mode(1)	Type 1, Type 2, Type 3 / Type 4, NFCIP-1 / NFCIP-2 ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz
	Card Emulation (PICC-VICC) Mode(1)	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
	Frequency	13.56 MHz
	NFC Modes Supported	Reader/Writer, Peer-to-Peer
	Raw RF Data Rates	106 kbps, 212 kbps, 424 kbps, 848 kbps
	Operating temperature	Operating: 0 °C to 70 °C (32 °F to 158 °F) Storage: -20 °C to 125 °C (-4 °F to 257 °F)



Technical Specifications – Networking

	Storage temperature	Operating: 10% - 90% (non-condensing) Non-Operating: 5% - 95% (non-condensing)
	Humidity	Operating: 10% - 90% (non-condensing) Non-Operating: 5% - 95% (non-condensing)
	Supply Operating voltage	4.35 to 5.25 Volts
	I/O Voltage	1.8V or 3.3V
	Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)	Booster enable, VBAT= 3.3V, VCC_BOOST = 5V
	Mode	Power Consumption, Typical
	Polling	7.3 mA
	Detected Test Tag Type 1	Total 283.8 mA Net Module 236.8 mA
	Detected Test Tag Type 2	Total 288.8 mA Net Module 241.8 mA
	Detected Test Tag Type 3	Total 287.7 mA Net Module 240.7 mA
	Detected Test Tag Type 4	Total 282.3 mA Net Module 235.3 mA
	Antenna	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.
Realtek RTL8111EPP 1GbE Ethernet Controller	Connector	RJ-45
	System Interface	PCI (Intel proprietary) + SMBus/ USB
	Data rates supported	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14), 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30), 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40),
	IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support, IEEE 802.1q VLAN support, IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable), IEEE 802.3az EEE (Energy Efficient Ethernet), TCP/IP/UDP Checksum Offload (configurable); Protocol Offload (ARP & NS); Large send offload and Giant send offload; Jumbo Frame 9K; Receiving Side Scaling;
	Performance	
	Power consumption	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW
	Power Management	ACPI compliant – multiple power modes; Situation-sensitive features reduce power consumption; Advanced link down power saving for reducing link down power consumption;



Technical Specifications – Networking

Qualcomm 9205 LTE-M (CAT-M1 fSVC) [1]	Management Interface	Auto MDI/MDIX Crossover cable detection
	IT Manageability	Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only); PXE 2.1 Remote Boot; Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)); Support DASH 1.1 compliant/Software KVM ASF 2.0
	Security & Manageability	
	Technology/Operating bands	FDD LTE: 1700/2100 (Band 4), 1700/2100 (Band 66), 1800 (Band 3), 1900 (Band 2), 1900 (Band 25), 2100 (Band 1), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 700 (Band 28), 700 (band 85), 800 (Band 20), 800 (Band 27), 850 (Band 18 lower), 850 (Band 19 upper), 850 (Band 26), 850 (Band 5), 900 (Band 8) MHz
	Wireless protocol standards	GSM/GPRS/EGPRS: 1800, 1900, 850, 900 MHz 3GPP TS 21.111 V10.0.0: USIM and IC card requirements 3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE - DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS) 3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE) 3GPP TS 31.102 V10.11.0: Characteristics of the Universal Subscriber Identity Module (USIM) application 3GPP TS 31.11 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT) 3GPP TS 36.124 V10.3.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and ancillary equipment 3GPP TS 36.521-1 V14.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing 3GPP TS 51.010-1 V10.5.0: Mobile Station (MS) conformance specification; Part 1: Conformance specification 3GPP TS 51.011 V4.15.0: Specification of the Subscriber Identity Module -Mobile Equipment (SIM-ME) interface Standalone GPS/Beidou/GLONASS/A-GPS (XTRA) 1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
	GPS	
	GPS bands	
	Maximum data rates	LTE FDD: 375.00 Kbps(Download), 1119.00 Kbps(Upload) GPRS: 107.00 Kbps(Download), 85.60 Kbps(Upload) EGPRS: 296.00 Kbps(Download), 236.80 Kbps(Upload)
	Maximum output power	LTE (all bands except B41): 21.5 dBm GSM: 34.0 dBm
	Maximum power consumption	LTE: 151 mA(peak), 16 mA(average)
	Form Factor	M.2



Technical Specifications – Networking

Weight	4.0 g (0.141 oz)
Dimensions (Length x Width x Thickness)	22.00 x 42.00 x 2.30 mm (0.87 x 1.65 x 0.09 inch)
embedded eSIM	Support

1. LPWAN (also called Mobile Narrowband) support HP Protect & Trace with Wolf Connect service through the subscription term, but do not support mobile broadband use.



Technical Specifications – Power

POWER

Power supply availability may vary by country.

HP 100W Slim USB-C Straight AC Power Adapter Mario II	Dimensions	5.354 x 2.362 x 0.866 in (13.6x6.0x2.2cm)
	Weight	340g ± 10g (Not including power cord. Power cord varies by country.)
	Input	100-240Vac
	Input Efficiency	81.50% min at 115 Vac/ 230 Vac @5.00V
		86.70% min at 115 Vac/ 230 Vac @9.00V
		88.00% min at 115 Vac/ 230 Vac @12.00V
		89.00% min at 115 Vac/ 230 Vac @15.00V
		89.00% min at 115 Vac/ 230 Vac @20.00V
	Input frequency range	47-63Hz
	Input AC current	Max. 1.6 A at 90 Vac
	Output	
	Output power	5V/15W
		9V/27W
		12V/60W
		15V/75W
		20V/100W
	DC output	5V/9V/12V/15V/20V
	Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
	Output current limit	5V/9V/12V/15V<125% max current, 20V<135% max current
	Connector	
	Connector	C6
	Environmental Design	
	Operating temperature	0° to 35° C (32° to 95° F)
	Non-operating (storage) temperature	-20° to 85° C (-4° to 185° F)
	Altitude	0 to 5,000 m (0 to 16,400 ft)
	Humidity	20% to 95%
	Storage Humidity	10% to 95%
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL 62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, Ukraine(CoC+DoC+RoHS+ECO)
HP 140W Slim USB-C Straight AC Power Adapter Daisy II	Dimensions	5.433 x 2.578 x 1.122 in (13.8x6.55x2.85cm)



Technical Specifications – Power

Weight	415g(+/-10g) (Not including power cord. Power cord varies by country.)
Input	100-240Vac
Input Efficiency	81.50% min at 115 Vac/ 230 Vac @5.00V 86.70% min at 115 Vac/ 230 Vac @9.00V 88.00% min at 115 Vac/ 230 Vac @12.00V 89.00% min at 115 Vac/ 230 Vac @15.00V 89.00% min at 115 Vac/ 230 Vac @20.00V 89.00% min at 115 Vac/ 230 Vac @28.00V
Input frequency range	47-63Hz
Input AC current	Max. 2.5 A at 90 Vac
Output	
Output power	5V/15W 9V/27W 12V/60W 15V/75W 20V/100W 28V/140W
DC output	5V/9V/12V/15V/20V/28V
Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input
Output current limit	5V/9V/12V/15V/20V<125% max current, 28V<135% max current
Connector	
Connector	C6
Environmental Design	
Operating temperature	0° to 35° C (32° to 95° F)
Non-operating (storage) temperature	-20° to 85° C (-4° to 185° F)
Altitude	0 to 5,000 m (0 to 16,400 ft)
Humidity	20% to 95%
Storage Humidity	10% to 95%
EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL 62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, Ukraine(CoC+DoC+RoHS+ECO)
MC 62Whr Long Life Polymer Fast charge 3 cell Battery	
Dimensions (H x W x L)	L 255.8 mm* W 67.8mm* T 7.4mm
Weight	Max 236.0g
Cells/Type	3cell Lithium-Ion Polymer cell
Energy	



Technical Specifications – Power

Voltage	11.58V
Amp-hour capacity	5355mAh / 5086mAh
Watt-hour capacity	62Whr
Temperature	
Operating (Charging)	0° C ~ 40° C
Operating (Discharging)	-10° C ~ 40° C
Fuel Gauge LED	
Warranty	
Optional Travel Battery Available	No



Technical Specifications – Audio

AUDIO	
HD Stereo Codec	Realtek ALC3315
Audio I/O Ports	3.5mm Headset: CTIA only;Headphone-out
Internal Speaker Amplifier	Cirrus Logic High-Efficiency Boosted Class D Amplifier
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front jacks or integrated speaker., Following MSFT Behavior
Sampling	DAC: Supports resolutions from 16-bit to 24-bit;48.0 kHz to 48.0 kHz ADC: Supports resolutions from 16-bit to 24-bit;44.1 kHz to 48.0 kHz
Internal Speaker	Yes



Technical Specifications – Fingerprint Reader

FINGERPRINT READER

Sensor vendor	SYNAPTICS
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	104 x 86 pixels
False Rejection Rate	< 3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.7 V ~ 3.6 V
Operating Temperature	5°C ~ 60°C (41°F ~ 140°F)
Current Consumption Image	100 mA max
Low Latency Wait For Finger	260 uA
Capture Rate	50 frames/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 7.4 x 6.0 mm sensor area

Fingerprint Reader	Second Source
Sensor vendor	ELAN
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	56 x 56 pixels
False Rejection Rate	< 3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.8 V ~ 3.6 V
Operating Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Current Consumption Image	100 mA max
Low Latency Wait For Finger	300 uA
Capture Rate	50 frames/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 4.0 x 4.0 mm sensor area

Options and Accessories (sold separately and availability may vary by country)

OPTIONS

Category	Description	Part Number
Audio/Video	TBD	TBD
Cases	TBD	TBD
Docking	TBD	TBD
Hub	TBD	TBD
Adapter	TBD	TBD
Keyboard/Combo	TBD	TBD
Mouse	TBD	TBD
Power	TBD	TBD
Commodity	TBD	TBD



Date of change	Version History		Description of change
May 16, 2025	From v1 to v2	Changed	Format page 1 and PROCESSOR section

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.