
Muliple Screen Split-Ultra HD Signage

Ultra HD UH5C Series



Key Features

Ultra HD

ULTRA HD

Ultra HD Resolution (3840x2160)

enhanced in content management. With LG SuperSign EZ providing basic content templates, you can create and edit content simply and guickly on your mobile device or signage display.

Ultra HD Large screen delivers immersive viewing experience by 4 times higher definition picture quality than FHD.







High Efficiency Video Coding

Supports HEVC-based content which has the double data compression ratio than the H.264, so network traffic can be reduced by half.





Conventional H.264

UH5C

Multiple Screen



Multiple Screen with PBP or PIP

PBP (Picture-By-Picture) and PIP (Picture-In-Picture) feature gives a chance to compose up to 4 divided split screen on landscape or portrait display format.







PBP - Landscape

PBP - Portrait



Muliple Screen Split-Ultra HD Signage

Ultra HD UH5C



Screen Sizes

86", 75"

UH5C Series

- Brightness: 500cd/m2
- Bezel: 86" (14.7mm Even Bezel) 75" (14.9mm Even Bezel)
- Depth : 86" (60.6mm / without logo, handle) 75" (39.7mm / without logo, handle)
- Interface: DP / HDMI / DVI / RS232C / RJ45 /
 - Pixel Sensor / SD Card / USB
- SuperSign W-Lite/C













Other Features

Smart Platform



Quad Core SoC*

The High Performance SoC can execute several tasks at the same time and provides smooth content playback.



*SoC: System-on-Chip

webOS 2.0

The webOS 2.0 platform provides powerful and convenient tools to create, including app development materials.



Space Management **Efficiency**



Slimmer Depth

With its slim depth and built-in speaker, which increases space efficiency, you don't need to install an extra media player. Also, you can move it conveniently with its handle on the back side.



Easy Maintenance



Real-Time Remote Monitoring

When an alarm occurs, an e-mail notification is sent using SuperSign C or SI SW through the SNMP Protocol. In case of malfunctions or errors, real-time remote care is available.



Embedded Template by SuperSign EZ

You can edit contents not only on your smart phone but also on your PC very easily and conveniently at any



Supportive Convenience

BEACON

With BEACON and Bluetooth Low Energy (BLE) supported by UH5C, retail stores can provide coupons and information in real-time.



OPS* Kit / HDBaseT Box

The UH5C provides an OPS Kit to connect a third-party OPS player or HDBaseT box. Users have the flexibility to choose any media player as long as it complies with the OPS.




*OPS: Open Pluggable Specification

Dimension


86"

 $75.8" \times 43.4" \times 2.5" / 108lbs (Without handle) \\ 75.8" \times 43.4" \times 3.1" (With handle) \\ *Without logo$



75"

66.2" \times 37.8" \times 2.3" / 91.5lbs (Without Handle) 66.2" \times 37.8" \times 2.9"(With Handle) *Without logo



Specifications


UH5C		86UH5C	75UH5C
	Screen Size	86"	75"
PANEL	Panel Technology	IPS	IPS
	Aspect Ratio	16:9	16:9
	<u> </u>		
	Native Resolution	3,840 x 2,160 (UHD)	3,840 x 2,160 (UHD)
	Brightness	500cd/m ²	500cd/m ²
	Contrast Ratio	1,200:1	1,200:1
	Dynamic CR	4,000,000:1	4,000,000:1 (DTV Label only)
	Viewing Angle (H x V)	178 x 178	178 x 178
	Response Time	8ms (G to G)	6ms (G to G)
	Surface Treatment	Low Haze 3%	Low Haze 3%
	Life time (Min.)	50,000 Hours	50,000 Hours
	Guaranteed Operation Hours	24 Hours	24 Hours
	Orientation	Portrait & Landscape	Portrait & Landscape
	Input	HDMI, DP, DVI-D, Audio, USB 3.0, SD Card	HDMI, DP, DVI-D, Audio, USB 3.0, SD Card
	Output	DP, Audio	DP, Audio
	External Control	RS232C, RJ45, IR Receiver, Pixel Sensor	RS232C, RJ45, IR Receiver, Pixel Sensor
PHYSICAL SPECIFICATION	Bezel Color	Black	Black
	Bezel Width	14.7mm	14.9mm
	Monitor Dimension (W x H x D)	75.8" x 43.2" x 2.4" (without Logo/Handle)	66.2" x 37.8" x 2.3" (without Logo/Handle)
	Weight (Head)	108lbs	91.5lbs
	Carton Dimensions (W x H x D)	81.6" x 49.6" x 11.5"	71.5" x 44.2" x 9"
	Packed Weight	134.7lbs	109.1lbs
	VESA™ Standard Mount Interface	600 x 400mm	600 x 400mm
SPECIAL FEATURES		Temperature Sensor, Auto Brightness Sensor, Tile Mode (up to 15x15), Natural Mode@Tile Mode, ISM Method, Internal Memory, Wi-Fi built-in, USB Cloning, Contents Scheduling, Sync mode, PM mode, Fail Over, Wake on LAN, BEACON (On/Off), Embedded Template	
ENVIRONMENT CONDITIONS	O	32°F to 104 °F	32°F to 104 °F
	Operation Temperature Range	32 F t0 104 F	32 F LO 104 F
ONDITIONS	Operation lemperature Range Operation Humidity Range	10 % to 80 %	10 % to 80 %
ONDITIONS			
ONDITIONS	Operation Humidity Range	10 % to 80 %	10 % to 80 %
	Operation Humidity Range Power Supply Power Type Tvp.	10 % to 80 % 100-240V~, 50/60Hz	10 % to 80 % 100-240V~, 50/60Hz
	Operation Humidity Range Power Supply Power Type	10 % to 80 % 100-240V~, 50/60Hz Built-In Power	10 % to 80 % 100-240V~, 50/60Hz Built-In Power
OWER	Operation Humidity Range Power Supply Power Type Power Consumption Smart Energy	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 240W
OWER	Operation Humidity Range Power Supply Power Type Power Consumption Typ. Smart Energy Saving	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W
OWER	Operation Humidity Range Power Supply Power Type Power Consumption Safety Operation Humidity Range Typ. Smart Energy Saving	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC
OWER TANDARD CERTIFICATION)	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC
OWER TANDARD CERTIFICATION) TEDIA PLAYER	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No
OWER TANDARD CERTIFICATION) TEDIA PLAYER OMPATIBILITY OFTWARE	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star OPS type compatible	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes
OWER TANDARD CERTIFICATION) MEDIA PLAYER COMPATIBILITY OFTWARE	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star OPS type compatible External Media player Attachable	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700)	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700)
COMPATIBILITY	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star OPS type compatible External Media player Attachable SuperSign W-Lite	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700) Yes	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700) Yes Yes
OWER TANDARD CERTIFICATION) TEDIA PLAYER OMPATIBILITY OFTWARE OMPATIBILITY	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star OPS type compatible External Media player Attachable SuperSign W-Lite SuperSign C	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes Yes Remote Controller (include 2ea batteries), Power Cord, QSG, DP 1.8M, Regulation Book, Phone to RS232C	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700) Yes Yes Remote Controller (include 2ea batteries), Power Corc QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover
CONDITIONS CONDITIONS COMPATIBILITY COMPATIBILITY ACCESSORY	Operation Humidity Range Power Supply Power Type Power Consumption Safety EMC ErP / Energy Star OPS type compatible External Media player Attachable SuperSign W-Lite SuperSign C Basic	10 % to 80 % 100-240V-, 50/60Hz Built-In Power 275W 193W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700) Yes Yes Remote Controller (include 2ea batteries), Power Cord, QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover Pixel sensor(KT-SP0), Media player, OPS Kit(KT-OPSA),	10 % to 80 % 100-240V~, 50/60Hz Built-In Power 240W 170W UL / cUL / CB / TUV / KC FCC Class "A" / CE / KCC No / No Yes Yes (MP500/MP700) Yes Yes Remote Controller (include 2ea batteries), Power Corc QSG, DP 1.8M, Regulation Book, Phone to RS232C Gender, Memory Cover Pixel sensor(KT-SP0), Media player, OPS Kit(KT-OPSA)

Connectivity

2 AUDIO IN
3 AUDIO OUT 4 DP OUT

5 DVI-D IN

6 PIXEL SENSOR 11 HDMI IN 1
7 IR & LIGHT SENSOR 12 USB 3.0 IN
8 DP IN 13 SD CARD
9 HDMI IN 3 12 RS-232C IN
10 HDMI IN 2 15 RS-232C OUT



HDMI"

Download LG Commercial Display Mobile App





More info Lg.com/us/commercial



