

Projectors

Ricoh PJ WXC4660

Ricoh PJ WUC4650

RICOH
imagine. change.

Ultra Short Throw projection for brighter images

Ricoh PJ WXC4660 and PJ WUC4650 are the new Ultra Short Throw projectors with an HLD (High Lumen Density) LED light source technology ensuring 20,000h extremely long life with reduced electricity consumption. Impressive image quality makes these models a perfect fit for mid-sized venues like meeting rooms, board rooms, classrooms and auditoriums. Thanks to the maintenance-free concept (no lamp replacement), the devices could be used for digital signage as well.

- Ultra Short Throw projection from just 75cm for screen size of 130 inches
- Exceptionally long life of 20,000h thanks to the new HLD light source technology
- Powerful speakers and 4,000lm brightness optimal for corporate/ education environments or digital signage
- Flexibility based on compatibility with room control systems like Crestron, AMX and PJ-Link
- Eco-friendly solution with reduced electricity consumption



Hardware specifications

| KEY FEATURES | PJ WXC4660 | PJ WUC4650 |
|---|--|--|
| Brightness | 4,000 lm | 3,600 lm |
| Throw Ratio | 0.27:1 (Ultra Short Throw) | 0.27:1 (Ultra Short Throw) |
| Light Source | High Lumen Density (HLD) LED | High Lumen Density (HLD) LED |
| Light Source Life | 20,000h | 20,000h |
| Resolution | WXGA, 1280x800 pixels | WUXGA, 1920x1200 pixels |
| Contrast Ratio | 500:1 | 450:1 |
| Device | 3-LCD | 3-LCD |
| Screen size | 70-130 inches | 70-130 inches |
| Weight | 10.9kg | 10.9kg |
| Focus | Manual | Manual |
| Zoom | Manual | Manual |
| Zoom Ratio | 1.05 | 1.05 |
| Lens Shift | Horizontal / Vertical (Motorized) | Horizontal / Vertical (Motorized) |
| Power Consumption | Full: 410W@220V ECO: 288W@220V | Full: 425W@220V ECO: 294W@220V |
| Standby Power | <0.5V | <0.5V |
| Noise | Normal 37.5dB, Eco 33.5dB | Normal 37.5dB, Eco 33.5dB |
| Speaker | 2 x 10W | 2 x 10W |
| Network Projection | Wired LAN | Wired LAN |
| 4 Corner Adjustment | Yes | Yes |
| 360° Tilt Free | Yes | Yes |
| Crestron / AMX / Extron / PJ-Link Compatibility | Yes | Yes |
| Interface | D-sub-in x1, D-sub-out x1, Video in x1, 3.5mm ST Mini Jack x1(In/out), RCA(R/L)x1, HDMI(MHL) x1, HDMIx1, Control LAN x1, USB Type A x1, USB-B(mini) x1 | D-sub-in x1, D-sub-out x1, Video in x1, 3.5mm ST Mini Jack x1(In/out), RCA(R/L)x1, HDMI(MHL) x1, HDMIx1, Control LAN x1, USB Type A x1, USB-B(mini) x1 |

