


Overview

HPE Storage Fibre Channel Switch C-Series SN6710C

The HPE Storage Fibre Channel Switch C-Series SN6710C (MDS 9124V) is the next generation 24-port 64Gbps Fibre Channel Switch providing high-speed Fibre Channel connectivity from the server rack to the SAN core. It empowers small, midsize, and large enterprises that are rapidly deploying cloud-scale applications providing the benefits of greater bandwidth, scale, and consolidation. The switch allows seamless transition to Fibre Channel Non-Volatile Memory Express (FC-NVMe) workloads whenever available without any hardware upgrade in the SAN. The HPE Storage Fibre Channel Switch C-Series SN6710C is offered with 24 ports partially or fully populated with either 32Gb or 64Gb transceivers. For ultimate flexibility, the HPE SN6710C Switch scales from eight to twenty-four ports.

The HPE Storage Fibre Channel Switch C-Series SN6710C can be provisioned, managed, monitored, and troubleshot using Nexus Dashboard Fabric Controller (NDFC) (previously called Data Center Network Manager (DCNM)) which currently manages the entire suite of Cisco data center products. Powered by C-series MDS 9000 NX-OS Software, it includes storage networking features and functions and is compatible with C-series SN8700C (MDS 9700) Series Multilayer Directors, C-series SN6010C (MDS 9148S) Multilayer Fabric Switches, C-series SN6610C (MDS 9132T), C-series SN6620C (MDS 9148T) Multilayer Fabric Switches, C-series SN6630C (MDS 9396T) Multilayer Fabric Switches, C-series SN6720C (MDS 9148V) Multilayer Fabric Switches, and C-series SN6640C (MDS 9220i) Multi-service Fabric Switches, providing transparent, end-to-end service delivery in core-edge deployments.



HPE Storage Fibre Channel Switch C-Series SN6710C

Standard Features

Key Features and Benefits

- **High Performance for AFA and virtualized workloads**
 - Up to 1536 Gbps of aggregate bandwidth in a 1 rack unit (RU)
 - Up to 24 autosensing Fibre channel ports capable of speeds of 8/16/32/64 Gbps
 - Offered partially or fully populated with either of 32Gb or 64Gb optics
 - Offering ultimate flexibility, from eight to twenty-four ports, configurable with 16, 32, or 64 Gb FC SFP+ optics
- **Intelligent network services for modern SAN**
 - N-Port ID Virtualization (NPIV) technology to provide independent management for each virtual machine
 - N-Port Virtualization (NPV) and fabric-port (F-port) channeling features to enable scaling of SANs without reaching Fibre Channel domain ID limits
 - Representational State Transfer (REST) and NX-API capabilities to enable flexible and rapid programming of utilities for the SAN.
- **High Availability Platform**
 - Designed for environments in which downtime is unacceptable
 - Non-disruptive software upgrades, dual hot swappable power supplies, and back to front port-side exhaust hot swappable fans
 - VSANs for fault isolation and PortChannels for Inter-Switch Link (ISL) resiliency
- **Simplified Management**
 - Supports SAN plug and play capability
 - Centralized management tool with task-based wizards that simplifies management of a standalone switch or multiple switches and fabrics. Reduced total cost of ownership

Industry leading 64-Gb Performance Capability

The switch offers full non-blocking 64-Gbps Fibre Channel performance on 24 non-oversubscribed line-rate ports and an aggregate bandwidth of 1536 Gbps in each direction in a 1 Rack unit form factor.

Scalability

The HPE Storage Fibre Channel Switch C-Series SN6710C is offered in either 32Gb or 64Gb partially or fully populated options. . The HPE Storage Fibre Channel Switch C-Series SN6710C comes in five preconfigured models; 8 ports active with 0 SFPs bundled, 8-ports with 32Gb SFPs bundled, 8-ports with 64Gb SFPs bundled, 24-ports with 32Gb SFPs bundled, or 24-ports with 64Gb SFPs bundled. The SN6710C model can grow by 8 ports, up to 24-ports by installing the 8-port FC Upgrade License (additional SFPs required).

Cost Effective Intelligent Storage Networking

The HPE Storage Fibre Channel Switch C-Series SN6710C comes standard in a compact, extremely cost-effective design that simplifies deployment and administration of small and medium-scale storage-area networks (SANs) and as an edge switch in a larger enterprise.

N-Port ID Virtualization (NPIV)

N-Port ID Virtualization (NPIV), a standard Fibre Channel protocol feature, individual virtual machines assume a full identity on the SAN so that Fibre Channel services such as zoning, Quality of Service (QoS), performance monitoring, and security can be provided to each virtual machine.

VSANs

VSAN, an industry standard for fabric virtualization capabilities, enables more efficient storage network use by creating hardware-based isolated environments within a single physical SAN fabric or switch. Up to 32 VSANs are supported per switch. Each VSAN can be zoned as a typical SAN and maintains its own fabric services for added scalability and resilience. VSANs allow the cost of SAN infrastructure to be shared among more users, while helping ensure segregation of traffic and retaining independent control of configuration on a VSAN-by-VSAN basis.



Standard Features

PortChannels

PortChannels allow users to aggregate up to 16 physical ISLs into a single logical bundle, providing optimized bandwidth use across all links. The bundle can consist of any port from the switch, helping ensure that the bundle remains active even in the event of a port failure.

High Availability

The HPE Storage Fibre Channel Switch C-Series SN6710C is designed for environments in which downtime is unacceptable. It offers:

- Non-disruptive software upgrades, In-Service Software Upgrade (ISSU)
 - Process monitoring and stateful process restart
 - Per-VSAN fabric services
 - Hot-swappable C-series SFP+ optics
 - Hot-swappable, dual redundant power supplies
 - Hot-swappable fan tray with switch integrated temperature and power management
 - Any port configuration for port channels
 - Port tracking
-

Simplified Storage Management

Single-pane management

The HPE Storage Fibre Channel Switch C-Series SN6710C can be provisioned, managed, monitored, and troubleshot using Nexus Dashboard Fabric Controller (NDFC) (previously called Data Center Network Manager (DCNM)), which currently manages the entire suite of Cisco data center products.

Interoperability

Offers compatibility with a broad range of Hewlett Packard Enterprise servers and operating systems, as well as disk and tape storage devices; see current compatibility matrix. Please refer to the Single Point of Connectivity Knowledge (SPOCK) website below for more details:

<https://h20272.www2.hpe.com/spock/>

Diagnostics

- Embedded diagnostics
 - Online Diagnostics
 - Link diagnostics (E Port and F Port)
 - Fibre Channel traceroute
-

Software Components, Included

NX-OS

HPE Storage Fibre Channel Switch C-Series SN6710C includes the Cisco MDS 9000 NX-OS Software operating system version 9.3(1) or higher, and a set of configuration, maintenance, and diagnostics tools. It also includes VSAN support, PortChannels, extended fabrics, and hardware-enforced zoning.

Advanced traffic management features, such as zone-based quality of service (QoS) and Inter-VSAN Routing (IVR), among others, are included with the optional HPE SN6710C/SN6720C Advantage or Premier License.



Standard Features

Software Components, Optional

HPE SN6710C 8-Port Upgrade E-LTU

The flexibility of the HPE Storage Fibre Channel Switch C-Series SN6710C is provided by the SN6710C 64Gb 8-port FC Upgrade license which enables upgrades from 8- to 24- ports in 8-port increments.

Cisco Smart Licensing and Subscription Licenses

Starting from Cisco NX-OS 9.2(2), Smart Licensing Using Policy is available for HPE C-Series switches. This enables the customer to purchase subscription-based licenses for a period of time.

For more information, refer to Cisco MDS Licensing Guide, Smart Licensing Using Policy:

<https://www.cisco.com/c/en/us/td/docs/dcn/mds9000/sw/9x/configuration/licensing/cisco-mds-9000-nx-os-licensing-guide-9x/smart-licensing-using-policy.html?dtid=ossdc000283>

Cisco Nexus Dashboard Fabric Controller

Cisco Data Center Network Manager (DCNM) is renamed as Cisco Nexus Dashboard Fabric Controller (NDFC) from Release 12.0.1a. Cisco NDFC is designed with an HTML-based web User Interface (UI), which is the main interface for the product. There is also a fully integrated device manager used for visualizing and managing each individual switch or director. Customers having an existing DCNM license, or the HPE SN6710C/SN6720C Advantage license below may use these features.

The day-to-day SAN operations, such as In-Service Software Upgrades (ISSU), Zoning, Event management, Port Monitoring (PMON), etc., are managed and maintained from the simplified web UI. The application is a platform providing historical data that can be used to help during day-to-day troubleshooting, viewing analytics data, and looking for SAN congestion through slow-drain analysis. NDFC is also critically important for reviewing event data, SNMP traps, syslogs, and consolidated auditing and reporting.

These features are available with the HPE SN6710C/SN6720C Advantage and Premier License.

HPE SN6710C/SN6720C Advantage E-LTU

The HPE SN6710C/SN6720C Advantage E-LTU (for the SN6710C and SN6720C Fabric Switches) is a combination of Nexus Dashboard Fabric Controller (NDFC) and Enterprise Package licenses. It comes with 1-, 3-, or 5-year terms and is provisioned through Cisco Smart Licensing.

The NDFC license offers includes advanced features such as historical performance data collection for network traffic hot-spot analysis, centralized management services and advanced application integration. The Enterprise package license includes a set of advanced traffic engineering and advanced security features that are recommended for all Enterprise SANs.

HPE SN6710C/SN6720C Premier E-LTU

The HPE SN6710C/SN6720C Premier E-LTU (for the Storage Switch C-series SN6710C and SN6720C Fabric Switches) is a combination of Nexus Dashboard Fabric Controller (NDFC), Enterprise Package, and SAN Analytics license features. This Premier License is offered in 1-, 3-, or 5-year terms and is provisioned through Cisco Smart Licensing

The NDFC license offers includes advanced features such as historical performance data collection for network traffic hot-spot analysis, centralized management services and advanced application integration. The Enterprise package license includes a set of advanced traffic engineering and advanced security features that are recommended for all Enterprise SANs. SAN Analytics offers end-to-end visibility into Fibre Channel block storage traffic. The solution is natively available on the storage area network due to its integrated-by-design architecture with the HPE Storage Switch C-series SN6710C. SAN Analytics delivers deep visibility into I/O traffic between the compute and the storage infrastructure. This information is in addition to the already-available visibility obtained from individual ports, switches, servers, virtual machines, and storage arrays that are integrated with Nexus Dashboard Fabric Controller (NDFC).

Notes: Starting from 12.0.1a, DCNM is renamed Nexus Dashboard Fabric Controller (NDFC). Read more at:

<https://www.cisco.com/c/en/us/products/collateral/cloud-systems-management/prime-data-center-network-manager/san-innovation-ndfc-so.html>



Service and Support

Warranty

(1-1-1) Hardware Warranty; 1-year parts; 1-year on-site (8x5, next business day response) and 1-year labor.

Notes: The hardware warranty covers firmware and embedded non-saleable software. Hardware or Software product installation is not included in the warranty but is available and highly recommended.

HPE Services

No matter where you are in your transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

<https://www.hpe.com/services>

Consulting services

No matter where you are in your journey to hybrid cloud, experts can help you map out your next steps. From determining what workloads should live where, to handling governance and compliance, to managing costs, our experts can help you optimize your operations.

<https://www.hpe.com/services/consulting>

HPE Managed Services

HPE runs your IT operations, providing services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

[HPE Managed Services | HPE](#)

Operational services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources. Meet service-level targets and business objectives with features designed to drive better business outcomes.

<https://www.hpe.com/services/operational>

Recommended Services

HPE Tech Care Service

HPE Tech Care Service is the operational support service experience for HPE products. The service goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Tech Care Service delivers a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Tech Care Service is available in three response levels. Basic, which provides 9x5 business hour availability and a 2-hour response time. Essential which provides a 15-minute response time 24x7 for most enterprise level customers, and Critical which includes a 6-hour repair commitment where available and outage management response for severity 1 incidents.

<https://www.hpe.com/services/techcare>

HPE Complete Care Service

HPE Complete Care Service is a modular, edge-to-cloud IT environment service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals through a personalized experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care Service provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

<https://www.hpe.com/services/complecare>



Service and Support

Other related services from HPE Services

HPE Lifecycle Services

HPE Lifecycle Services provide a variety of options to help maintain your HPE systems and solutions at all stages of the product lifecycle. A few popular examples include:

- Lifecycle Install and Startup Services: Various levels for physical installation and power on, remote access setup, installation and startup, and enhanced installation services with the operating system.
- HPE Firmware Update Analysis Service: Recommendations for firmware revision levels for selected HPE products, taking into account the relevant revision dependencies within your IT environment.
- HPE Firmware Update Implementation Service: Implementation of firmware updates for selected HPE server, storage, and solution products, taking into account the relevant revision dependencies within your IT environment.
- Implementation assistance services: Highly trained technical service specialists to assist you with a variety of activities, ranging from design, implementation, and platform deployment to consolidation, migration, project management, and onsite technical forums.
- HPE Service Credits: Access to prepaid services for flexibility to choose from a variety of specialized service activities, including assessments, performance maintenance reviews, firmware management, professional services, and operational best practices.

<https://www.hpe.com/services/lifecycle>

- For a list of the most frequently purchased services using service credits, see the [HPE Service Credits Menu](#)

HPE SAN Deployment Service

Hewlett Packard Enterprise delivers complete design and implementation services for Fibre Channel, FCoE, FCIP, SAS, and iSCSI SAN connectivity components.

Learn more: https://www.hpe.com/psnow/doc/5981-8527enw?jumpid=in_lit-psnow-red

HPE Installation Service

Provides for the basic hardware installation of HPE branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

Learn more: <https://h20195.www2.hpe.com/v2/Getdocument.aspx?docname=5981-9356enw>

HPE Education Services

Training and certification designed for IT and business professionals across all industries. Broad catalogue of course offerings to expand skills and proficiencies in topics ranging from cloud and cybersecurity to AI and DevOps. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options.

<https://www.hpe.com/services/training>

Defective Media Retention

An option available with HPE-Complete Care Service and HPE Tech Care Service and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and services options.



Service and Support

Parts and Materials

HPE will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

How to purchase services

Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find services at <https://ssc.hpe.com/portal/site/ssc/>

AI Powered and Digitally Enabled Support Experience

Achieve faster time to resolution with access to product-specific resources and expertise through a digital and data driven customer experience.

Sign into the HPE Support Center experience, featuring streamlined self-serve case creation and management capabilities with inline knowledge recommendations. You will also find personalized task alerts and powerful troubleshooting support through an intelligent virtual agent with seamless transition when needed to a live support agent.

<https://support.hpe.com/hpesc/public/home/signin>

Consume IT on your terms

HPE GreenLake edge-to-cloud platform brings the cloud experience directly to your apps and data wherever they are—the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake edge-to-cloud platform accelerates digital transformation in a distributed, edge-to-cloud world.

- Get faster time to market
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

To learn more about HPE Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE"

<https://www.hpe.com/us/en/contact-hpe.html>

For more information: <http://www.hpe.com/services>



Configuration Information

The HPE Storage Fibre Channel Switch C-Series SN6710C comes preconfigured with a maximum of 24 autosensing Fibre Channel ports capable of 64, 32, 16, and 8Gb in a compact 1RU form factor chassis. Customers can choose between partially or fully populated with 64Gb or 32Gb SFPs. The SN6710C switch comes in five preconfigured models; 8 ports active with 0 SFPs bundled, 8-ports with 32Gb SFPs bundled, 8-ports with 64Gb SFPs bundled, 24-ports with 32Gb SFPs bundled, or 24-ports with 64Gb SFPs bundled. The SN6710C model can grow by 8 ports, up to 24 ports by installing the 8-port FC Upgrade License (additional SFPs required).

Step 1 - Base Configuration (Select one)

Description	SKU
HPE SN6710C 64Gb 24/8 Fibre Channel Switch	
HPE SN6710C 64Gb 24/8 Fibre Channel Switch	S1V06A
<ul style="list-style-type: none"> 24-Port Fabric Switch with 8 active ports, Dual Power Supplies, Power Cords (configurable by ship-to country) and 4 Fans, VSANs, PortChannels, firmware, accessory kit, and documentation 	
HPE SN6710C 64Gb 24/8 32Gb Short Wave SFP+ Fibre Channel Switch	
HPE SN6710C 64Gb 24/8 32Gb Short Wave SFP+ Fibre Channel Switch	S1V09A
HPE SN6710C 64Gb 24/8 32Gb Short Wave SFP+ Fibre Channel v2 Switch	S1V09B*
<ul style="list-style-type: none"> 24-Port Fabric Switch with 8 active ports with 8x32Gb SW SFP+, Dual Power Supplies, Power Cords (configurable by ship-to country) and 4 Fans, VSANs, PortChannels, firmware, accessory kit, and documentation 	
HPE SN6710C 64Gb 24/8 64Gb Short Wave SFP+ Fibre Channel Switch	
HPE SN6710C 64Gb 24/8 64Gb Short Wave SFP+ Fibre Channel Switch	S1V10A
HPE SN6710C 64Gb 24/8 64Gb Short Wave SFP+ Fibre Channel v2 Switch	S1V10B*
<ul style="list-style-type: none"> 24-Port Fabric Switch with 8 active ports with 8x64Gb SW SFP+, Dual Power Supplies, Power Cords (configurable by ship-to country) and 4 Fans, VSANs, PortChannels, firmware, accessory kit, and documentation 	
HPE SN6710C 64Gb 24/24 32Gb Short Wave SFP+ Fibre Channel Switch	
HPE SN6710C 64Gb 24/24 32Gb Short Wave SFP+ Fibre Channel Switch	SOW92A
HPE SN6710C 64Gb 24/24 32Gb Short Wave SFP+ Fibre Channel v2 Switch	SOW92B*
<ul style="list-style-type: none"> 24-Port Fabric Switch with 24 active ports with 24x32Gb SW SFP+, Dual Power Supplies, Power Cords (configurable by ship-to country) and 4 Fans, VSANs, PortChannels, firmware, accessory kit and documentation 	
HPE SN6710C 64Gb 24/24 64Gb Short Wave SFP+ Fibre Channel Switch	
HPE SN6710C 64Gb 24/24 64Gb Short Wave SFP+ Fibre Channel Switch	SOW93A
HPE SN6710C 64Gb 24/24 64Gb Short Wave SFP+ Fibre Channel v2 Switch	SOW93B*
<ul style="list-style-type: none"> 24-Port Fabric Switch with 24 active ports with 24x64Gb SW SFP+, Dual Power Supplies, Power Cords (configurable by ship-to country) and 4 Fans, VSANs, PortChannels, firmware, accessory kit, and documentation. 	

Notes: *These part numbers include built-in discounts. No additional cost relief available.

Step 2 - Optional Software

Description	SKU
On Demand Port Activation License	
HPE SN6710C 64Gb 8-port Fibre Channel Upgrade E-LTU	S1X20AAE

Notes: SFPs not included with Port Activation License. Supported transceivers listed below.



Configuration Information

Description	SKU
Management Software	
HPE SN6710C/SN6720C Advantage 1-year E-LTU	SOX06AAE
HPE SN6710C/SN6720C Advantage 3-year E-LTU	SOX07AAE
HPE SN6710C/SN6720C Advantage 5-year E-LTU	SOX08AAE
HPE SN6710C/SN6720C Premier 1-year E-LTU	SOX03AAE
HPE SN6710C/SN6720C Premier 3-year E-LTU	SOX04AAE
HPE SN6710C/SN6720C Premier 5-year E-LTU	SOX05AAE

Notes: Advantage license is a combination of Nexus Dashboard Fabric Controller (NDFC) and Enterprise Package license features. **Premier license is a combination of Nexus Dashboard Fabric Controller (NDFC), Enterprise Package, and SAN Analytics license features.** HPE Premier and HPE Advantage licenses are offered with a bundle of software maintenance and support including access to software updates for the duration of the license; customers will not be able to purchase additional software support for these configurations. At the end of the license period, the customer will need to purchase a new software license to continue using the software. Software support renewal via HPE Services is not allowed/supported.

Step 3 - Options

Supported transceivers are listed below:

Description

64Gb FC Transceivers*

HPE C-series 64Gb SFP+ Short Wave Fibre Channel Transceiver	S0W91A
---	--------

32Gb FC Transceivers*

HPE C-series 32 Gb Fibre Channel Short Wave SFP+ Transceiver	Q9D30A
--	--------

HPE C-series 32 Gb Fibre Channel Long Wave SFP+ Transceiver	Q9D31A
---	--------

Notes: *Compatible with SFP28 MSA spec

16 Gb FC Transceivers

HPE C-series 16 Gb Fibre Channel SW SFP+ Transceiver	C8S72A
--	--------

HPE C-series 16 Gb Fibre Channel LW SFP+ Transceiver	C8S73A
--	--------

Notes: Each port on the SN6710C may be configured to accept Short or Long Wave SFP optical transceivers (as available). Current bundles are only configured with short wave SFP optical transceivers. Please use only the above Cisco SFP optical transceivers; no substitutions allowed. Using other transceivers may void product warranty.

Installation and Deployment Services

For complete design and implementation of Fibre Channel connectivity components, select **HPE SAN Deployment Service**
<http://h20195.www2.hpe.com/V2/GetPDF.aspx/5981-8527ENW.pdf>

For basic hardware installation, select **HPE Installation Service**
<https://h20195.www2.hpe.com/v2/Getdocument.aspx?docname=5981-9356enw>



Configuration Information

Recommended Cables

Description

SKU

HPE PremierFlex OM4+ Fiber Optic Cables

HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable	QK737A

HPE OM3 LC-LC Optical Cables

HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A



Technical Specifications

Family Information

	Switch Type	Maximum ports	Number of slots per chassis
HPE C-series SN8700C 4-slot/8-slot/16-slot 16/32/64Gb FC Director	Multilayer Director	4-slot: 192 16/32/64 Gbps Fibre Channel ports 8-slot: 384 16/32/64 Gbps Fibre Channel ports 16-slot: 768 16/32/64 Gbps Fibre Channel ports	Four/Eight/Sixteen
HPE Storage Switch C-series SN6730C	Multilayer Fabric Switch	Ninety-six 64 Gbps Fibre Channel ports	One fixed
HPE C-series SN6710C 64Gb Fabric Switch	Multilayer Fabric Switch	Twenty-four 64 Gbps Fibre Channel ports	One fixed
HPE C-series SN6720C 64Gb Fabric Switch	Multilayer Fabric Switch	Forty-eight 64 Gbps Fibre Channel ports	One fixed
HPE C-series SN6640C 32Gb Multi-service Switch	Multilayer Fabric Switch	Up to 12 32-Gbps Fibre Channel ports, four 1/10-, two 25-, and one 40- Ethernet IP storage services ports	One fixed
HPE C-series SN6630C 32Gb Fabric Switch	Multilayer Fabric Switch	Up to 96 32 Gbps Fibre Channel ports	One fixed
HPE C-series SN6620C 32Gb Fabric Switch	Multilayer Fabric Switch	Up to 48 32 Gbps Fibre Channel ports	One fixed
HPE C-series SN6610C 32Gb Fabric Switch	Multilayer Fabric Switch	Up to 32 32 Gbps Fibre Channel ports	One fixed and one expansion slot
HPE C-series SN6010C 16Gb Fabric Switch	Multilayer Fabric Switch	Up to 48 16 Gbps Fibre Channel ports	One fixed

Notes: For additional switch support information, refer to the C-series FC Switch Connectivity Stream on the Single Point of Connectivity Knowledge (SPOCK) website at: <https://h20272.www2.hpe.com/spock/>. You must sign up for a Hewlett Packard Enterprise Passport to enable access. Once logged in, click Switches under Other Hardware in the last navigation panel of the window to access the Fibre Channel Switch Streams. Click on the C-Series FC Switch Connectivity Stream to open the document.

Minimum software requirements

MDS 9000 NX-OS Software Release 9.3(1)

Performance and port configuration

- Port speed: 64, 32, 16 and 8 Gbps autosensing with 64 Gbps of dedicated bandwidth per port
- Buffer credits: Up to 24000 for a group of 24 ports, with a default of 1000 buffer credits per port and a maximum of 16000 buffer credits for a single port in the group
- Ports per chassis: Up to 24 64-Gbps ports
- Base configuration with 8-ports; additional configurations up to 24 ports.
- PortChannel: Up to 24 load balanced physical links in a PortChannel



Technical Specifications

Security

- VSANs fabric isolation
- Intelligent packet inspection at port level
- Hardware zoning by Access Control Lists (ACLs)
- FC-SP for host-to-switch and switch-to-switch authentication
- Port security
- Management access
 - SSHv2 implementing AES
 - SNMPv3 implementing AES
 - IP ACLs

Fabric Services

- Name server
- Registered state change notification (RSCN)
- Login services
- Fabric Configuration Server (FCS)
- Broadcast
- In-order delivery

Compatibility

Fibre Channel protocols

- FC-PH, Revision 4.3 (ANSI INCITS 230-1994)
- FC-PH, Amendment 1 (ANSI INCITS 230-1994/AM1-1996)
- FC-PH, Amendment 2 (ANSI INCITS 230-1994/AM2-1999)
- FC-PH-2, Revision 7.4 (ANSI INCITS 297-1997)
- FC-PH-3, Revision 9.4 (ANSI INCITS 303-1998)
- FC-PI, Revision 13 (ANSI INCITS 352-2002)
- FC-PI-6 (ANSI INCITS 512-2015)
- FC-PI-7 (ANSI INCITS 543-2019)
- FC-FS, Revision 1.9 (ANSI INCITS 373-2003)
- FC-FS-2, Revision 1.01 (ANSI INCITS 424-2007)
- FC-FS-2, Amendment 1 (ANSI INCITS 424-2007/AM1-2007)
- FC-FS-3, Revision 1.11 (ANSI INCITS 470-2011)
- FC-FS-4
- FC-LS, Revision 1.62 (ANSI INCITS 433-2007)
- FC-LS-2, Revision 2.21 (ANSI INCITS 477-2011)
- FC-LS-3, Includes revision 3.53
- FC-SW-2, Revision 5.3 (ANSI INCITS 355-2001)
- FC-SW-3, Revision 6.6 (ANSI INCITS 384-2004)
- FC-SW-4, Revision 7.5 (ANSI INCITS 418-2006)
- FC-SW-5, Revision 8.5 (ANSI INCITS 461-2010)
- FC-SW-6
- FC-GS-3, Revision 7.01 (ANSI INCITS 348-2001)
- FC-GS-4, Revision 7.91 (ANSI INCITS 387-2004)
- FC-GS-5, Revision 8.51 (ANSI INCITS 427-2007)
- FC-GS-6, Revision 9.4 (ANSI INCITS 463-2010)



Technical Specifications

- FC-GS-7, Includes revision 10.8
- FCP, Revision 12 (ANSI INCITS 269-1996)
- FCP-2, Revision 8 (ANSI INCITS 350-2003)
- FCP-3, Revision 4 (ANSI INCITS 416-2006)
- FCP-4, Revision 2b (ANSI INCITS 481-2011)
- FC-SB-2, Revision 2.1 (ANSI INCITS 349-2001)
- FC-SB-3, Revision 1.6 (ANSI INCITS 374-2003)
- FC-SB-3, Amendment 1 (ANSI INCITS 374-2003/AM1-2007)
- FC-SB-4, Revision 3.0 (ANSI INCITS 466-2011)
- FC-SB-5, Revision 2.00 (ANSI INCITS 485-2014)
- FC-BB-2, Revision 6.0 (ANSI INCITS 372-2003)
- FC-BB-3, Revision 6.8 (ANSI INCITS 414-2006)
- FC-BB-4, Revision 2.7 (ANSI INCITS 419-2008)
- FC-BB-5, Revision 2.0 (ANSI INCITS 462-2010)
- FC-BB-6, Revision 2.00 (ANSI INCITS 509-2014)
- FC-VI, Revision 1.84 (ANSI INCITS 357-2002)
- FC-SP, Revision 1.8 (ANSI INCITS 426-2007)
- FC-SP-2, Revision 2.71 (ANSI INCITS 496-2012)
- FAIS, Revision 1.03 (ANSI INCITS 432-2007)
- FAIS-2, Revision 2.23 (ANSI INCITS 449-2008)
- FC-IFR, Revision 1.06 (ANSI INCITS 475-2011)
- FC-FLA, Revision 2.7 (INCITS TR-20-1998)
- FC-PLDA, Revision 2.1 (INCITS TR-19-1998)
- FC-Tape, Revision 1.17 (INCITS TR-24-1999)
- FC-MI, Revision 1.92 (INCITS TR-30-2002)
- FC-MI-2, Revision 2.6 (INCITS TR-39-2005)
- FC-MI-3, Revision 1.03 (INCITS TR-48-2012)
- FC-DA, Revision 3.1 (INCITS TR-36-2004)
- FC-DA-2, Revision 1.06 (INCITS TR-49-2012)
- FC-MSQS, Revision 3.2 (INCITS TR-46-2011)
- Fibre Channel classes of service: Class 2, Class 3, and Class F
- Fibre Channel standard port types: E and F
- Fibre Channel enhanced port types: SD, ST, and TE
- NVMe/FC
- In-band management using IP over Fibre Channel (RFC 2625)
- IPv6, IPv4, and Address Resolution Protocol (ARP) over Fibre Channel (RFC 4338)
- Extensive IETF-standards-based TCP/IP, Simple Network Management Protocol Version 3 (SNMPv3), and Remote Monitoring (RMON) MIBs

Advanced Services

Please note that some services require the optional HPE SN6710C/SN6720C Advantage or Premier license.

- NPIV
 - VSAN
 - PortChannels
 - NPV mode
 - Flow-based and zone-based QoS
 - IVR (in Cisco MDS 9000 NX-OS Software Release 8.3(1) or later)
-

Technical Specifications

Diagnostic and Troubleshooting

- SPAN
 - POST (Power-on-Self-Test) diagnostics
 - Online Health Management System (OHMS) diagnostics
 - Internal loopbacks
 - Fibre Channel traceroute
 - Fibre Channel ping
 - Syslog
 - Port-level statistics
 - Link diagnostics (E-port and F-port links)
 - Read Diagnostic Parameter
-

Management

- Access methods
 - Out-of-band 10/100/1000 Ethernet port
 - RS-232 serial console port
 - Access protocols
 - Command-Line Interface (CLI) using the console and Ethernet port
 - SNMPv3 using the Ethernet port and in-band IP over Fibre Channel access
 - NX-API for HTTP/HTTPS Full Programmability
 - Security
 - Per-VSAN RBAC using LDAP, RADIUS, and TACACS+-based AAA functions
 - VSAN-based roles
 - SSHv2 implementing AES
 - SNMPv3 implementing AES
 - Simple File Transfer Protocol (SFTP)
-

Management Applications

- Cisco MDS 9000 Family CLI
 - C-series Nexus Dashboard Fabric Controller (optional; requires license which includes Nexus Dashboard Fabric Controller features)
-

Availability

- Non-disruptive software upgrades
 - Process monitoring and stateful process restart
 - Per-VSAN fabric services
 - Hot-swappable SFP and SFP+ optics
 - Up to 24 load balanced physical links in a PortChannel
-



Technical Specifications

Safety

- CE Marking
 - UL 60950
 - CAN/CSA-C22.2 No. 60950
 - EN 60950
 - IEC 60950
 - TS 001
 - AS/NZS 3260
 - IEC 60825
 - EN 60825
 - 21 CFR 1040
-

EMC

- FCC Part 15 (CFR 47) Class A
 - ICES-003 Class A
 - EN55022 Class A
 - CISPR22 Class A
 - AS/NZS 3548 Class A
 - VCCI Class A
 - EN55024
 - EN50082-1
 - EN61000-3-2
 - EN61000-3-3
 - EN61000-6-1
-

Serviceability

- Configuration file management
 - Port beaconing (Link Cable Beaconing)
 - System LEDs
 - SNMP traps for alerts
-

Environmental

- Physical dimensions (H x W x D) of 1RU: 1.72 x 17.3 x 18 in. [4.37 x 43.94 x 45.72 cm]) excluding Power Supply Unit (PSU) and fan-tray handles)
 - Weight of fully configured chassis: 18.73 lb (8.5 kg)
 - Ambient operating temperature: 32 to 104°F (0 to 40°C)
 - Ambient non-operating temperature: -40 to 158°F (-40 to 70°C)
 - Humidity (RH), ambient (noncondensing) operating: 10 to 90%
 - Humidity (RH), ambient (noncondensing) non-operating and storage: 10 to 95%
 - Operating altitude: -197 to 6500 ft (-60 to 2000 m)
-



Technical Specifications

Power and Cooling

- Power supplies (500W AC) (maximum of 2 per switch)
 - AC Input: 100 to 240 VAC nominal (+/-10% for full range)
 - Frequency: 50 to 60 Hz nominal (+/-3 Hz for full range)
 - Typical power consumption:
 - ° 286W for 24-Port switch with 24 64G SW optics modules under 50% line rate
 - Airflow: Rear to front (toward ports)
 - HPE recommends maintaining a minimum air space of 2.5 in. (6.4 cm) between walls and chassis air vents and a minimum horizontal separation of 6 in. (15.2 cm) between two chassis to prevent overheating
-






Summary of Changes

Date	Version History	Action	Description of Change
15-Apr-2024	Version 7	Changed	Rebranding Series Name applied
08-Jan-2024	Version 6	Changed	Standard Features, Configuration Information and Technical Specifications sections were updated. Added SN6710C/SN6720C Premier Licenses
13-Nov-2023	Version 5	Changed	HPE Service Rebranding
02-Oct-2023	Version 4	Changed	HPE Re-branding - Series name and HPE Services information updated
07-Aug-2023	Version 3	Changed	Overview, Standard Features, Configuration Information and Technical Specifications sections were updated. Added new program PNs
05-Jun-2023	Version 2	Changed	Overview, Service and Support, Configuration Information and Technical Specifications sections were updated. Updates/Added Volume Program PNs
06-Mar-2023	Version 1	New	New QuickSpecs



Copyright

**Make the right purchase decision.
Contact our presales specialists.**



© Copyright 2024 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

a50006981enw - 17091 - Worldwide - V7 - 15-April-2024