

HP 65W GaN USB-C LC Power Adapter

Universal Compatibility. Everyday Reliability.

Charge with confidence wherever you go. This 65W GaN USB-C® adapter delivers fast, efficient¹ power across devices⁵, with a portable design that keeps everyday charging simple and clutter-free.



*Product image may differ from actual product



Reliable Power for Daily Demands

Experience faster, more efficient charging without added bulk. Powered by GaN technology^{1,2}, this 65W adapter delivers higher-density power with less heat, supporting power-heavy notebooks and helping reduce charging time.



One Charger for Every Device

Simplify charging across devices with a universal USB-C® PD 3.0^{3,4} solution. Designed to work seamlessly with USB-C®-enabled notebooks and devices⁵, this 65W adapter eliminates the need for device-specific chargers, making everyday charging simpler and convenient.



Charge Faster. Stay Productive.

Spend less time plugged in. With HP Fast Charge Technology, select HP notebooks can reach up to a 50% charge in just 30 minutes⁶, helping reduce downtime and keeping productivity moving.

Sustainability in action

Built for a Better Tomorrow

Thoughtfully designed, this compact and reliable power adapter contains at least 25% post-consumer recycled plastic⁷, and comes with FSC®-certified packaging.



HP 65W GaN USB-C LC Power Adapter

Specifications



Product number	D36ZXAA
Supported platforms	Supports up to 65 W power delivery
UPC number	(AB0) 199896482431; (AB1) 199896482448; (AB2) 199896482455; (ABA) 199896551212; (ABB) 199896482462; (ABG) 199896482479; (ABJ) 4573620141614; (ABM) 199896482486; (ABT) 199896482493; (ABU) 199896482509; (ABY) 199896482516; (ABZ) 199896482523; (AC4) 199896482530; (ACJ) 199896482547; (ACQ) 199896482554; (AKL) 199896482561; (AR6) 199896482578; (UUF) 199896482585; (UUZ) 199896482592
Connection type	USB Type-C®
Input operating current	1.6 A at 90 VAC max
Input efficiency	89% min at 115 VAC/230 VAC at 20V/3.25A
Output power	65 W
Output voltages	5V/9V/15V/20V
Hold-up time	5 ms at 115 VAC input
Cable length	70.87 in (non-detachable USB-C cable); 39.37 in (Power cord);
System Requirements, Minimum	USB Type-C® port
Warranty	HP standard one-year limited warranty ²
Certifications and compliances	CE Mark; IEC 60950-1; UL 62368-1; C-UL-US; FCC Class B; CISPR 32 Class B; CCC; BSMI; ISC; PSB; EN62368-1; EN 55032 Class B; IEC 62368-1; BIS; CECP; TUV/GS; TUV/PSE; EAEU; KCC; K-MEPS; NRCan; NRCS; SEC; Argentina S-Mark; UAE; UKCA DoC; CU (EAC); Australia RCM
What's in the box	AC power adapter; Power cord; Warranty card
Dimensions (W x D x H)	3.58 x 2.09 x 1.24 in
Weight	0.55 lb
Package dimensions (W x D x H)	8.56 x 3.76 x 2.4 in;
Package weight	
Sustainable impact specifications	FSC Certified Packaging; 25% post-consumer recycled plastic ¹
Operating temperature range	32 to 95°F; 0 to 35°C
Operating altitude	Up to 16,400 ft
Operating humidity range	20 to 95% RH



HP 65W GaN USB-C LC Power Adapter

Footnotes

Messaging Footnotes

- ¹ Compliant with IEC 62368-1 and EU Lot7 power efficiency.
- ² Compliant with the latest safety standards (IEC 62368-1).
- ³ Supports USB-C® PD protocol.
- ⁴ Up to 65W max output.
- ⁵ Compatible with most devices that charge using USB-C®.
- ⁶ Recharges your HP laptop battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter minimum of 65 watts required for battery capacities 56Wh or less. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.
- ⁷ Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT criteria.

Technical Specifications Footnotes

- ¹ Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT criteria.
- ² Please refer to the warranty card supplied with the product for details. Warranty may vary by country as required by law. Go to hp.com/support to learn about HP award winning service and support options in your region.

