

## EnviroSense2 (E2) Environmental Sensor Module, Temperature, TAA

MODEL NUMBER: E2MT



Monitors ambient temperature conditions.

### Description

The E2MT E2 Environmental Sensor Module works with LX Platform devices, including WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MT allows you to remotely monitor ambient temperature conditions in network environments.

If temperature values exceed a certain limit, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MT mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

### Features

**Compatible with LX Platform Devices** Compatible devices include WEBCARDLX, WEBCARDLXE, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs Measures and monitors ambient temperature

**Easy to Install and Operate** Attaches magnetically to most racks and cabinets Up to 3 E2 modules can be daisy-chained together Built-in cable harness reduces clutter USB cable included Compatible with free downloadable PowerAlert software

### Highlights

- Compatible with LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

### Package Includes

- E2MT EnviroSense2 Environmental Sensor Module
- USB cable (A to Micro-B), 3 ft.
- Owner's manual

## Specifications

| OVERVIEW             |                      |
|----------------------|----------------------|
| UPC Code             | 037332196293         |
| CONNECTIONS          |                      |
| Side A - Connector 1 | USB A (FEMALE)       |
| Side B - Connector 1 | MICRO-USB B (FEMALE) |
| PHYSICAL             |                      |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| Cable Length (ft.)                   | 3                                    |
| Cable Length (m)                     | 0.91                                 |
| Shipping Dimensions (hwd / in.)      | 1.10 x 4.20 x 5.90                   |
| Shipping Dimensions (hwd / cm)       | 2.79 x 10.67 x 14.99                 |
| Shipping Weight (lbs.)               | 0.28                                 |
| Shipping Weight (kg)                 | 0.13                                 |
| Unit Dimensions (hwd / in.)          | 0.830 x 2.520 x 1.420                |
| <b>COMMUNICATIONS</b>                |                                      |
| Product Compatibility                | WEBCARDLX; WEBCARDLXMINI; WEBCARDLXE |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                      |
| Sensing Capability                   | Temperature                          |
| Contact Closure Capability           | Contact Closure Input Monitoring     |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                      |
| Product Compliance                   | Trade Agreements Act (TAA)           |
| <b>WARRANTY &amp; SUPPORT</b>        |                                      |
| Product Warranty Period (Worldwide)  | 2-year limited warranty              |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.