

Product datasheet

Specifications



Rack PDU Extender, Basic, 2U, 32A, 230V, (4) IEC C19

AP7585

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	8.5 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	8.9 cm
Width	43.7 cm
Output Voltage	230 V
Depth	8.9 cm
Net weight	4.09 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire
Outlet type and quantity	4 IEC 60320 C19

Environment

Product certifications	CE GOST VDE
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	52.1 cm
Package 1 Length	52.1 cm
Package 1 Weight	4.99 kg

Logistical informations

Country of origin	IN
--------------------------	----

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)