

Product data sheet

Specifications



APC Network SurgeArrest, 7 outlet



NET7

⚠ Discontinued on: Feb 14, 2024

⚠ To be discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V

Input Connection Type NEMA 5-15P

Cable length 6 ft (1.8 m)

Number of cables 1

Provided equipment User manual

Physical

Colour Beige

Height 2.008 in (5.1 cm)

Width 4.3 in (10.8 cm)

Depth 10.5 in (26.7 cm)

net weight 2.006 lb(US) (0.91 kg)

Mounting preference No preference

mounting mode Not rack-mountable

Input

Maximum line current 15 A

Network frequency 50/60 Hz +/- 5 Hz auto-sensing

Output

Number of power socket outlets 7

Outlet standard NEMA 5-15R

Conformance

UL 1449 TVSS rating 330

Product certifications CSA

Standards UL 1283
UL 1363
UL 1449

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Equipment protection policy	Lifetime : \$100000
-----------------------------	---------------------

Environmental

Ambient air temperature for operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Surge Protection and Filtering

EP joule rating	3420 J
Response time	0 ns common mode
Common mode rejection	70 dB
Peak current	26 kAcommon mode 13 kAnormal mode
Surge energy rate	1680 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.09 in (5.3 cm)
Package 1 Width	12.8 in (32.4 cm)
Package 1 Length	7.2 in (18.4 cm)
Package 1 Weight	2.31 lb(US) (1.05 kg)
SCC14	10731304000201

Contractual warranty

Warranty	Limited Lifetime
----------	------------------