



## rSeries 4222-15 Case

SKU: 3R4222-15B-E



### Description

The rSeries Mil-Standard cases have been designed to meet the most exacting military specifications. They are roto-molded of impact-resistant/UV stabilized LLDPE for strength and durability, featuring airtight and waterproof construction with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions. Our rSeries cases come standard with an empty interior, and some models are available with: cubed foam, layered foam, padded dividers, and a pull handle with wheels.

### Features

- Waterproof and dust tight design (MIL-STD 810H)
- LLDPE Polyethylene impact resistant
- UV, solvents, corrosion, fungus resistant (MIL-STD 810H)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD 810H)
- Stainless steel latches and hinges

### Specifications

|                            |          |           |
|----------------------------|----------|-----------|
| Exterior                   | Hard     |           |
| Built In Wheels or Casters | No       |           |
| Interior Length            | 41.75 in | 106.05 cm |
| Interior Width             | 21.75 in | 55.24 cm  |

|                     |          |           |
|---------------------|----------|-----------|
| Interior Lid Depth  | 3.375 in | 8.57 cm   |
| Interior Base Depth | 11.5 in  | 29.21 cm  |
| Product Weight      | 54.18 lb | 24.58 kg  |
| Exterior Length     | 45 in    | 114.30 cm |
| Exterior Width      | 25.25 in | 64.14 cm  |
| Exterior Height     | 18 in    | 45.72 cm  |
| Carton Length       | 46 in    | 116.84 cm |
| Carton Width        | 25.5 in  | 64.77 cm  |
| Carton Height       | 18.5 in  | 46.99 cm  |
| Shipping Weight     | 58.52 lb | 26.54 kg  |
| Max Temp            | 0 °F     | -17.8 °C  |
| Min Temp            | 0 °F     | -17.8 °C  |

**AVAILABLE CONFIGURATIONS**

|              |                      |
|--------------|----------------------|
| 3R4222-15B-E | Black / Empty        |
| 3R4222-15B-L | Black / Layered Foam |