

## 8-Port Metal DIN-Rail Mounting Keystone Patch Panel with Grounding, Black/Silver, TAA

MODEL NUMBER: N063-008-ENC



Accepts snap-in keystone jacks and couplers to help you manage your DIN-rail network cable application.

### Features

#### Organizes a Wide Variety of Ethernet Network Patch Cables in Your DIN-Rail Installation

This DIN-rail mounting patch panel lets you manage network cable interconnectivity with eight blank cutouts, which accommodate all Tripp Lite snap-in keystone jacks and in-line couplers. Each RJ45 Ethernet cutout features metal contacts for grounding purposes. The N063-008-ENC also allows patching with Tripp Lite NGI/NFI DIN-rail-mount Ethernet switches (sold separately).

#### Easy to Install in Rugged Industrial Applications

Made from sheet metal with a plastic rear frame, the N063-008-ENC quickly installs on a standard 35-millimeter DIN rail. Ports are numbered to help you organize your application and identify specific connections. A grounding wire is included.

#### TAA-Compliant for GSA Schedule Purchases

The N063-008-ENC is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

## Specifications

OVERVIEW	
UPC Code	037332276933
Technology	Cat5/5e; Cat6; Cat6a
Firmware / Software Docs	
Offset Ports	No
PHYSICAL	

### Highlights

- Rugged metal front construction with plastic rear frame for industrial applications
- 8 front blank cutouts compatible with all Tripp Lite keystone jacks and couplers
- Numbered ports allow at-a-glance identification of cable connections
- Built-in mounting clip attaches easily to standard 35 mm DIN rail with no tools needed
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Package Includes

- N063-008-ENC Metal DIN-Rail Mounting Keystone Patch Panel, 8 Ports
- Grounding wire
- Installation instructions



Primary Form Factor	Din-Rail
Color	Black; Silver
Material of Construction	Plastic (PC FR) & Metal (SPCC/FE)
Total Number of Ports	8
Shipping Dimensions (hwd / in.)	2.36 x 7.87 x 3.15
Shipping Weight (lbs.)	0.51
Unit Dimensions (hwd / in.)	6.060 x 2.190 x 3.100
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	-13 to 122 F (-25 to 50 C)
Storage Temperature Range	-40 to 70 F (-40 to 158 C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	10% to 85% RH, Non-Condensing
<b>CONNECTIONS</b>	
Number of Ports	8
Side A - Connector 1	(8) KEYSTONE JACK CUTOUT
<b>FEATURES &amp; SPECIFICATIONS</b>	
Keystone Jacks	Yes
All-in-One Kit	No
Down-Angled Ports	No
Built-in Cables	No
Color-Coded Connections	No
Numbered Ports	Yes
EIA/TIA 2/32 Spacing	No
Labeled Ports	No
DIN Mountable	Yes
IP68 Rated	No
Panel Applications	Ethernet
Antibacterial	No
IP20 Rated	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Compliance	CE (Europe); REACH; RoHS; UKCA
<b>WARRANTY &amp; SUPPORT</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Product Warranty Period (Worldwide)	Lifetime limited warranty
--	---------------------------

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>