

Product data sheet

Specifications



Rack PDU, Basic, Zero U, 16A, 208/230V, (15) C13



AP9572

Overview

Lead time Usually in Stock

Main

Color Black

Product or Component Type PDU

PDU Type Basic

Cord length 8.2 ft (2.5 m)

Number of cables 1

Provided Equipment Rack Mounting brackets
Toolless Mounting Kit
User Manual

Complementary

Input Voltage 200 V
208 V
230 V

Height 24.4 in (62 cm)

Width 1.7 in (4.4 cm)

Output Voltage 200 V
208 V
230 V

Depth 1.7 in (4.4 cm)

Net Weight 4.4 lb(US) (2 kg)

Mounting Location Side

Mounting preference No preference

Input Plug Type IEC 60320 C20

Mounting Mode Rack-mounted

Rack units 0U

Mounting position Vertical

Max line current 16 A

Input current limits 16 A

Load Capacity 3680 VA

Input Frequency 50/60 Hz

Outlet type and quantity 15 IEC 60320 C13

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| | |
|----------------------------------------------|--------------------------------------------------------------|
| Product Certifications | cUL Listed CE Queensland Australia UL Listed VDE |
| Standards | UL 60950 |
| Ambient Air Temperature for Operation | 32.0000000000...113.0000000000 °F (0...45 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13.0000000000...149.0000000000 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|--------------------------|--------------|
| GTIN | 731304226369 |
| Country of origin | IN |

Packing Units

| | |
|-------------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25.1 in (63.8 cm) |
| Package 1 Width | 6.6 in (16.8 cm) |
| Package 1 Length | 5.7 in (14.6 cm) |
| Package 1 Weight | 6.005 lb(US) (2.724 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile

[End of Life Information](#)

California Proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov