



Key Features

Full HD 1080p resolution | 3,500 Lumen Brightness
 | Long Lamp Life | Powered USB Port | Reduced
 Input Latency



Product Description

Perfect for home entertainment, the ViewSonic® PX700HD projector features 3,500 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An ultra-low input latency provides faster frame-by-frame action, while a Sports Mode feature delivers stunning detail so you can enjoy fast-action sports on the big screen. Full HD 3D compatibility lets you enjoy 3D movies and games. What's more, an energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours*. Extensive connectivity options include dual HDMI inputs and USB power, making the PX700HD a versatile home entertainment solution.

*Lamp life may vary based on actual usage and other factors.




01. IR remote sensor
 02. Projection lens
 03. Elevation foot
 04. Focus / zoom rings

05. USB type Mini B
 06. USB 2.0 Type A (powered)
 07. HDMI (x2)
 08. AC In

09. VGA
 10. RS232
 11. Monitor Out
 12. Control Panel


13. Kensington® Lock Slot
 14. Audio In/Out



1920 x 1080
RESOLUTION



3,500 ANSI
LUMENS



1.5 - 1.65
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	Full HD 1080p
Resolution:	1920 x 1080
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.5 - 25.0 ft / 0.7 - 7.6 m
Throw Ratio:	1.5 - 1.65
Keystone:	Vertical ($\pm 40^\circ$)
Lens:	1.1x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	12,000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1200
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1200
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI(2), VGA In(1), Mini USB(1)

Audio:

Internal Speakers:	2W
--------------------	----

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	350W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	8.1
Gross (lbs):	10.8

Weight (metric):

Net (kg):	3.7
Gross (kg):	4.9

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.4 x 8.2 x 13.2
Physical (in.):	13.1 x 5.3 x 10.3

Dimensions (metric) (WxHxD):

Packaging (mm):	417.0 x 207.0 x 336.0
Physical (mm):	332.0 x 135.0 x 261.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PX700HD projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907929119

Accessories:

HB10B, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PM-FCP, PRJ-EE-07-03, RLC-116, VC10, VCB10