

VG730m

17" DIGITAL MEDIA GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Full multimedia performance.

The ViewSonic® 17" VG730m offers a feature-rich, price-performance solution for today's business applications with mixed data, audio, graphics and video content. It's equipped with features not normally offered in value-positioned displays. With its FAST 8MS VIDEO RESPONSE, the VG730m provides ULTRA-SMOOTH STREAMING VIDEO and scrolling text. OptiSync® analog and digital inputs ensure seamless compatibility with the installed base of VGA-output sources as well as pure digital DVI connectivity. Advanced ergonomic functions such as HEIGHT ADJUST AND SWIVEL ALLOW FOR ERGONOMIC FLEXIBILITY. Integrated stereo speakers provide a rich, uncluttered multimedia experience. For a no-compromise display solution on a strict business budget, choose the endless possibilities of the VG730m.

8MS RESPONSE FOR MULTIMEDIA EXCELLENCE

- > **ClearMotiv® 8ms video response time**
Fast 8ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **High brightness and contrast ratio**
280-nit brightness (typ) and 600:1 contrast ratio (typ) for rich, detailed images.
- > **1280x1024 optimum resolution**
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **AutoTune® Function**
Automatically optimizes display settings without requiring user adjustments.
- > **Height adjustment and wall-mount versatility**
Ergonomic flexibility with height adjustment and 360° swivel base and VESA® wall-mount interface.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **Windows Vista approved**
- > **PC and Mac® compatible**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic®
See the difference® 

VG730m

17" DIGITAL MEDIA GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST



360° SWIVEL



HEIGHT ADJUST



TILT



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14824-00B-01/10] VG730m-1

LCD	Type	17" color TFT active matrix SXGA LCD
	Display Area	13.3" horizontal x 10.6" vertical; 17.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	600:1 (typ)
	Viewing Angles	170° horizontal, 155° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	280 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _H : 24~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac**	Power Mac™ G3/G4/G5 up to 1280x1024
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
AUDIO	Speakers	2x1.5-watt
	Amplifier	1.5-watt
CONTROLS	Basic	Power, 1, down, up, 2, mute
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K, 5400K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING	Temperature	32~104°F (0~40°C)
CONDITIONS	Humidity	10~90% (non-condensing)
DIMENSIONS	Physical with stand	15.2" x 18.7" x 9" (386.8mm x 475.2mm x 230mm)
	Physical without stand	15.2" x 14.4" x 2.6" (386.8mm x 366.6mm x 67mm)
(W x H x D)		
WEIGHT	Net with stand	11.1 lb. (5.0 kg)
	Net without stand	8.2 lb. (3.7 kg)
	Gross with stand	15.4 lb. (7.0 kg)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, GS, ICES 003, TUV-S, ERGO, TCO'03, GOST-R, SASO, BSMI, CCC, PSB, C-TICK, RoHS
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS		LCD display, VGA cable (DVI cable not included), power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on parts, labor and backlight

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com