

# Product data sheet

Specifications



## APC Rack PDU 9000 Switched, ZeroU, 16A, 100-240V, (21) C13/C15 & (3) C19/C21, Japan

APDU9959J

### Overview

Lead time Usually in Stock

### Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

### Complementary

Input Voltage	200 V
Height	70.7 in (179.7 cm)
Width	2.2 in (5.5 cm)
Output Voltage	200 V
Depth	1.8 in (4.6 cm)
Net Weight	12.24 lb(US) (5.55 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60320 L6-20P
Mounting Mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	16 A
Acceptable Input Voltage	100...240 V
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	21C13/C15 3C19/C21

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Communication Network Type	10/100/1000BASE-T
----------------------------	-------------------

## Environment

---

Product Certifications	FCC part 15 class A PSE
------------------------	----------------------------

---

Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
---------------------------------------	--------------------------

---

Relative Humidity	5...95 %
-------------------	----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
-------------------------------------	----------------------------

---

Storage Relative Humidity	5...95 %
---------------------------	----------

---

Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
------------------	--

## Ordering and shipping details

---

GTIN	731304412922
------	--------------

---

Country of origin	IN
-------------------	----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	78.8 in (200.2 cm)
------------------	--------------------

---

Package 1 Width	4.5 in (11.4 cm)
-----------------	------------------

---

Package 1 Length	6.5 in (16.5 cm)
------------------	------------------

---

Package 1 Weight	17.33 lb(US) (7.86 kg)
------------------	------------------------

## Contractual warranty

---

Warranty	3 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)