

# Product data sheet

Specifications



## APC NetShelter Rack PDU Advanced Gen 2, Switched, 3Phase, 22.1kW 400V 32A or 17.3kW 415V 30A, 530P6, 48 Outlet

APDU11350SW

### Overview

Lead time Usually in Stock

### Main

Colour Black

Product or component type PDU

PDU type Switched

Cord length 9.8 ft (3 m)

### Complementary

Input Voltage 415 V 3 phases  
400 V 3 phases

Height 70.08 in (1780 mm)

Width 2.2 in (56 mm)

Output Voltage 240 V

Depth 3.0 in (75 mm)

Net weight 21.2 lb(US) (9.6 kg)

Mounting location Side

Mounting preference No preference

Input Plug Type IEC 60309 30 A 3P + N + PE

Mounting mode Rack-mounted

Rack units 0U

Mounting position Vertical

Communication port protocol 1000BASE-T  
10/100BASE-T

[In] rated current 24 A

Permissible voltage 200...240 V  
346...415 V

Input current limits 30 A

Load capacity 17300 VA

Network frequency 50/60 Hz

Outlet type and quantity 24 C13/C15/C19/C21  
24C13/C15

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Product certifications	UKCA TAA compliance
Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
IP degree of protection	IP44
Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.000000000...15240.000000000 m)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	77.95 in (198 cm)
Package 1 Width	5.20 in (13.2 cm)
Package 1 Length	10.31 in (26.2 cm)
Package 1 Weight	27.8 lb(US) (12.6 kg)

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

#### Materials and Substances

[EU RoHS Directive](#)

Compliant with Exemptions

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

### Use Again

#### Repack and remanufacture

Take-back

No

Image of product / Alternate images

Alternative

---





