

C1C

HD Resolution Indoor Wi-Fi Camera

As Sharp-Eyed as an Owl

This is where smart home security meets sharp night vision. Designed for simple and quick installation, the C1C's super night vision safeguards every corner even in places without illumination.





Supports 2.4GHz Wi-Fi



110°/130° Wide-Angle Lens



Two-Way Talk



Infrared Night Vision (Up to 12meters)



Supports MicroSD Card (Up to 256GB)





Always in the Know

You can't always be there – or can you? Featuring motion detection, the C1C watches over your property and immediately alerts you on your mobile device with an captured image when anything unusual happens. (Instant alerts must be activated manually.)

Communication Anytime, Anywhere

Talk to your loved ones and deter unwelcome strangers – all by using the C1C's two-way communication feature. Using the EZVIZ App on your mobile device, you can easily and conveniently enjoy communication wherever you might be.





Plug, Clamp and Go

A magnetic base and mounting kits make installation a breeze. Just place the C1C on the shelf or clamp it to the wall or ceiling, and voila! Once set up, you can manually adjust its position to monitor just about anywhere.



Specifications 720p: CS-C1C-D0-1D1WFR/ 1080p: CS-C1C-D0-1D2WFR

Camera

Image Sensor 720p: 1/4" Progressive Scan CMOS

1080p: 1/2.9" Progressive Scan CMOS

Shutter Speed Self-adaptive shutter

Lens 720p: 2.8mm, view angle:92° (Horizontal), 110° (Diagonal)

1080p: 2.8mm, view angle:106° (Horizontal), 130° (Diagonal)

Lens Mount M12

Day & Night IR-cut filter with auto-switching

DNR 3D DNR WDR Digital WDR

Compression

Video Compression H.264

H.264 Type Main profile

Video Bit Rate 720p : HD; Standard; Basic. Adaptive bit rate.

1080p: Ultra-HD; HD; Standard. Adaptive bit rate.

Audio Bit Rate Self-adaptive

Max. Bitrate 2M

Network

Smart Alarm Motion detection

Wi-Fi Pairing AP pairing

Protocol EZVIZ cloud proprietary protocol Interface Protocol EZVIZ cloud proprietary protocol

General Features Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image,

Password Protection, Watermark

Interface

Storage MicroSD card slot (Max. 256G)

Power Micro USB

Wi-Fi

Standard IEEE802.11b, 802.11g, 802.11n

Frequency Range 2.4 GHz ~ 2.4835 GHz

Channel Bandwidth Supports 20MHz

Security 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Transmission Rate 11b: 11Mbps,11g:54Mbps,11n:72Mbps

General

Power Supply DC 5V±10%

Power Consumption MAX. 4.0 W

IR Range MAX. 12meters(39.37ft)

Produtct Dimensions 64mm x 64mm x 103mm(2.52 " x 2.52 " x 4.06 ")

Packaging Dimensions 123mm x 79mm x 125.5mm(4.84 " x 3.11 " x 4.94 ")

Suttle Weight 96g(0.21lbs)

Image

Max. Resolution 720p : 1280 x 720

1080p: 1920 x 1080

Frame Rate Max:20fps; Self-adaptive during network transmission

Package Contents:

- IP Camera
- 3-Meter (10-foot) USB Cable
- Power Adapter
- 2 Foam Stickers
- Metal Plate(3.5mm Hole Diameter)
- Quick Start Guide

Requirements

- 10 - 45°C (14 - 113°F) Humidity 95% or less (non-condensing)

Certificates

FCC / CE / UL / REACH / WEEE / RoHS

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd.

Other brands and product names are trademarks or registered trademarks of their respective holders.