

3 m (9.8 ft.) HDMI to DisplayPort Cable - 4K 30Hz

Product ID: HD2DPMM3M



This 3 m (10ft.) HDMI to DisplayPort cable with USB power lets you connect an HDMI video source, such as your laptop, desktop, Blu-ray TM player, or camera, to a DisplayPort monitor or projector without the need for additional video cables. The adapter cable features male connectors enabling you to connect your video source directly to the display, with no need for additional adapters or cables.

Convenient Connectivity

The active HDMI 1.4 to DisplayPort 1.2 converter cable offers plug-and-play installation, providing a hassle-free setup with no software or drivers to install. The adapter is powered via a USB port, avoiding the need for an extra power adapter.

Astonishing picture quality

With support for 4K at 30Hz, you get a sharp, crisp picture that's richer and more true-to-life than traditional HD, with far greater detail. The HDMI to DisplayPort Adapter cable delivers Ultra HD content to your DisplayPort monitor and supports 7.1 channel surround sound audio.



Data Sheet

The HDMI to DisplayPort adapter is backward compatible with 1080p and 1440p displays, which makes it a great accessory to future-proof your existing setup for 4K video.

The Choice of IT Pros Since 1985

StarTech.com conducts thorough compatibility and performance testing on all our products to ensure we are meeting or exceeding industry standards and providing high-quality products to IT Professionals. Our local StarTech.com Technical Advisors have broad product expertise and work directly with our StarTech.com Engineers to provide support for our customers both pre and post-sales.

The HD2DPMM3M is backed by a StarTech.com 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Use in your boardroom or office workstations for installations requiring 3 meters (9.8 feet) of cable
- Connect your HDMI computer to a DisplayPort monitor
- Viewing video footage from your HDMI source on a DisplayPort monitor

Features

- Provides a convenient plug-and-play solution with no additional cables required
- Active HDMI to DisplayPort conversion transmits high-definition audio and video from your computer to a DP monitor
- Deliver astonishing picture quality with support for video resolutions up to Ultra HD 4K



Data Sheet

Hardware Active or Passive Adapter Active Audio Yes AV Input HDMI - 1.4 AV Output DisplayPort Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications DisplayPort - 7.1 Channel Audio Maximum Digital Resolutions 3840 x2160 Supported Resolutions Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Video Revision HDMI 1.4 Connector B 1 - HDMI (19 pin) Male Input Connector B 1 - DisplayPort (20 pin) Male Output Power Power Source USB-Powered Environmental Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature 10°C to 55°C (14°F to 131°F) Physical Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Packaging Package Height 20.000 Package Width 20.00		Warranty	2 Years
AV Input AV Output DisplayPort Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications DisplayPort - 7.1 Channel Audio Maximum Digital Resolutions 3840 x2160 Supported Resolutions DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - HDMI (19 pin) Male Input Connector B 1 - DisplayPort (20 pin) Male Output Power Power Overse USB-Powered Environmental Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400	Hardware	Active or Passive Adapter	Active
AV Output Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications Maximum Digital Resolutions Supported Resolutions Supported Resolutions DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Additional resolutions and refresh rates may be supported Additional resolutions and refresh rates may be supported Yes Connector (s) Connector A Connector B Connector B Connector B Connector B Connector B Conperting Temperature VSS-Powered Environmental Humidity S-90% RH (Non-condensing) Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature Color Storage Temperature Plastic Product Height Product Height Product Height 10.600 Product Length Product Width 20.900 Weight of Product Package Height 165.400 Package Height 10.600 Package Width Package Width Package Width Package Width Package Width Package Width Package Weight 170.400		Audio	Yes
Chipset ID MegaChips Technology - STDP2600		AV Input	HDMI - 1.4
Performance Audio Specifications DisplayPort - 7.1 Channel Audio Maximum Digital Resolutions 3840 x2160 Supported Resolutions DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A Connector B 1 - HDMI (19 pin) Male Input Connector B 1 - DisplayPort (20 pin) Male Output Power Power Source USB-Powered Environmental Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		AV Output	DisplayPort
Maximum Digital Resolutions Supported Resolutions DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector(s) Connector A 1 - HDMI (19 pin) Male Input Connector B 1 - DisplayPort (20 pin) Male Output Power Power Source USB-Powered Environmental Humidity S~90% RH (Non-condensing) Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature 10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Height 20.900 Weight of Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length Package Length Package Width 218.000 Shipping (Package) Weight 170.400		Chipset ID	MegaChips Technology - STDP2600
Supported Resolutions DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector B 1 - HDMI (19 pin) Male Input Connector B 1 - DisplayPort (20 pin) Male Output Power Power Source USB-Powered Environmental Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Height 10.600 Product Width 20.900 Weight of Product 165.400 Packaging Information Package Height 20.000 Package Uidth Package Width Shipping (Package) Weight 170.400	Performance	Audio Specifications	DisplayPort - 7.1 Channel Audio
Additional resolutions and refresh rates may be supported Video Revision Wide Screen Supported Yes Connector(s) Connector A Connector B 1 - DisplayPort (20 pin) Male Output Power Power Source USB-Powered Environmental Humidity Operating Temperature O°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Product Height Product Length Product Length Product Width 20,900 Weight of Product 165.400 Package Height Package Length Package Width Shipping (Package) Weight 170.400		Maximum Digital Resolutions	3840 x2160
Connector(s)Connector A Connector B1 - HDMI (19 pin) Male InputPowerPower SourceUSB-PoweredEnvironmentalHumidity5~90% RH (Non-condensing)Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 55°C (14°F to 131°F)Physical CharacteristicsMaterialPlasticProduct Height10.600Product Length300 cm [118.1 in]Product Width20.900Weight of Product165.400Packaging InformationPackage Height20.000Package Length20.000Package Width218.000Shipping (Package) Weight170.400		Supported Resolutions	
Connector(s)Connector A Connector B1 - HDMI (19 pin) Male InputPowerPower SourceUSB-PoweredEnvironmentalHumidity5~90% RH (Non-condensing)Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 55°C (14°F to 131°F)Physical CharacteristicsColorBlackMaterial Product Height10.600Product Width Product Width300 cm [118.1 in]Product Width Weight of Product20.900Meight of Product165.400Packaging InformationPackage Height20.000Package Length Package Width Shipping (Package) Weight218.000Shipping (Package) Weight170.400		Video Revision	HDMI 1.4
PowerConnector B1 - DisplayPort (20 pin) Male OutputPowerPower SourceUSB-PoweredEnvironmentalHumidity5~90% RH (Non-condensing)Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 55°C (14°F to 131°F)Physical CharacteristicsMaterialPlasticProduct Height10.600Product Length300 cm [118.1 in]Product Width20.900Weight of Product165.400Packaging InformationPackage Height20.000Package Length200.000Package Width218.000Shipping (Package) Weight170.400		Wide Screen Supported	Yes
Power Power Source USB-Powered Environmental Humidity 5~90% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Height Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400	Connector(s)	Connector A	1 - HDMI (19 pin) Male Input
EnvironmentalHumidity5~90% RH (Non-condensing)Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 55°C (14°F to 131°F)Physical CharacteristicsColorBlackMaterialPlasticProduct Height10.600Product Length300 cm [118.1 in]Product Width20.900Weight of Product165.400Packaging InformationPackage Height20.000Package Length200.000Package Width218.000Shipping (Package) Weight170.400		Connector B	1 - DisplayPort (20 pin) Male Output
Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400	Power	Power Source	USB-Powered
Physical Characteristics Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400	Environmental	Humidity	5~90% RH (Non-condensing)
Physical CharacteristicsColorBlackMaterialPlasticProduct Height10.600Product Length300 cm [118.1 in]Product Width20.900Weight of Product165.400Packaging InformationPackage Height20.000Package Length200.000Package Width218.000Shipping (Package) Weight170.400		Operating Temperature	0°C to 70°C (32°F to 158°F)
Characteristics Material Plastic Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.990 Weight of Product 165.400 Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		Storage Temperature	-10°C to 55°C (14°F to 131°F)
Product Height 10.600 Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400	=	Color	Black
Product Length 300 cm [118.1 in] Product Width 20.900 Weight of Product 165.400 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		Material	Plastic
Product Width 20.900 Weight of Product 165.400 Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		Product Height	10.600
Packaging InformationPackage Height20.000Package Length200.000Package Width218.000Shipping (Package) Weight170.400		Product Length	300 cm [118.1 in]
Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		Product Width	20.900
Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 170.400		Weight of Product	165.400
Package Width 218.000 Shipping (Package) Weight 170.400		Package Height	20.000
Shipping (Package) Weight 170.400		Package Length	200.000
		Package Width	218.000
What's in the Box Included in Package 1 - HDMI to DisplayPort Cable		Shipping (Package) Weight	170.400
	What's in the Box	Included in Package	1 - HDMI to DisplayPort Cable

Product appearance and specifications are subject to change without notice.