

Product data sheet

Specifications



APC Smart-UPS X External Battery Pack, Rack/Tower 2U, 120Vdc, W/rail kit

SMX120RMBP2U

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually Ships within 2 Weeks

Main

| | |
|---------------------------|--|
| Product or Component Type | Battery |
| Number of rack unit | 2U |
| Battery Type | Lead-Acid battery |
| Provided Equipment | Installation guide Rack Mounting brackets |
| Range of Product | Smart-UPS Battery Systems |

Batteries & Runtime

| | |
|---------------------------|----------------------------|
| Battery blocks per string | 10 |
| Device mounting | Enclosed battery cartridge |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| RBC Quantity | 2 |
| Battery Voltage | 120 V |
| Replacement battery | APCRBC118 |

Physical

| | |
|----------------|--------------------------|
| Color | Black |
| Height | 3.3 in (8.5 cm) |
| Width | 17.008 in (43.2 cm) |
| Depth | 26.3 in (66.7 cm) |
| Net Weight | 124.25 lb(US) (56.36 kg) |
| Mounting Mode | Rack-mounted |
| USB compatible | No |

Environmental

| | |
|---------------------------------------|---|
| Ambient Air Temperature for Operation | 32.0000000000...104.0000000000 °F (0...40 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-------------------------------------|--|
| Ambient Air Temperature for Storage | 5.0000000000...113.0000000000 °F (-15...45 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304295839 |
| Returnability | No |
| Country of origin | PH |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.6 in (24.3 cm) |
| Package 1 Width | 23.5 in (59.6 cm) |
| Package 1 Length | 34.2 in (86.9 cm) |
| Package 1 Weight | 140.30 lb(US) (63.64 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 34.3 in (87 cm) |
| Package 2 Width | 39.4 in (100 cm) |
| Package 2 Length | 47.2 in (120 cm) |
| Package 2 Weight | 859.8 lb(US) (390 kg) |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov