# Product data sheet

Specifications





APC Smart-UPS On-Line, 10kVA/ 10kW, Rackmount 6U, 208V, 4x L6-20R+2x L6-30R NEMA outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit

SRT10KRMXLT

#### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main	
Main Input Voltage	208 V
Product or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Kw Rating	10000 W
Rated power in VA	10000 VA
output connection type	4 NEMA L6-20R 2 NEMA L6-30R
Output connector type	Hard Wire 3-wire (2PH + G) 1
Number of rack unit	6U
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Temperature Probe USB cable Warranty card Web/SNMP Management Card
Range of Product	Smart-UPS On-Line

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	Lead-Acid battery
Included Battery Modules	0
Typical recharge time	1.5 h
RBC Quantity	2
Battery Voltage	+/-192 V (split battery referenced to neutral)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Battery Charge Power (Watts)	1191 W rated
Battery life	35 year(s)
Replacement battery	APCRBC140 ☐
Extendable Run Time	1

### General

Topology	Double Conversion Online
product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### **Physical**

,	
color	Black
Height	10.4 in (26.3 cm)
Width	17.008 in (43.2 cm)
Depth	28.1 in (71.5 cm)
Net Weight	245.99 lb(US) (111.58 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

# Input

Input Frequency	40 - 70 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (2PH + G)
Efficiency at full load	100275 V adjustable (half load)

# Output

Maximum configurable power in VA	10000 VA
Max Configurable Power (Watts)	10000 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Waveform Type	Sine wave
Harmonic distortion	Less than 2%
Crest factor	3:1
Bypass type	Internal Bypass (Automatic and Manual)

### Conformance

ENERGY STAR V2.0 (USA) FCC part 15 class A NOM UL 1778 **Product Certifications** 

#### **Environmental**

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
Acoustic level	55 dBA
Online Thermal Dissipation	2490 Btu/h
IP degree of protection	IP20

### **Communications & Management**

Free slots	1
Pre-Installed SmartSlot™ Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

### **Surge Protection and Filtering**

Surge energy rating 480

# Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304292692
Returnability	No
Country of origin	PH

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.1 in (46.1 cm)
Package 1 Width	39.4 in (100 cm)
Package 1 Length	23.6 in (60 cm)
Package 1 Weight	286.006 lb(US) (129.73 kg)

### **Contractual warranty**

Warranty 3 years repair or replace (excluding battery) and 2 years for battery



**Green Premium** TM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

#### Resource performance

**Energy Efficient Product** 

Take-Back Program Available

#### Well-being performance

Mercury Free

Rohs Exemption Information

Yes

#### **Environmental Certifications**

Energy Star®

ENERGY STAR UPS V2.0 (USA)

#### **Certifications & Standards**

**Reach Regulation REACh Declaration Eu Rohs Directive** Compliant with Exemptions **Environmental Disclosure Product Environmental Profile Circularity Profile** End of Life Information California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov